

SPECIFICATIONS

FEATURES / SPECS	
MOTOR	PREMIUM 6.0HP SERIES WOUND
SWITCH	500A SEALED CONTACTOR
THERMAL LIMITER	MOTOR OVERHEAT PROTECTION WITH LED FEEDBACK LIGHT & AUTO RECONNECT
CONTROLLER	WIRED: HAND CONTROL WITH 12' LEAD INCLUDED WIRELESS: OPTIONAL & AVAILABLE 20156
POWER UNIT	REMOTE MOUNTABLE
BATTERY LEADS	6' W/HIGH HEAT/ABRASION RESISTANT SHEATHING
GEAR TRAIN	3 STAGE PLANETARY
GEAR RATIO	262:1
GEAR BOX	CLOCKABLE TO ROTATE SHIFTER (contact for instructions)
CLUTCH	FREESPOOLING
BRAKE	AUTOMATIC LOAD HOLD IN DRUM
DRUM DIA X L	2.5" X 9" (63 X 224mm)
OVERALL DIMENSIONS (LxWxH)	23x6.7x9.8" (552x170x250mm)
MOUNTING BOLT PATTERN	10x4.5"
WARRANTY	LIMITED LIFETIME
BATTERY RECOMMENDATION	650CCA

PULL, SPEED, AMPS

LINE PULL LBS	LINE SPEED FT/MIN	CURRENT A
0	25.6	65
2000	12.5	100
4000	8.9	130
8000	7.3	200
10000	6.4	230
12500	6	290

LINE PULL AND ROPE CAPACITY IN LAYER

LAYER	RATED LINE PULL LBS	TOTAL ROPE ON DRUM FT
1	12500	15.75
2	10750	36.4
3	9460	61.3
4	8040	90