

SPECIFICATIONS

FEATURES & SPECS	
MOTOR	SERIES WOUND 12vDC 5.5hp
SWITCH	450 AMP SEALED CONTACTOR
CONTROLLER	WIRED: HAND CONTROL WITH 12' LEAD INCLUDED WIRELESS: OPTIONAL & AVAILABLE 20156
POWER UNIT	MULTI-MOUNT / REMOTE MOUNTABLE
BATTERY LEADS	6'
GEAR TRAIN	3-STAGE PLANETARY
GEAR RATIO	265:1
GEAR BOX	CLOCKABLE TO ROTATE SHIFTER (contact for instructions)
CLUTCH	FREESPOOLING
BRAKE	AUTOMATIC LOAD HOLD IN DRUM
DRUM DIA x L	2.5" x 8.8" (63.5 x 223.5mm)
OVERALL DIMENSIONS(LxWxH)	21.7" x 6.3" X 8.6" (551 x 160 x 218mm)
MOUNTING BOLT PATTERN	10" x 4.5"
WARRANTY	2 YEAR LIMITED
BATTERY RECOMMENDATION	650CCA

PULL, SPEED, AMPS

LINE PULL LBS	SPEED FT/MIN	CURRENT (A)
0	24.6	80
2000	14.4	180
4000	10.6	240
6000	8.5	280
8000	7	330
9500	6.4	380

LINE PULL & ROPE CAPACITY IN LAYER

LAYER	RATED LINE PULL LBS	TOTAL ROPE ON DRUM FT
1	9500	16.2
2	7700	39
3	6500	68.2
4	5700	100