

SPECIFICATIONS

FEATURES / SPECS	
MOTOR	SERIES WOUND 6.0 HP 12vDC
SWITCH	450A SEALED CONTACTOR
CONTROLLER	WIRED: HAND CONTROL WITH 12' LEAD INCLUDED WIRELESS: OPTIONAL & AVAILABLE 20156
POWER UNIT	MULTI-MOUNT / REMOTE MOUNTABLE
BATTERY LEADS	6'
GEAR TRAIN	3 STAGE PLANETARY
GEAR RATIO	265:1
GEAR BOX	CLOCKABLE TO ROTATE SHIFTER (contact for instructions)
CLUTCH	FREESPOOLING
BRAKE	AUTOMATIC LOAD HOLD IN DRUM
DRUM DIA X L	2.5" X 8.8" (63.5mm X 223.5mm)
OVERALL DIMENSIONS(LxWxH)	21.7" x 6.3" X 8.6" (551 x 160 x 218mm)
MOUNTING BOLT PATTERN	10 X 4.5"
WARRANTY	2 YEAR LIMITED
BATTERY RECOMMENDATION	650CCA

PULL, SPEED, AMPS

LINE PULL LBS	LINE SPEED FT/MIN	CURRENT A
0	21.3	65
2000	11.5	126
4000	9.4	175
6000	7.9	230
8000	6.5	280
10000	5.8	355
12000	4.4	400

LINE PULL & ROPE CAPACITY IN LAYER

LAYER	RATED LINE PULL LBS	TOTAL ROPE ON DRUM FT
1	12000	17
2	9210	41
3	8030	71
4	6894	90