

SPECIFICATIONS

FEATURES / SPECS	
MOTOR	PREMIUM 6.8HP SERIES WOUND
SWITCH	500A SEALED CONTACTOR THERMAL LIMITER MOTOR OVERHEAT PROTECTION WITH LED FEEDBACK LIGHT & AUTO RECONNECT CONTROLLER
CONTROLLER	WIRED: HAND CONTROL WITH 12' LEAD INCLUDED WIRELESS: OPTIONAL & AVAILABLE 20156
POWER UNIT	REMOTE MOUNTABLE
BATTERY LEADS	LEADS 6' W/HIGH HEAT/ABRASION RESISTANT SHEATHING
GEAR TRAIN	3 STAGE PLANETARY
GEAR RATIO	262:1
GEAR BOX	CLOCKABLE TO ROTATE SHIFTER (contact for instructions)
CLUTCH	FREESPOOLING
BRAKE	AUTOMATIC LOAD HOLD IN DRUM
DRUM DIA X L	2.5" X 9" (63 X 224mm)
OVERALL DIMENSIONS(LxWxH)	23x6.7x9.8" (552x170x250mm)
MOUNTING BOLT PATTERN	10 X 4.5"
WARRANTY	LIMITED LIFETIME
BATTERY RECOMMENDATION	650CCA

View [other winches & accessories](#) made by [Bulldog Winch](#) on our [website](#).