

# Installation Instructions

## 8891024 & 8891025 LED Dashboard Mount Strobe Lights



\* 12-24V, 0.4 Amps @ 12V

### Installation

Choose windshield location  
Clean windshield and dashboard surface with alcohol  
Loosen 2 sets of screws on each side and adjust tilt to match angle of windshield. Once correct angle is found, secure screws.

Choose mounting option:

1. Suction cup
2. Velcro

Attach light

### Operation

Insert power plug into vehicle accessory power port  
Push power on/off switch  
Push flash pattern selector switch for next pattern

FP#	Flash Patterns
1	Random 1
2	Side-to-Side Alt. Single
3	Side-to-Side Alt. Double
4	Side-to-Side Alt. Triple
5	Side-to-Side Alt. Quint
6	Side-to-Side Alt. Hold
7	Side-to-Side Alt. Burst
8	Side-to-Side Alt. Mega
9	Side-to-Side Alt. Ultra
10	Synchro Flash
11	Synchro Flash Triple
12	Synchro Flash Mega
13	Synchro Flash Ultra 1
14	Synchro Flash Ultra 2
15	Random 2
16	Random 3
17	Steady DS, Dbl. Flash PS
18	Steady PS, Dbl. Flash DS
19	Off

### WARNING

Do not block airbags with power cord.



8891025  
Shown powered on

### WARNING

Do not look directly into LEDs while in operation; this may cause momentary blindness and/or eye damage.