



## Hydraulic Motor With 4-Bolt Mount/NPT Threads And 11.3 Cubic Inches Displacement

**Buyers Part Number: CM054P**

**Buyers Products Hydraulic Motors are designed to be economical, compact, and powerful.**

- Designed to be economical, efficient, compact, and powerful.
- Ideal for powering medium-duty applications such as compressors, augers, winches, cranes, and spreaders.
- Industry-proven spool valve design.
- State-of-the-art gerotors.
- Excellent at providing a high degree of start-up torque or the right mixture of torque and flow rate.

### Specifications

<b>Compares To</b>	101-1005-009	<b>Displacement</b>	11.3 in. <sup>2</sup>
<b>Flow (Continuous)</b>	15 GPM	<b>Flow (Intermittent)</b>	20 GPM
<b>Input Mount Type</b>	4 Bolt	<b>Material</b>	Cast Iron
<b>Maximum Case Pressure (Without Case Drain)</b>	1500 PSI	<b>Maximum Speed (Continuous)</b>	304 RPM
<b>Maximum Speed at Continuous Flow</b>	304 RPM	<b>Maximum Speed at Intermittent Flow</b>	405 RPM
<b>Minimum Starting Torque (Continuous Pressure)</b>	1870 Inch Pound	<b>Minimum Starting Torque (Intermittent Pressure)</b>	2590 Inch Pound
<b>Pilot Diameter</b>	1.75"	<b>Port Size</b>	1/2 NPT
<b>Pressure ? Bar (Continuous)</b>	1600 PSI	<b>Pressure ? Bar (Intermittent)</b>	2150 PSI
<b>Shaft Keyway</b>	0.25"	<b>Shaft Size</b>	1.00"
<b>Shaft Type</b>	Straight	<b>Torque Rating (Continuous)</b>	2343 Inch Pound
<b>Torque Rating (Intermittent)</b>	2590 Inch Pound	<b>Shipping Weight</b>	14.27 lb