



Replacement 2-Bolt 24.9 Cubic Inch Hydraulic Motor with NPT Threads

Buyers Part Number: CM092P

Buyers Products Hydraulic Motors are designed to be economical, compact, and powerful.

- Designed to be economical, efficient, compact, and powerful.
- Ideal for powering medium-duty applications such as compressors, augers, winches, cranes, and spreaders.
- Industry-proven spool valve design.
- State-of-the-art gerotors.
- Excellent at providing a high degree of start-up torque or the right mixture of torque and flow rate.

Specifications

Displacement	24.9 in. ²	Flow (Continuous)	20 GPM
Flow (Intermittent)	25 GPM	Input Mount Type	2 Bolt
Material	Cast Iron	Maximum Case Pressure (Without Case Drain)	1500 PSI
Maximum Speed (Continuous)	152 RPM	Maximum Speed at Continuous Flow	152 RPM
Maximum Speed at Intermittent Flow	130 RPM	Minimum Starting Torque (Continuous Pressure)	3130 Inch Pound
Minimum Starting Torque (Intermittent Pressure)	3900 Inch Pound	Pilot Diameter	3.25"
Port Size	1/2 NPT	Pressure ? Bar (Continuous)	1050 PSI
Pressure ? Bar (Intermittent)	1350 PSI	Shaft Keyway	0.25"
Shaft Size	1.00"	Shaft Type	Straight
Torque Rating (Continuous)	2920 Inch Pound	Torque Rating (Intermittent)	3900 Inch Pound
Shipping Weight	23.17 lb		