



MAIN SPECS



CAPACITIES

Payload Distributed Capacity	1000 lbs
Tie-down Load Rating	400 lbs per tie-down
Bearing Load Rating	Combined Load Rating of Bearings = 56,476
Load	8 @ 4700 ea./12 @ 1573 ea.
Carrier	N/A
Side-Thrust	N/A
Plus-Nut Rating (1/8" steel)	6 - 8 @ 1500 lbs. each
Extension	100%

DIMENSIONS / WEIGHT RANGES

Length	48" - 95"
Width	22" - 48"
Profile/ Deck Height (inches)	3 3/4"
Side Rails	4" with 8" High Sides
Grab Rail	Based on width of unit
Weight	210 - 297 lbs

1000 lb capacity. 100% of the Cargo Tray Length Slides Out for Total Access to your Cargo. Real plywood deck with a TPO Rubber laminated surface for strength and durability. 20 Industrial Cam Follower Needle and Ball Bearings provide Dependable Lasting support for the Cargo You Haul In Your CargoGlide. Powder Coated Industrial 4" high extruded 6061-T6 Thick Aluminum Side Rails with integrated Full Perimeter Tie-Down Tracks and 4 Infinitely Adjustable Eyebolt Tie-Downs to make securing cargo easy and versatile. Includes 8" High Side Extensions on the first four feet of the rails at the cab end, helps contain more cargo.