




1981-87 Full Size Chevy GMC Grille Installation Instructions



TOOLS REQUIRED:

- Cutting disk or saw
- #15 Torx
- 13 mm Socket
- Phillips Screwdriver
- Silicone Sealer



STEP 1 Remove right and left headlight doors with a torx wrench.




STEP 2 Remove the grille. Screws are along the top, in the corners and in the center at the bottom.



STEP 3 Push the top of the grille in and pull bottom out to remove.



STEP 4 Press and twist parking light bulb socket to remove.




STEP 5 Remove parking lights from grille.




STEP 6 Cut off the top mounting tabs of each parking light unit (note tape line).



STEP 7 Slip the parking light under the L-shaped tab attached to the grille.




STEP 8 Attach the bottom L-shaped bracket with the screw provided in the kit.



STEP 9 Apply silicone around the top and bottom tabs to hold the light securely.




STEP 10 Install clips on the grille mounting brackets.



STEP 11 Install clips provided onto lower corners of the grille opening, if needed.



STEP 12 Reinstall the parking light bulb sockets in light housings.



STEP 13 Insert grille into opening by tipping it back, inserting the top first.



STEP 14 Center grille in opening, align the top middle screw with hole in grille insert and install. Continue by installing the 7 screws provided. Reinstall the headlight doors.