



# 2010 Ford F-150


## FX4 (Bolt Over)

**PART# 44741 (Brushed) 44742 - (Polished) 44743 - (Black) Upper**




### Hardware

- 2 - 10-24 x 2" Phillips head toggle bolt assemblies
- 8 - 10-24 x 1 1/4" Phillips head bolts
- 10 - 10-24 u-clips
- 2 - Upper Brackets
- 2 - Lower Brackets
- 2 - Top center Brackets
- 4 - Square Tabs



Upper Bracket

Lower Bracket is shorter length wise.



Showing the backside of stock grille shell.

Lower Bracket

Locate the 4 supplied [billet grille](#) brackets. Take note that there are upper and lower specific brackets. The upper brackets are slightly larger than the lower. Place supplied u-clips on the short end of all upper and lower brackets. Now attached brackets to billet grille using the supplied 10-24 x 1" bolts as shown above.

Next place the billet grille into the grille shell and center. Locate the supplied 10-24 x 1 1/4" bolts and push through the upper mounting holes in both the upper and lower brackets. Next place the 10-24 u-clips on the square tabs. Then attach the square tabs using the already placed 10-24 x 1 1/4" bolts.



Next you will be attaching the (2) center brackets. Place supplied u-clips on brackets as shown above. Push the supplied 10-24 x 2" bolts through the 2 upper center mounting tabs in billet grille. Next place the brackets and rotate as necessary to catch the backside plastic and then tighten. With all brackets in place check alignment and then tighten all hardware.

### Completed Installation

For installation of billet grilles that require cutting of the stock shell, proper tools, knowledge and skill are needed. Carriage Works is not responsible for care & Accuracy of the installation, only for Fit & Finish of its products. Use a qualified installer or contact original vendor for references to complete all instructions.

**NOTE:** Please adjust horizontal blades if irregular. This is the result of shipping and handling outside of Carriage Works control.  
Also Carriage Works Recommends applying a high quality automotive wax to maintain the original appearance.