

CARRICHS ACCESSORIES, LLC.

INSTALLATION GUIDE

FENDER TRIM FOR 2014 - 2015 CHEVROLET SILVERADO 1500 PART #FTCH105, FTCH106, FTCH205, FTCH206, FTCH406

REQUIRED TOOLS:

- Pliers
- T-15 Torx Screwdriver
- Phillips Screwdriver* (optional)

INCLUDED HARDWARE:

- Hooked Clips
- Clips with holes \subset
- Phillips Screws*




FRONT FENDER TRIM INSTRUCTIONS (NO-DRILL):

- 1. Using a T-15 Torx screwdriver to remove seven (7) T-15 Torx screws (Fig. 1). **Keep** existing T-15 Torx screws and washers for re-install later.
- 2. Place a correct fender trim (fitment sticker can be found on back of fender trim) over fender to be installed.
- 3. Slide a "clip with hole" through each slot on fender trim. There are seven (7) clips per front fender trim.
- 4. Use existing T-15 Torx screws and washers to tighten over "clip with hole".
- 5. Pull the other end of the clip with a pair of pliers and bend the clip toward the wheel well to secure the fender trim (Fig. 2).
- 6. Repeat step 1-5 for all seven (7) T-15 Torx screws on each front side.

REAR FENDER TRIM INSTRUCTIONS (NO-DRILL):

- 1. Place a correct fender trim (fitment sticker can be found on back of fender trim) over fender to be installed.
- 2. Slide a "hooked clip" through each slot on fender trim. There are seven (7) clips per rear fender trim.
- 3. Pull the other end of the clip with a pair of pliers and bend the clip toward the wheel well to secure the fender trim (Fig. 3).
- 4. Repeat step 1-3 for all seven clips per rear fender trim

Fig. 1



OPTIONAL FENDER TRIM INSTRUCTIONS (DRILL METHOD*):

- 1. Place a correct fender trim (fitment sticker can be found on back of fender trim) over fender to be installed.
- 2. Align fender trim properly onto fender and use 7/64 a bit to drill into fender well using the pre-drilled hole on fender trim for guidance (Fig. 4).
- 3. Use the provided screws to screw the fender trim to the fender using a phillips screwdriver.
- 4. Repeat step 1-3 for each and every fender trim.

