



Installation Instructions


T-Connector



Impreza Sport



C



D



E

TOOLS REQUIRED:

10mm Socket & Ratchet or 10mm Wrench, Trim Panel Remover, Drill (3/32" Drill Bit), 1/4" Socket, Wire Crimpers, Wire Cutters, Phillips Head Screwdriver, Test-probe

1. Open the rear tailgate to access the bolts that hold the taillights in place **A**. Remove the taillights on both the driver and passenger side of the vehicle **B**.
2. Behind the taillights, there will be connection points matching the ends of the T-Connector adapter on the back of each of the vehicle taillight housings. Beginning on the driver's side, separate the vehicle's wiring connectors, being careful not to break the locking tabs. Attach both ends of the T-Connector containing the **yellow** and **brown** wires. Be careful not to damage the locking tabs and be sure that connectors are fully inserted with locking tabs in place.
3. On the Driver's side, route the T-Connector end with the **green** wire and the wire with the 4-Flat connector down through the opening between the vehicle bumper and body.
4. Route harness containing the **green** wire underneath the vehicle up through the opening between the vehicle bumper and body to the passenger's side taillight pocket. Repeat step 2 using the T-Connector ends containing the **green** wire.

5. Locate a suitable grounding point on the driver's side near the connectors. Drill a 3/32" hole and secure **white** wire with eyelet using screw provided. Do not drill into any exposed surfaces.

⚠ CAUTION

Verify what is behind any surface prior to drilling to avoid damage to the vehicle and/or personal injury. Do not drill into any exposed surfaces.

6. From inside the vehicle, connect the **black** 12 ga. wire and the **red** wire from the T-Connector black box with the supplied yellow butt connector. Either route the **black** wire thru a grommet and along the exterior frame or follow the existing wiring along the thresholds into the engine compartment up to the battery avoiding areas that may pinch or break the wire **C**.

⚠ WARNING

If routing the wire thru a grommet and along the exterior of the vehicle, be careful to avoid any hot pipes, heat shields, the fuel tank or any other points that may pinch or break the wire.

7. Disconnect the vehicle's negative (-) battery cable. If not removed, remove the fuse from the yellow fuse holder (provided). After cutting the fuse holder wire **D**, attach the ring terminal and secure to the vehicle's Positive (+) battery cable **E**. Connect the other end of the fuse holder to the black 12 ga. wire, using the yellow butt connector (provided).

⚠ WARNING

Read and follow all warnings and cautions printed on the tow vehicle's battery. All connections must be complete for the T-Connector to function properly. Test and verify installation with a test light or trailer once installed. For initial test, reset vehicle electrical system by temporarily removing the key from the ignition.

8. Secure the remainder of the T-Connector harness with the cable ties provided, to prevent damage or rattling and being careful to avoid any areas that would pinch, cut or melt the wire.
9. On the Driver's side, mount the T-Connector black box using the double-sided tape provided. Secure the remainder of the T-Connector harness with the cable ties provided, to prevent damage or rattling and being careful to avoid any areas that would cut or pinch the wire.
10. Reinstall taillight assemblies and other items removed during installation, being careful not to pinch or cut the wires.

NOTE

Store 4-Flat in trunk area when not in use.

⚠ WARNING

Overloading circuit can cause fires. DO NOT exceed lower of vehicle manufacturer rating or:

- Max. stop/turn light: 1 per side (2.1 amps)
- Max. tail lights: (5.6 amps)

Read vehicle's owners manual & instruction sheet for additional information.