

Cognito Motorsports, Inc., GM 2000-2006 6-Lug Truck and SUV Pitman/Idler Arm Support Kit

****UTILITY PATENT US7,475,891 B2****

Introduction

- This application is for stock and lifted applications that use the factory steering center link in the factory location. Aftermarket steering stabilizers that do not mount in a factory location may interfere with this system.
- Installation requires a qualified mechanic.
- Read instructions carefully and study the pictures before attempting installation.
- Check the parts and any hardware packages against the parts list to assure that your kit is complete.
- Tools needed: 1 5/16" box end wrench, 24mm end wrench, qty. 2 of 15/16" box end wrench, 15mm socket, 7/8" socket or box end wrench.

Parts List

- 8197 Pitman arm bracket
- 8209 Idler arm bracket
- (2) 9/16" lock washer
- (2) 3/4"-5/8" rod ends
- (4) 5/8" jam nuts
- (2) Fine thread shank nuts (normally silver)
- (2) Coarse thread shank nuts (normally gold)
- Thread locker



Figure 1: Layout of parts

Instruction Set # 7047

Installation Instructions

1. If there is an existing skid plate and shroud at the front cross member of the vehicle, underneath the front of the engine, they should be removed with a 15mm socket to access the pitman and idler arms and set aside for re-installation later.
2. Unscrew the factory lock nuts that hold the drag link to the pitman and idler arms, using a 21mm socket, and discard them.
3. Unscrew the large nut holding the pitman arm to the steering box using a 1 5/16" boxed end wrench. Remove it and the large lock washer. Figure 5
4. Remove the nut holding the idler arm to the idler arm pivot with a 24mm boxed end wrench. Figure 3
5. Apply a small amount of thread locker on all of the threads on both of the 5/8"x 3/4" rod ends, then thread one 5/8" jam nut all the way on to both of the rod ends. Then insert the rod end through the 5/8" diameter hole on both the pitman and idler arm brackets as shown in Figure 2. Now thread a second jam nut on to both rod ends, but do not tighten at this time.
6. Insert one lock washer over each of the drag link studs, and then install the pitman and idler arm brackets on to the pivot ends where hardware was previously removed in steps 3 and 4, at the same time place the rod end which is connected to the Cognito Motorsports brackets over the drag link studs so that the lock washer is in between the Cognito rod end and the drag link.
7. Re-install the factory lock nut on the pivot stud of the idler arm that was removed in step 4. Re-install the factory lock washer and nut on the pivot shaft of the steering box that was removed in step 3. Do not tighten yet.
8. The gold shank nuts are for factory or coarse thread arms, and the silver shank nuts are for aftermarket or fine thread arms. Apply a small amount of thread locker on the threads of the shank nuts and insert a shank nut on to each of the drag link studs, passing through the rod ends and locking against the lock washer and drag link. Jam each support bracket in between the jam nuts. Tighten shank nuts with 7/8" socket and jam nuts with both 15/16" boxed end wrenches, to 60 ft-lb. Figure 4 & 6

Instruction Set # 7047

9. Tighten the factory hardware mentioned in Steps 3, 4 and 7 at this time. The hardware may not accommodate clearance to use a torque wrench, but need to be tightened as tight as possible with the box end of an end wrench, roughly 70 ft-lb on the idler arm side, and 120 ft-lb on the large pitman arm nut.
10. Re-install any other hardware for skid plate/shroud previously removed and tighten to factory specification.



Figure 2: Support brackets assembled

Instruction Set # 7047



Figure 3: idler arm



Figure 4: idler arm bracket installed

Instruction Set # 7047



Figure 5: pitman arm



Figure 6: pitman arm bracket installed

Instruction Set # 7047

Cognito Motorsports

Limited Lifetime Warranty

Cognito Motorsports warrants, to the original retail purchaser, that its suspension products are free from defects in workmanship and material for as long as the purchaser owns the vehicle on which the product was originally installed. Cognito Motorsports does not warrant the product for finish, alterations, modifications, and/or original installation contrary to specifications of Cognito Motorsports. Cognito Motorsports suspension products are not designed nor intended to be installed on vehicles used in race applications or for racing purposes or for similar activities involving abnormal abuse other than the vehicle was originally designed to handle or endure. (A "RACE" is defined as any contest between two or more vehicles, and/or contest of one or more vehicle against the clock, whether or not such contest is for a prize.)

This warranty is for a one-time replacement of each Cognito Motorsports product and does not cover any part that Cognito Motorsports has previously replaced under this warranty. This warranty does not include coverage for police or taxi vehicles, race vehicles, or vehicles used for government or commercial purposes. Also excluded from this warrant are sales outside of the United States of America. Alterations to the finish of the parts including but not limited to painting, powder coating, plating, and/or welding will void all warranties. Cognito Motorsports obligation under this warranty is limited to the repair or replacement, at Cognito Motorsports option of the defective product. Any and all costs of removal, installation or re-installation, freight charges, incidental or consequential damages are expressly excluded from this warranty.

This warranty excludes the following items: bushings, bumpstops, tie-rod ends, limiting straps, and heim joints. These parts are subject to wear and are not considered defective when worn. They are warranted for 60 days of purchase for defects in workmanship. Cognito Motorsports suspension components must be installed as a complete system. Any substitutions or exemptions of required components will immediately void the warranty. Some finish damage may happen to parts during shipping and is not covered under warranty. This warranty shall not apply to any product that had been subject to accident, negligence, alteration, abuse, or misuse. Cognito Motorsports does not warrant products not manufactured by Cognito Motorsports. Cognito Motorsports reserves the right to supersede, discontinue, or change the design, finish, part number and/or application of parts when deemed necessary by Cognito Motorsports without written notice, and in the sole and absolute discretion of Cognito Motorsports.

Warranty Claims

All warranty claims must be submitted through the original company of purchase. All claims must be shipped back to the original company of purchase with an approved RMA number listed as a reference on the shipping label and clearly printed on two opposing sides of the package(s); product in question must be inspected by Cognito Motorsports before replacement parts are shipped out.

Product Consumer Safety and Warning

The installation of this kit will modify the suspension of your vehicle and may cause it to handle significantly different than a factory equipped vehicle. Installing larger tires with modified suspension and increased ground clearance will significantly alter the handling characteristics of the vehicle, and may result in increased braking distances as well as changes in vehicle maneuverability and handling compared to the factory equipped vehicle. As with any vehicle, extreme caution and care must be used to prevent loss of control or roll-over during sharp turns or abrupt maneuvers. Always wear seat belts and drive safely, recognizing the reduced speeds and specialized driving techniques is required.

This suspension system will not strengthen nor reinforce the stock frame of the vehicle, nor will it increase rollover protection. It is necessary to periodically inspect all suspension and drive train components for tightness of fit or any damage. Installation of these parts will modify the height of the vehicle and will raise the center of gravity. Altered height modifications and off-road operation may increase your vehicle's susceptibility to roll over conditions and may cause serious injury or death. Many states regulate the height modification to each vehicle. Check the laws in your state for exact specifications. Height modifications may affect the reaction, ride, handling, and wear factor of your vehicle's components.

Failure to drive this vehicle safely may result in injury or death! Do not drive this vehicle unless you are familiar with its unique handling characteristics and are confident of your ability to maintain control under all driving conditions. Some modifications and combinations of modifications are not recommended, unsafe, and may not be permitted in your state. Consult your vehicle owner's manual, the instructions accompanying this product, and your state laws before undertaking these modifications. The owner of the modified vehicle and the qualified mechanic required to install this product are responsible for the legality and safety of the vehicle being modified.