Description

Part Number:	08-609-44	Grind Number:	305QIO8	
Lifter Type:	Hydraulic Roller			
Engine Family:	Chevrolet 262-400 C.I. 8 CYL. 1955-1998 THE ABSOLUTE LEADER IN VALVE TRAIN TECHNOLOGY			
Description:	HYDRAULIC - Recommended in larger c.i. and high compression applications. 3500+ stall.			
Cam Family:	4-PATTERN O.E. Hydraulic Roller Camshafts			
Specifications			Intake	Exhaust
RPM Range:	3300 to 7500	Valve Lash:	Hyd.	Hyd.
Valve Timing:	.006	Duration:	307 / 305	319 / 317
Lobe Separation:	108.5 / 107.5°	Duration @ .050" Lift:	255 / 253	265 / 263
Intake Centerline:	103 / 102°	Valve Lift:	.638 / .638	.622 / .622
		Lobe Lift:	.399 / .399	.389 / .389
Valve Timing @ .006 Lift:				
Closes Opens	Exhaust 47 / 47 ATDC 92 / 90 BBDC	103 / 102 BDC	Center Line Of In. Lobe BDC	Intake 49/49 Opens BTDC 78/76 Closes ABDC

Recommended Components

Installation Notes (These notes apply to the above recommended components with the trailing installation note numbers)