

ContiTrac™

EXCELLENT ALL-SEASON PERFORMANCE, RIDE AND COMFORT
WIDE, DEEP TREAD GROOVES AND A SOLID CENTER RIB PROVIDE
SMOOTH, STABLE HANDLING AND INCREASED TREAD LIFE.



UTQG:	TREAD:	TRACTION:	TEMPERATURE:
P255/70R15	420	A	A
ALL OTHER SIZES	520	A	B

FEATURES:	BENEFITS:
• Solid center rib	• Provides smooth, stable handling and increased tread life
• Wide, deep tread grooves	• Enhance resistance to hydroplaning for comfort and safety
• Optimized tread pitch sequencing	• Offers excellent durability
• Staggered tread blocks	• Provide biting traction for excellent all-season performance and light off-road use

ORIGINAL EQUIPMENT FITMENTS	RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER (in)	TIRE WEIGHT (KG)	TIRE WEIGHT (LB)	MAX. INFLATION PRESSURE (PSI)	OVERALL SECTION WIDTH (MEASURING RIM) (in)	APPROVED RIM WIDTHS (in)	TREAD DEPTH (in - 32nds)	REVS PER MILE
Ford	15	70	P225/70R15	100S	SL	BSW	15473440000	27.4	11.6	25.5	44	9.0 (6.5)	6.0 - 7.5	12/32	761
Ford			P225/70R15	100S	SL	OWL	15473450000	27.4	11.9	26.2	44	9.0 (6.5)	6.0 - 7.5	12/32	761
Ford	16	70	P235/70R16	104T	SL	OWL	15481000000	29.0	14.6	32.3	44	9.4 (7.0)	6.0 - 8.0	13/32	720
Ford			P235/70R16	104T	SL	BSW	15482500000	29.0	14.3	31.5	44	9.4 (7.0)	6.0 - 8.0	13/32	720
Ford	17	65	P255/65R17	108S	SL	OWL	15463460000	30.1	15.7	34.5	44	10.2 (7.5)	7.0 - 9.0	12/32	696
Ford		75	LT245/75R17	121/118S	E	BSW	04567490000	31.5	21.6	47.5	80	9.7 (7.0)	6.0 - 7.5	11/32	660
Ford		LT245/75R17	121/118S	SL	OWL	04567500000	31.5	21.6	47.4	80	9.7 (7.0)	6.0 - 7.5	11/32	660	
Ford	18	50	LT275/50R18	125/122S	E	BSW	04567510000	33.2	23.9	52.5	80	10.9 (8.0)	7.0 - 8.5	12/32	626
Ford		65	LT275/65R18	123/120S	E	BSW	04567530000	33.2	24.3	53.4	80	10.9 (8.0)	7.0 - 8.5	12/32	626
Ford		LT275/65R18	123/120S	E	OWL	04567540000	33.4	24.6	54.1	80	10.9 (8.0)	7.0 - 8.5	15/32	623	
Nissan	70		P265/70R18	114S	SL	BSW	15482600000	32.6	19.0	41.7	44	10.7 (8.0)	7.0 - 9.0	11/32	639