

Continental 
The Future in Motion



HTL2 Eco Plus

Heavy Trailer Long Haul

Continental offers the right tire for every application and type of terrain. Whether you need to take the highway, regional roads, city traffic or even venture off road, our premium tires for trucks and buses are engineered to suit your specific application needs.


HTL2 Eco Plus

Fuel Saving

Mileage



Heavy Trailer Long Haul



- Low rolling resistance compound provides excellent fuel economy at cool operating temperatures.
- Advanced tread design provides long original mileage and low cost per mile.
- Innovative groove geometry promotes efficient water evacuation, traction and wet braking capabilities throughout tire life.
- Heavy ply construction for structural durability in large capacity applications.
- Patented groove technology leads to minimum stone retention, extending casing life.



Applications

Trailers and free rolling positions.

Segment

- Goods
- Construction

Tire Size	Load Range	Article Number	Tread Depth (32nds)	Max Speed (MPH)#	Static Loaded Radius IN (MM)	Overall Inflated Diameter IN (MM)	Overall Inflated Width IN (MM)	Loaded Section Width IN (MM)	Approved Rim(s)	Minimum Dual Spacing IN (MM)	Revs Per Mile (KM)	Tire Weight LB (KG)	MAX. LOAD@INFLATION	
													LBS PSI (KG KPa)	LBS PSI (KG KPa)
TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS														
215/75R17.5	J	05310170000	15	75	141 (359)	30.4 (772)	8.5 (215)	9.1 (231)	6.00, 6.75	9.5 (242)	681 (423)	61 (28)	4805 125 (2180 860)	4540 125 (2060 860)
235/75R17.5	J	05310180000	13	75	14.5 (369)	31.6 (802)	9.2 (234)	10.0 (254)	6.75, 7.50	10.6 (269)	656 (407)	65 (29)	6005 125 (2725 860)	5675 125 (2575 860)
245/70R17.5	J	05310190000	13	75	14.5 (369)	31.6 (802)	9.2 (234)	10.0 (254)	6.75, 7.50	10.6 (269)	656 (407)	65 (29)	6005 125 (2725 860)	5675 125 (2575 860)

Note - Rim listed first is the measuring rim. Minimum Dual Spacing calculated without chains. * - ECE Certified # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.