

# Continental



The Future in Motion



## Passenger & Light Truck Tires



Tested to the limits by championship-winning racecar drivers,<sup>†</sup> the ExtremeContact™ Sport satisfies even the most demanding driver.

This dynamic, ultra-high performance street tire is built for car enthusiasts and engineered for extreme grip in dry and wet conditions. SportPlus Technology provides precise handling; security on wet, slippery roads; and excellent tread life.

**Rim Diameter:**

15 - 20

**Aspect Ratio:**

25 - 55

**Speed Rating**

W, Y

ULTRA-HIGH PERFORMANCE SUMMER



# ExtremeContact™ Sport



UTQG - All Sizes

---

**Tread**

---

340

**Traction**

---

AA

**Temperature**

---

A

## Features: Benefits

---



### **SportPlus Technology.**

Improves tread life while enhancing grip on wet roads and provides precise steering for maximum control.

### **QuickView Indicators.**

Indicators visually inform drivers to the level tires are performing in dry, wet and snow and the need to check vehicle's alignment.

†IMSAs Drivers: Andy Lally, Ryan Dalziel, João Barbosa,  
Lawson Aschenbach, Ozz Negri



Restrictions and Limitations Apply. See complete Total Confidence Plan for complete coverage details.

**Continental** 

Dynamic ultra-high performance summer tire tuned for drivers seeking extreme grip in dry and wet conditions without sacrificing excellent tread life and comfort.

**Rim Diameter:**

16 - 21

**Aspect Ratio:**

25 - 55

**Speed Rating**

W, Y

ULTRA-HIGH PERFORMANCE SUMMER



# ExtremeContact™ DW



UTQG - All Sizes

---

Tread

---

340

Traction

---

AA

Temperature

---

A

## Features: Benefits

---

### Enhanced Performance In Dry Conditions.

Solid outer shoulder and chamfered tread blocks maximize road contact.

### Outstanding Wet Handling and Braking.

High Void-to-Tread ratio with open longitudinal grooves aids in water evacuation for excellent resistance to hydroplaning.

### Excellent Treadlife and Fuel Efficiency.

Dynamic Temperature Distribution technology reduces distortion in the tread to improve wear and rolling resistance.

### Consumer-Friendly Performance Indicators.

Tuned Performance Indicators alert drivers to tire's performance level in Dry and Wet Conditions.



Restrictions and Limitations Apply. See complete Total Confidence Plan for complete coverage details.

**Continental** 

# ULTRA-HIGH PERFORMANCE ALL-SEASON

The ultra-high performance, all-season tire choice for drivers seeking true, year round traction. All new SportPlus™ Technology provides precise handling, security on wet, slippery roads, and excellent tread life.

**Rim Diameter:**

---

16 - 22

**Aspect Ratio:**

---

25 - 55

**Speed Rating**

---

W, Y



# ExtremeContact™ DWS<sup>06</sup>



## UTQG - All Sizes

	Tread	Traction	Temp
≤ 103	560	AA	A
≥ 104	560	A	A

## Features: Benefits



### SportPlus Technology.

Improves tread life while enhancing grip on wet roads and provides precise steering for maximum control.

### QuickView Indicators.

Indicators visually inform drivers to the level tires are performing in dry, wet and snow and the need to check vehicle's alignment.

### Improved All-Season Traction.

Traction Grooves improve snow performance through increased pattern edges, while X-Sipe technology improves braking, cornering and acceleration in wet, snow and ice.



Restrictions and Limitations Apply. See complete Total Confidence Plan for complete coverage details.

**Continental**

A skillful balance of luxury and all-season performance designed for long wear, a comfortable ride, and best-in-class wet braking.

**Rim Diameter:**

15 - 18

**Aspect Ratio:**

40 - 65

**Speed Rating**

H, V

LUXURY PERFORMANCE & TOURING ALL-SEASON





# PureContact™



**UTQG - All Sizes**

---

**Tread**

---

700

**Traction**

---

A

**Temperature**

---

A

## Features: Benefits

---

### Extra Measure of Confidence.

Tuned Performance Indicators - Dry, Wet & Snow (DWS) Indicators disappear when tire is no longer tuned for optimum performance in either dry, wet or snow conditions.

### Smooth, Comfortable Ride.

Comfort Ride Technology's continuous comfort band system absorbs vibrations caused by various road surfaces.

### Stop Shorter, Last Longer, Save Money.

EcoPlus Technology improves treadwear and fuel efficiency while enhancing grip on wet roads promoting a shorter stopping distance.



Restrictions and Limitations Apply. See complete Total Confidence Plan for complete coverage details.

**Continental** 

Touring performance, all-seasons traction combined with fuel efficiency, long-wear and best-in-class wet braking make this tire a confident choice.

**Rim Diameter:**

15 - 19

**Aspect Ratio:**

45 - 65

**Speed Rating**

T, H and V

STANDARD PERFORMANCE & TOURING - ALL SEASON



# TrueContact™



## UTQG - All Sizes

	Tread	Traction	Temp
T	800	A	B
H & V	800	A	A

### Features: Benefits

#### Long tread life and enhanced fuel efficiency.

EcoPlus Technology reduces rolling resistance with Tg-F polymers, providing extended tread life and improved fuel efficiency to lower CO<sub>2</sub> emissions while saving you money.

#### Offers a confident controlled driving experience.

Tuned Performance Indicators (DWS) and Alignment Verification System for complete confidence.

#### Excellent Wet Braking.

EcoPlus Technology's +Silane provides an optimum balance of exceptional wet grip and extended tread life.



Restrictions and Limitations Apply. See complete Total Confidence Plan for complete coverage details.



The premium SUV, Crossover, and Light Truck all season tire with excellent wet braking, long wear & enhanced fuel efficiency.

**Rim Diameter:**

16 - 22

**Aspect Ratio:**

45 - 75

**Speed Rating**

S, T H

LUXURY & COMFORT



# CrossContact™ LX20



## UTQG - All Sizes

	Tread	Traction	Temp
S&T	740	A	B
H	680	A	A

Available in Outlined White Letter (OWL) and Black Sidewall (BSW)

### Features: Benefits

#### Enhanced Fuel Efficiency.

EcoPlus Technology reduces rolling resistance with Tg-F polymers, providing improved fuel efficiency and lower CO<sub>2</sub> emissions.

#### Improved Snow Performance.

Traction Grooves provide gripping teeth inside the groove that lock snow for improved snow grip.

#### Reduced Noise, Comfortable Ride and Crisp Handling Response.

Smooth Response Technology features continuous ribs that provide smooth rolling surfaces for improved comfort and reduced noise, while reinforcing the shoulders for improved handling response.

#### Excellent Wet Braking and Long Wear.

EcoPlus Technology's +Silane provides an optimum balance of exceptional wet grip and extended tread life.

**ECOPLUS+**  
TECHNOLOGY



Restrictions and Limitations Apply. See complete Total Confidence Plan for complete coverage details.

**Continental**

# ALL-TERRAIN - ALL-SEASON

The ideal all-terrain tire for CUV, SUV and Light Trucks with the durability to conquer dirt, gravel and grass while providing a quiet, comfortable ride on pavement. This tire strikes the perfect balance between off-road traction and on-road manners.

## **35 Sizes: Covers over 80% of Premium All-Terrain Market**

- 20 Metric Sizes • 15 LT Metric Sizes
- 235 - 315 Width
- Aspect Ratio: 45 - 80
- Rim Diameter: 16" - 22"



# TerrainContact™ A/T



Available in Outlined White Letter (OWL) and Black Sidewall (BSW)

## UTQG

Metric	Tread	Traction	Temp
S&T	680	A	B
H&V	680	A	A

LT	Tread	Traction	Temp
S Rated	N/A	N/A	N/A

## Features: Benefits



### Traction Plus Technology.

Balances off-road traction and durability with on-road manners, including exceptional wet grip and low noise.

### All Season Traction.

Traction Grooves provide gripping teeth inside the groove that lock snow for improved snow grip. Full depth sipes aid in snow and ice traction while providing the comfort and traction needed in wet and dry conditions the rest of the year.

### Long Tread Life.

Even road surface contact provided by a flat contour shape and strong tread shoulders, boost the tires treadlife on CUV, SUV, and Light Trucks.



Restrictions and Limitations Apply. See complete Total Confidence Plan for complete coverage details.



Designed for snow and ice traction.  
Tread stays pliable in sub-zero  
temperatures enhancing grip  
on slippery road surfaces.

**Rim Diameter:**

15 - 17

**Aspect Ratio:**

45 - 70

**Speed Rating**

T, H, V

WINTER





# WinterContact™ SI



## Features: Benefits

---

### Improved Snow Performance.

Traction grooves and increased pattern edges.

### Consumer Friendly Alignment Indicators.

Alignment Verification System visually alerts the driver of vehicle misalignment allowing a correction before the tires are ruined.

### Reduce braking distance in wet, snow and ice.

Polar Plus technology keeps tread pliable in sub-zero temperatures and +Silane enhances grip on slippery conditions like wet, snow and ice covered roads.



Restrictions and Limitations Apply. See complete Total Confidence Plan for complete coverage details.



# Tire Size Lineup

## EXTREMECONTACT™ SPORT

SIZE	LOAD/SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	OVERALL TIRE/WHEEL DIAMETER (in.)	OVERALL SECTION WIDTH (measuring rim) (in.)	APPROVED RIM WIDTHS (in.)
205/50ZR15*	86W	SL	BSW	15507030000	23.1	8.4 (6.5)	5.5 - 7.5
205/55ZR16*	91W	SL	BSW	15506540000	24.9	8.4 (6.5)	5.5 - 7.5
195/50ZR16*	84W	SL	BSW	15507040000	23.7	8.5 (6.0)	5.5 - 7.0
225/50ZR16*	92W	SL	BSW	15507060000	24.9	9.2 (7.0)	6.0 - 8.0
205/45ZR16*	83W	SL	BSW	15507050000	23.3	8.1 (7.0)	6.5 - 7.5
205/50ZR17*	93W	XL	BSW	15507070000	25.1	8.5 (6.5)	5.5 - 7.5
225/50ZR17*	94W	SL	BSW	15507090000	25.9	9.2 (7.0)	6.0 - 8.0
205/45ZR17*	88W	XL	BSW	15506560000	24.3	8.4 (7.0)	6.5 - 7.5
215/45ZR17*	91W	XL	BSW	15507080000	24.6	8.5 (7.0)	7.0 - 8.0
225/45ZR17*	91W	SL	BSW	15506470000	25	8.9 (7.5)	7.0 - 8.0
235/45ZR17*	94W	SL	BSW	15506480000	25.3	9.3 (8.0)	7.5 - 9.0
245/45ZR17*	95Y	SL	BSW	15507100000	25.7	9.6 (8.0)	7.0 - 9.0
255/45ZR17*	98W	SL	BSW	15506550000	26	10.2 (8.5)	8.0 - 9.5
245/40ZR17*	91W	SL	BSW	15506500000	24.7	9.8 (8.5)	8.0 - 9.5
255/40ZR17*	94W	SL	BSW	15507110000	25	10.2 (9.0)	8.5 - 10.0
275/40ZR17*	98W	SL	BSW	15507120000	25.7	10.9 (9.5)	9.0 - 11.0
285/40ZR17*	100W	SL	BSW	15507130000	26	11.4 (10.0)	9.5 - 11.0
235/50ZR18*	97Y	SL	BSW	15507160000	27.3	9.6 (8.0)	6.5 - 8.5
225/45ZR18*	91Y	SL	BSW	15492510000	26	8.9 (7.5)	7.0 - 8.5
245/45ZR18*	100Y	XL	BSW	15507180000	26.7	9.6 (8.0)	7.5 - 9.0
255/45ZR18*	103Y	XL	BSW	15507210000	27	10.0 (8.5)	8.0 - 9.5
215/40ZR18*	89Y	XL	BSW	15507140000	24.8	8.6 (7.5)	7.0 - 8.5
225/40ZR18*	92Y	XL	BSW	15495980000	25.1	9.0 (8.0)	7.5 - 9.0
235/40ZR18*	95Y	XL	BSW	15506530000	25.4	9.5 (8.5)	8.0 - 9.5
245/40ZR18*	97Y	XL	BSW	15505140000	25.7	9.8 (8.5)	8.0 - 9.5
255/40ZR18*	99Y	XL	BSW	15507200000	26	10.2 (9.0)	8.5 - 10.0
265/40ZR18*	101Y	XL	BSW	15507230000	26.3	11.2 (9.5)	9.0 - 10.5
275/40ZR18*	99Y	SL	BSW	15507250000	26.7	10.9 (9.5)	9.0 - 11.0
285/40ZR18*	101Y	SL	BSW	15507270000	27	11.4 (10.0)	9.5 - 11.0
245/35ZR18*	92Y	XL	BSW	15507170000	24.8	9.8 (8.5)	8.0 - 9.5
255/35ZR18*	94Y	XL	BSW	15507190000	25	10.2 (9.0)	8.5 - 10.0
265/35ZR18*	97Y	XL	BSW	15507220000	25.3	10.7 (9.5)	9.0 - 10.5
275/35ZR18*	95Y	SL	BSW	15507240000	25.6	11.2 (9.5)	9.0 - 11.0
295/35ZR18*	99Y	SL	BSW	15507280000	26.1	12.0 (10.5)	10.0 - 11.0
285/30ZR18*	93Y	SL	BSW	15507260000	24.7	11.5 (10.0)	9.5 - 10.5
225/45ZR19*	92Y	SL	BSW	15507320000	27	9.6 (8.0)	7.0 - 8.5
235/40ZR19*	96Y	XL	BSW	15507340000	26.4	9.5 (8.5)	8.0 - 9.5
245/40ZR19*	98Y	XL	BSW	15507360000	26.7	9.8 (8.5)	8.0 - 9.5
255/40ZR19*	100Y	XL	BSW	15506490000	27	10.2 (9.0)	8.5 - 10.0
265/40ZR19*	102Y	XL	BSW	15507390000	27.4	11.1 (9.5)	9.0 - 10.5
275/40ZR19*	101Y	SL	BSW	15507420000	27.7	11.1 (9.5)	9.0 - 11.0
225/35ZR19*	88Y	XL	BSW	15507310000	25.2	9.1 (8.0)	7.5 - 9.0
235/35ZR19*	91Y	XL	BSW	15507330000	25.5	9.5 (8.5)	8.0 - 9.5
245/35ZR19*	93Y	XL	BSW	15507350000	25.8	9.8 (8.5)	8.0 - 9.5
255/35ZR19*	96Y	XL	BSW	15506510000	26	10.3 (9.0)	8.5 - 10.0
265/35ZR19*	94Y	SL	BSW	15507380000	26.3	10.7 (9.5)	9.0 - 10.0
275/35ZR19*	100Y	XL	BSW	15507410000	26.6	10.9 (9.5)	9.0 - 11.0
285/35ZR19*	99Y	SL	BSW	15506520000	26.9	11.4 (10.0)	9.0 - 11.0
295/35ZR19*	104Y	XL	BSW	15507440000	27.1	11.9 (10.5)	10.0-11.5

\*INDICATES SIZE HAS A RIM PROTECTOR

# Tire Size Lineup

## EXTREMECONTACT™ SPORT (continued)

SIZE	LOAD/SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	OVERALL TIRE/WHEEL DIAMETER (in.)	OVERALL SECTION WIDTH (measuring rim) (in.)	APPROVED RIM WIDTHS (in.)
255/30ZR19*	91Y	XL	BSW	15507370000	25	10.2 (9.0)	8.5 - 9.5
275/30ZR19*	96Y	XL	BSW	15507400000	25.5	10.9 (9.5)	9.0 - 10.0
285/30ZR19*	98Y	XL	BSW	15507430000	25.7	11.4 (10.0)	9.5 - 10.5
305/30ZR19*	102Y	XL	BSW	15507450000	26.2	12.3 (11.0)	10.5 - 11.5
325/30ZR19*	101Y	SL	BSW	15507460000	26.7	13.0 (11.5)	11.0 - 12.0
245/45ZR20*	103Y	XL	BSW	15507500000	28.7	9.6 (8.0)	7.5 - 9.0
245/40ZR20*	99Y	XL	BSW	15507490000	27.7	9.8 (8.5)	8.0 - 9.5
255/40ZR20*	101Y	XL	BSW	15507520000	28	10.2 (9.0)	8.5 - 10.0
275/40ZR20*	106Y	XL	BSW	15507570000	28.7	10.9 (9.5)	9.0 - 10.5
235/35ZR20*	88Y	SL	BSW	15507470000	26.5	9.5 (8.5)	8.0 - 9.5
245/35ZR20*	95Y	XL	BSW	15507480000	26.8	9.8 (8.5)	8.0 - 9.5
255/35ZR20*	97Y	XL	BSW	15507510000	27	10.7 (9.0)	8.0 - 10.0
265/35ZR20*	99Y	XL	BSW	15507530000	27.3	10.7 (9.5)	9.0 - 10.5
275/35ZR20*	102Y	XL	BSW	15507560000	27.6	11.0 (9.5)	9.0 - 11.0
285/35ZR20*	100Y	SL	BSW	15507590000	27.9	11.4 (10.0)	9.5 - 11.0
305/35ZR20*	104Y	SL	BSW	15507620000	28.4	12.3 (11.0)	10.0 - 12.0
315/35ZR20*	110Y	XL	BSW	15507630000	28.7	12.6 (11.0)	10.5 - 12.5
275/30ZR20*	97Y	XL	BSW	15507550000	26.5	10.4 (9.5)	9.0 - 10.0
285/30ZR20*	99Y	XL	BSW	15507580000	26.7	11.4 (10.0)	9.5 - 10.5
295/30ZR20*	101Y	XL	BSW	15507600000	27	11.9 (10.5)	10.0 - 11.0
305/30ZR20*	103Y	XL	BSW	15507610000	27.2	12.3 (11.0)	10.5 - 11.5
335/25ZR20*	99Y	SL	BSW	15507640000	26.6	13.5 (12.0)	11.5 - 12.5

\*INDICATES SIZE HAS A RIM PROTECTOR

## EXTREMECONTACT™ DW

SIZE	LOAD/SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	OVERALL TIRE/WHEEL DIAMETER (in.)	OVERALL SECTION WIDTH (measuring rim) (in.)	APPROVED RIM WIDTHS (in.)
205/55ZR16	91W	SL	BSW	15481580000	24.9	8.4 (6.5)	5.5 - 7.5
225/55ZR16	95W	SL	BSW	15481620000	25.7	9.2 (7.0)	6.0 - 8.0
225/50ZR16	92W	SL	BSW	15481610000	24.9	9.2 (7.0)	6.0 - 8.0
205/50ZR17*	93W	XL	BSW	15481650000	25.1	8.4 (6.5)	5.5 - 7.5
225/50ZR17*	94W	SL	BSW	15481720000	25.9	9.2 (7.0)	6.0 - 8.0
235/50ZR17*	96W	SL	BSW	15481740000	26.3	9.6 (7.5)	6.5 - 8.5
205/45ZR17 *	88W	XL	BSW	15481640000	24.3	8.4 (7.0)	6.5 - 7.5
215/45ZR17*	91W	XL	BSW	15481680000	24.6	8.5 (7.0)	7.0 - 8.0
225/45ZR17*	91W	SL	BSW	15481710000	25	8.9 (7.5)	7.0 - 8.0
235/45ZR17*	94W	SL	BSW	15481730000	25.3	9.3 (8.0)	7.5 - 9.0
245/45ZR17*	95Y	SL	BSW	15494080000	25.7	9.6 (8.0)	7.0 - 9.0
255/45ZR17*	98W	SL	BSW	15481810000	26	10.2 (8.5)	8.0 - 9.5
245/40ZR17*	91W	SL	BSW	15481750000	24.7	9.8 (8.5)	8.0 - 9.5
255/40ZR17*	94W	SL	BSW	15481790000	25	10.2 (9.0)	8.5 - 10.0
275/40ZR17*	98W	SL	BSW	15481830000	25.7	10.9 (9.5)	9.0 - 11.0
285/40ZR17*	100W	SL	BSW	15481840000	26	11.4 (10.0)	9.5 - 11.0
235/50ZR18*	97Y	SL	BSW	15481940000	27.3	9.6 (8.0)	6.5 - 8.5
225/45ZR18*	91Y	SL	BSW	15481910000	26	8.9 (7.5)	7.0 - 8.5
245/45ZR18 *	100Y	XL	BSW	15494060000	26.7	9.6 (8.0)	7.5 - 9.0
255/45ZR18*	103Y	XL	BSW	15482020000	27	10.0 (8.5)	8.0 - 9.5
215/40ZR18 *	89Y	XL	BSW	15481870000	24.8	8.6 (7.5)	7.0 - 8.5
225/40ZR18*	92Y	XL	BSW	15481890000	25.1	9.0 (8.0)	7.5 - 9.0

\*INDICATES SIZE HAS A RIM PROTECTOR

# Tire Size Lineup

## EXTREMECONTACT™ DW (continued)

SIZE	LOAD/SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	OVERALL TIRE/WHEEL DIAMETER (in.)	OVERALL SECTION WIDTH (measuring rim) (in.)	APPROVED RIM WIDTHS (in.)
235/40ZR18*	95Y	XL	BSW	15481920000	25.4	9.5 (8.5)	8.0 - 9.5
245/40ZR18 *	97Y	XL	BSW	15494040000	25.7	9.8 (8.5)	8.0 - 9.5
255/40ZR18*	99Y	XL	BSW	15482010000	26	10.2 (9.0)	8.5 - 10.0
265/40ZR18 *	101Y	XL	BSW	15482040000	26.3	11.2 (9.5)	9.0 - 10.5
285/40ZR18*	101Y	SL	BSW	15482110000	27	11.4 (10.0)	9.5 - 11.0
245/35ZR18 *	92Y	XL	BSW	15493940000	24.8	9.8 (8.5)	8.0 - 9.5
255/35ZR18 *	94Y	XL	BSW	15494070000	25	10.0 (9.0)	8.5 - 10.0
265/35ZR18*	97Y	XL	BSW	15482030000	25.3	10.7 (9.5)	9.0 - 10.5
275/35ZR18*	95Y	SL	BSW	15482050000	25.6	11.2 (9.5)	9.0 - 11.0
285/35ZR18 *	101Y	XL	BSW	15482090000	25.9	11.4 (10.0)	9.5 - 11.0
295/35ZR18*	99Y	SL	BSW	15482130000	26.1	12.0 (10.5)	10.0 - 11.0
285/30ZR18*	93Y	SL	BSW	15482080000	24.7	11.5 (10.0)	9.5 - 10.5
225/45ZR19*	92W	SL	BSW	15496430000	27	9.6 (8.0)	7.0 - 8.5
245/45ZR19*	98Y	SL	BSW	15482220000	27.7	9.6 (8.0)	7.5 - 9.0
225/40ZR19 *	93Y	XL	BSW	15482170000	26.1	9.1 (8.0)	7.5 - 9.0
245/40ZR19 *	98Y	XL	BSW	15494050000	26.7	9.8 (8.5)	8.0 - 9.5
255/40ZR19*	100Y	XL	BSW	15482250000	27	10.2 (9.0)	8.5 - 10.0
275/40ZR19*	101Y	SL	BSW	15482310000	27.7	11.1 (9.5)	9.0 - 11.0
225/35ZR19 *	88Y	XL	BSW	15482160000	25.2	9.1 (8.0)	7.5 - 9.0
235/35ZR19*	91Y	XL	BSW	15482180000	25.5	9.5 (8.5)	8.0 - 9.5
245/35ZR19*	93Y	XL	BSW	15482190000	25.8	9.8 (8.5)	8.0 - 9.5
255/35ZR19 *	96Y	XL	BSW	15482240000	26	10.2 (9.0)	8.5 - 10.0
265/35ZR19*	94Y	SL	BSW	15482270000	26.3	10.7 (9.5)	9.0 - 10.0
275/35ZR19 *	100Y	XL	BSW	15482290000	26.6	10.9 (9.5)	9.0 - 11.0
285/35ZR19*	99Y	SL	BSW	15482330000	26.9	11.4 (10.0)	9.0 - 11.0
255/30ZR19 *	91Y	XL	BSW	15482230000	25	10.2 (9.0)	8.5 - 9.5
265/30ZR19 *	93Y	XL	BSW	15482260000	25.3	10.7 (9.5)	9.0 - 10.0
275/30ZR19 *	96Y	XL	BSW	15482280000	25.5	10.9 (9.5)	9.0 - 10.0
285/30ZR19*	98Y	XL	BSW	15482320000	25.7	11.4 (10.0)	9.5 - 10.5
305/30ZR19 *	102Y	XL	BSW	15482350000	26.2	12.3 (11.0)	10.5 - 11.5
325/30ZR19*	101Y	SL	BSW	15483110000	26.7	13.0 (11.5)	11.0 - 12.0
245/45ZR20*	103Y	XL	BSW	15496420000	28.7	9.6 (8.0)	7.5 - 9.0
245/40ZR20*	99Y	XL	BSW	15482410000	27.7	9.8 (8.5)	8.0 - 9.5
275/40ZR20*	106Y	XL	BSW	15496440000	28.7	10.9 (9.5)	9.0 - 10.5
255/35ZR20*	97Y	XL	BSW	15482430000	27	10.2 (9.0)	8.0 - 10.0
275/35ZR20*	102Y	XL	BSW	15482460000	27.6	11.0 (9.5)	9.0 - 11.0
315/35ZR20*	110Y	XL	BSW	15496460000	28.7	12.6 (11.0)	10.5 - 12.5
335/25ZR20*	99Y	SL	BSW	15496470000	26.6	13.5 (12.0)	11.5 - 12.5
245/35ZR21*	96Y	XL	BSW	15482520000	27.8	9.8 (8.5)	8.0 - 9.5

\*INDICATES SIZE HAS A RIM PROTECTOR

## EXTREMECONTACT™ DWS<sup>06</sup>

SIZE	LOAD/SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	OVERALL TIRE/WHEEL DIAMETER (in.)	OVERALL SECTION WIDTH (measuring rim) (in.)	APPROVED RIM WIDTHS (in.)
205/55ZR16	91W	SL	BSW	15499550000	24.9	8.4 (6.5)	5.5 - 7.5
215/55ZR16	93W	SL	BSW	15499560000	25.3	8.9 (7.0)	6.0 - 7.0
225/55ZR16	95W	SL	BSW	15499580000	25.7	9.2 (7.0)	6.0 - 8.0
195/50ZR16	84W	SL	BSW	15499510000	23.7	8.5 (6.0)	5.5 - 7.0
205/50ZR16	87W	SL	BSW	15499530000	24.1	8.4 (6.5)	5.5 - 7.5

\*INDICATES SIZE HAS A RIM PROTECTOR

# Tire Size Lineup

EXTREMECONTACT™ DWS06 (continued)

SIZE	LOAD/SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	OVERALL TIRE/WHEEL DIAMETER (in.)	OVERALL SECTION WIDTH (measuring rim) (in.)	APPROVED RIM WIDTHS (in.)
225/50ZR16	92W	SL	BSW	15499570000	24.9	9.2 (7.0)	6.0 - 8.0
205/45ZR16*	83W	SL	BSW	15499520000	23.3	8.1 (7.0)	6.5 - 7.5
215/55ZR17	94W	SL	BSW	15499630000	26.3	8.9 (7.0)	6.0 - 7.0
225/55ZR17	97W	SL	BSW	15499660000	26.7	9.2 (7.0)	6.0 - 8.0
235/55ZR17	99W	SL	BSW	15499690000	27.2	9.6 (7.5)	6.5 - 8.5
205/50ZR17*	93W	XL	BSW	15499600000	25.1	8.5 (6.5)	5.5 - 7.5
215/50ZR17*	95W	XL	BSW	15499620000	25.5	8.9 (7.0)	6.0 - 7.0
225/50ZR17*	94W	SL	BSW	15499650000	25.9	9.2 (7.0)	6.0 - 8.0
235/50ZR17*	96W	SL	BSW	15499680000	26.3	9.7 (7.5)	6.5 - 8.5
245/50ZR17*	99W	SL	BSW	15499720000	26.6	10.0 (7.5)	7.0 - 8.5
205/45ZR17*	88W	XL	BSW	15499590000	24.3	8.4 (7.0)	6.5 - 7.5
215/45ZR17*	91W	XL	BSW	15499610000	24.6	8.5 (7.0)	7.0 - 8.0
225/45ZR17*	91W	SL	BSW	15499640000	25	8.9 (7.5)	7.0 - 8.0
235/45ZR17*	94W	SL	BSW	15499670000	25.3	9.3 (8.0)	7.5 - 9.0
245/45ZR17*	99Y	XL	BSW	15499710000	25.7	9.6 (8.0)	7.0 - 9.0
255/45ZR17*	98W	SL	BSW	15499740000	26	10.2 (8.5)	8.0 - 9.5
245/40ZR17*	91W	SL	BSW	15499700000	24.7	9.8 (8.5)	8.0 - 9.5
255/40ZR17*	94W	SL	BSW	15499730000	25	10.2 (9.0)	8.5 - 10.0
235/55ZR18	100W	SL	BSW	15499830000	28.2	9.6 (7.5)	6.5 - 8.5
255/55ZR18*	109W	XL	BSW	15499900000	29	10.4 (8.0)	7.0 - 9.0
225/50ZR18*	95W	SL	BSW	15499790000	26.9	9.2 (7.0)	6.0 - 8.0
235/50ZR18*	97W	SL	BSW	15499820000	27.3	9.6 (8.0)	6.5 - 8.5
215/45ZR18*	93Y	XL	BSW	15499760000	25.6	8.4 (7.0)	7.0 - 8.0
225/45ZR18*	91Y	SL	BSW	15499780000	26	8.9 (7.5)	7.0 - 8.5
235/45ZR18*	98Y	XL	BSW	15499810000	26.3	9.3 (8.0)	7.5 - 9.0
245/45ZR18*	100Y	XL	BSW	15499860000	26.7	9.6 (8.0)	7.5 - 9.0
255/45ZR18*	103Y	XL	BSW	15499890000	27	10.0 (8.5)	8.0 - 9.5
215/40ZR18*	89Y	XL	BSW	15499750000	24.8	8.6 (7.5)	7.0 - 8.5
225/40ZR18*	92Y	XL	BSW	15499770000	25.1	9.0 (8.0)	7.5 - 9.0
235/40ZR18*	95Y	XL	BSW	15499800000	25.4	9.5 (8.5)	8.0 - 9.5
245/40ZR18*	97Y	XL	BSW	15499850000	25.7	9.8 (8.5)	8.0 - 9.5
255/40ZR18*	99Y	XL	BSW	15499880000	26	10.2 (9.0)	8.5 - 10.0
265/40ZR18*	101Y	XL	BSW	15499920000	26.3	11.2 (9.5)	9.0 - 10.5
275/40ZR18*	99Y	SL	BSW	15499940000	26.7	10.9 (9.5)	9.0 - 11.0
245/35ZR18*	92Y	XL	BSW	15499840000	24.8	9.8 (8.5)	8.0 - 9.5
255/35ZR18*	94Y	XL	BSW	15499870000	25	10.0 (9.0)	8.5 - 10.0
265/35ZR18*	97Y	XL	BSW	15499910000	25.3	10.7 (9.5)	9.0 - 10.5
275/35ZR18*	95Y	SL	BSW	15499930000	25.6	11.2 (9.5)	9.0 - 11.0
285/35ZR18*	101Y	XL	BSW	15499950000	25.9	11.4 (10.0)	9.5 - 11.0
295/35ZR18*	99Y	SL	BSW	15499960000	26.1	12.0 (10.5)	10.0 - 11.0
245/50ZR19*	105Y	XL	BSW	15500030000	28.7	10.0 (7.5)	7.0 - 8.5
255/50ZR19*	107W	XL	BSW	15500060000	29	10.4 (8.0)	7.0 - 9.0
225/45ZR19*	92W	SL	BSW	15499980000	27	9.6 (8.0)	7.0 - 8.5
245/45ZR19*	98Y	SL	BSW	15500020000	27.7	9.6 (8.0)	7.5 - 9.0
275/45ZR19*	108W	XL	BSW	15500130000	28.7	10.7 (9.0)	8.5 - 10.5
225/40ZR19*	93Y	XL	BSW	15499970000	26.1	9.1 (8.0)	7.5 - 9.0
245/40ZR19*	98Y	XL	BSW	15500010000	26.7	9.8 (8.5)	8.0 - 9.5
255/40ZR19*	100Y	XL	BSW	15500050000	27	10.2 (9.0)	8.5 - 10.0

\*INDICATES SIZE HAS A RIM PROTECTOR

# Tire Size Lineup

## EXTREMECONTACT™ DWS06 (continued)

SIZE	LOAD/SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	OVERALL TIRE/WHEEL DIA-METER (in.)	OVERALL SECTION WIDTH (measuring rim) (in.)	APPROVED RIM WIDTHS (in.)
275/40ZR19*	101Y	SL	BSW	15500120000	27.7	11.1 (9.5)	9.0 - 11.0
235/35ZR19*	91Y	XL	BSW	15499990000	25.5	9.5 (8.5)	8.0 - 9.5
245/35ZR19*	93Y	XL	BSW	15500000000	25.8	9.8 (8.5)	8.0 - 9.5
255/35ZR19*	96Y	XL	BSW	15500040000	26	10.2 (9.0)	8.5 - 10.0
265/35ZR19*	98Y	XL	BSW	15500080000	26.3	10.7 (9.5)	9.0 - 10.0
275/35ZR19*	100Y	XL	BSW	15500110000	26.6	10.5 (9.5)	9.0 - 11.0
285/35ZR19*	99Y	SL	BSW	15500160000	26.9	11.4 (10.0)	9.0 - 11.0
265/30ZR19*	93Y	XL	BSW	15500070000	25.3	10.7 (9.5)	9.0 - 10.0
275/30ZR19*	96Y	XL	BSW	15500090000	25.5	10.9 (9.5)	9.0 - 10.0
285/30ZR19*	98Y	XL	BSW	15500140000	25.7	11.4 (10.0)	9.5 - 10.5
255/50ZR20*	109Y	XL	BSW	15500220000	30	10.4 (8.0)	7.0 - 9.0
245/45ZR20*	103Y	XL	BSW	15500190000	28.7	9.6 (8.0)	7.5 - 9.0
255/45ZR20*	105Y	XL	BSW	15500210000	29	10.0 (8.5)	8.0 - 9.5
265/45ZR20*	104Y	SL	BSW	15500240000	29.4	10.5 (9.0)	8.5 - 10.0
275/45ZR20*	110W	XL	BSW	15500280000	29.7	10.7 (9.0)	8.5 - 10.0
245/40ZR20*	99Y	XL	BSW	15500180000	27.7	9.8 (8.5)	8.0 - 9.5
275/40ZR20*	106Y	XL	BSW	15500270000	28.7	10.9 (9.5)	9.0 - 10.5
295/40ZR20*	110W	XL	BSW	15500300000	29.3	11.9 (10.5)	10.0 - 11.5
245/35ZR20*	95Y	XL	BSW	15500170000	26.8	9.8 (8.5)	8.0 - 9.5
255/35ZR20*	97W	XL	BSW	15500200000	27	10.2 (9.0)	8.0 - 10.0
265/35ZR20*	99Y	XL	BSW	15500230000	27.3	10.7 (9.5)	9.0 - 10.5
275/35ZR20*	102Y	XL	BSW	15500260000	27.6	11.0 (9.5)	9.0 - 11.0
315/35ZR20*	110Y	XL	BSW	15500310000	28.7	12.6 (11.0)	10.5 - 12.5
275/30ZR20*	97Y	XL	BSW	15500250000	26.5	10.4 (9.5)	9.0 - 10.0
285/30ZR20*	99W	XL	BSW	15500290000	26.7	11.4 (10.0)	9.5 - 10.5
295/40ZR21*	111Y	XL	BSW	15500330000	30.3	11.9 (10.5)	10.0 - 11.5
295/35ZR21*	107Y	XL	BSW	15500320000	29.1	11.9 (10.5)	10.0 - 11.5
265/40ZR22*	106W	XL	BSW	15500370000	30.3	10.7 (9.5)	9.0 - 10.5
265/35ZR22*	102W	XL	BSW	15500360000	29.3	10.7 (9.5)	9.0 - 10.5
285/35ZR22*	106W	XL	BSW	15500390000	29.9	11.4 (10.0)	9.5 - 11.0
255/30ZR22*	95Y	XL	BSW	15500340000	28.1	10.2 (9.0)	8.5 - 9.5
265/30ZR22*	97Y	XL	BSW	15500350000	28.3	10.4 (9.5)	9.0 - 10.0
285/30ZR22*	101Y	XL	BSW	15500380000	28.7	11.4 (10.0)	9.5 - 10.5
295/25ZR22*	97Y	XL	BSW	15500400000	27.8	11.6 (10.5)	10.0 - 11.0

\*INDICATES SIZE HAS A RIM PROTECTOR

## PURECONTACT™

SIZE	LOAD/SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	OVERALL TIRE/WHEEL DIA-METER (in.)	OVERALL SECTION WIDTH (measuring rim) (in.)	APPROVED RIM WIDTHS (in.)
195/65R15	91H	SL	BSW	15493540000	25	7.9 (6.0)	5.5 - 7.0
205/65R16	95H	SL	BSW	15493660000	26.5	8.2 (6.0)	5.5 - 7.5
205/60R16	92H	SL	BSW	15493590000	25.7	8.2 (6.0)	5.5 - 7.5
205/60R16	92V	SL	BSW	15493600000	25.7	8.2 (6.0)	5.5 - 7.5
215/60R16	95V	SL	BSW	15493640000	26.2	8.7 (6.5)	6.0 - 7.0
215/60R16	95H	SL	BSW	15493910000	26.2	8.7 (6.5)	6.0 - 7.0
205/55R16	91H	SL	BSW	15493570000	24.9	8.4 (6.5)	5.5 - 7.5
205/55R16	91V	SL	BSW	15493580000	24.9	8.4 (6.5)	5.5 - 7.5
215/55R16	97H	XL	BSW	15493620000	25.3	8.9 (7.0)	6.0 - 7.0

\*INDICATES SIZE HAS A RIM PROTECTOR

# Tire Size Lineup

## PURECONTACT™ (continued)

SIZE	LOAD/SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	OVERALL TIRE/WHEEL DIAMETER (in.)	OVERALL SECTION WIDTH (measuring rim) (in.)	APPROVED RIM WIDTHS (in.)
215/55R17	94V	SL	BSW	15493630000	26.3	8.9 (7.0)	6.0 - 7.0
225/55R17	97V	SL	BSW	15493700000	26.8	9.2 (7.0)	6.0 - 8.0
235/55R17	99H	SL	BSW	15493770000	27.2	9.6 (7.5)	6.5 - 8.5
205/50R17*	93V	XL	BSW	15493560000	25.1	8.4 (6.5)	5.5 - 7.5
215/50R17*	95V	XL	BSW	15493610000	25.5	8.9 (7.0)	6.0 - 7.0
225/50R17*	98V	XL	BSW	15493670000	25.9	9.2 (7.0)	6.0 - 8.0
235/50R17*	96V	SL	BSW	15493750000	26.3	9.6 (7.5)	6.5 - 8.5
245/50R17*	99V	SL	BSW	15498280000	26.6	10.0 (7.5)	7.0 - 8.5
225/45R17*	91H	SL	BSW	15493650000	25	8.9 (7.5)	7.0 - 8.5
225/45R17*	91V	SL	BSW	15494410000	25	8.9 (7.5)	7.0 - 8.5
235/45R17*	94H	SL	BSW	15493720000	25.3	9.3 (8.0)	7.5 - 9.0
245/45R17*	99V	XL	BSW	15493810000	25.7	9.6 (8.0)	7.0 - 9.0
225/60R18	100H	SL	BSW	15493800000	28.6	9.0 (6.5)	6.0 - 8.0
235/55R18	100V	SL	BSW	15493780000	28.2	9.6 (7.5)	6.5 - 8.5
235/50R18*	97V	SL	BSW	15493840000	27.3	9.6 (8.0)	6.5 - 8.5
245/50R18*	100V	SL	BSW	15500860000	27.6	10.0 (7.5)	7.0 - 8.5
225/45R18*	91V	SL	BSW	15493790000	26	8.9 (7.5)	7.0 - 8.5
235/45R18*	94V	SL	BSW	15493740000	26.3	9.6 (8.0)	7.5 - 9.0
245/45R18*	100V	XL	BSW	15493820000	26.7	9.6 (8.0)	7.5 - 9.0
245/40R18*	97V	XL	BSW	15493830000	25.7	9.8 (8.5)	8.0 - 9.5
255/45R19*	100V	SL	BSW	15500840000	28	10.0 (8.5)	8.0 - 9.5
245/40R19*	98V	XL	BSW	15500850000	26.7	9.8 (8.5)	8.0 - 9.5
245/45R20*	99V	SL	BSW	15498290000	28.7	9.6 (8.0)	7.5 - 9.0

\*INDICATES SIZE HAS A RIM PROTECTOR

## TRUECONTACT™

SIZE	LOAD/SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	OVERALL TIRE/WHEEL DIAMETER (in.)	OVERALL SECTION WIDTH (measuring rim) (in.)	APPROVED RIM WIDTHS (in.)
185/65R15	88T	SL	BSW	15497050000	24.5	7.4 (5.5)	5.0 - 6.5
195/65R15	91T	SL	BSW	15497080000	25	7.9 (6.0)	5.5 - 7.0
195/60R15	88T	SL	BSW	15497070000	24.2	8.0 (6.0)	5.0 - 7.0
205/65R16	95T	SL	BSW	15497140000	26.5	8.2 (6.0)	5.5 - 7.5
215/65R16	98T	SL	BSW	15497220000	27	8.7 (6.5)	6.0 - 7.0
215/65R16	98H	SL	BSW	15497230000	27	8.7 (6.5)	6.0 - 7.0
225/65R16	100T	SL	BSW	15497360000	27.5	9.0 (6.5)	6.0 - 8.0
235/65R16	103T	SL	BSW	15497460000	28	9.4 (7.0)	6.5 - 7.5
205/60R16	92T	SL	BSW	15497120000	25.7	8.2 (6.0)	5.5 - 7.5
215/60R16	95T	SL	BSW	15497190000	26.2	8.7 (6.5)	6.0 - 7.0
225/60R16	98T	SL	BSW	15497320000	26.6	9.0 (6.5)	6.0 - 8.0
225/60R16	98H	SL	BSW	15497330000	26.6	9.0 (6.5)	6.0 - 8.0
215/65R17	99T	SL	BSW	15497240000	28	8.7 (6.5)	6.0 - 7.0
225/65R17	102T	SL	BSW	15497370000	28.5	9.0 (6.5)	6.0 - 8.0
235/65R17	104T	SL	BSW	15497470000	29	9.4 (7.0)	6.5 - 8.5
215/60R17	96T	SL	BSW	15497210000	27.2	9.3 (6.5)	6.0 - 7.0
225/60R17	99T	SL	BSW	15497340000	27.6	9.0 (6.5)	6.0 - 8.0
225/60R17	99H	SL	BSW	15497350000	27.6	9.0 (6.5)	6.0 - 8.0
235/60R17	102T	SL	BSW	15497430000	28.1	9.4 (7.0)	6.5 - 8.5
215/55R17	94T	SL	BSW	15497160000	26.3	8.9 (7.0)	6.0 - 7.0
225/55R17	97H	SL	BSW	15497300000	26.8	9.2 (7.0)	6.0 - 8.0

\*INDICATES SIZE HAS A RIM PROTECTOR

# Tire Size Lineup

## TRUECONTACT™ (continued)

SIZE	LOAD/SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	OVERALL TIRE/WHEEL DIAMETER (in.)	OVERALL SECTION WIDTH (measuring rim) (in.)	APPROVED RIM WIDTHS (in.)
235/55R17	99T	SL	BSW	15497380000	27.2	9.6 (7.5)	6.5 - 8.5
225/50R17*	94T	SL	BSW	15497270000	25.9	9.2 (7.0)	6.0 - 8.0
215/45R17*	87V	SL	BSW	15497150000	24.6	8.5 (7.0)	7.0 - 8.0
235/60R18	103T	SL	BSW	15497440000	29.1	9.4 (7.0)	6.5 - 8.5
235/60R18	103H	SL	BSW	15497450000	29.1	9.4 (7.0)	6.5 - 8.5
215/55R18	95T	SL	BSW	15497180000	27.3	8.9 (7.0)	6.0 - 7.0
235/55R18	100T	SL	BSW	15497400000	28.2	9.6 (7.5)	6.5 - 8.5
225/50R18*	95T	SL	BSW	15497290000	26.9	9.2 (7.0)	6.0 - 8.0
225/55R19	99H	SL	BSW	15497310000	28.8	9.2 (7.0)	6.0 - 8.0
235/55R19	101H	SL	BSW	15497420000	29.2	9.6 (7.5)	6.5 - 8.5

\*INDICATES SIZE HAS A RIM PROTECTOR

## CROSSCONTACT™ LX20

SIZE	LOAD/SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	OVERALL TIRE/WHEEL DIAMETER (in.)	OVERALL SECTION WIDTH (measuring rim) (in.)	APPROVED RIM WIDTHS (in.)
235/75R16*	108S	SL	OWL	15490790000	29.9	9.3 (6.5)	6.0 - 8.0
245/75R16*	111S	SL	OWL	15490940000	30.5	9.8 (7.0)	6.5 - 8.0
265/75R16*	116T	SL	OWL	15490760000	31.6	10.5(7.5)	7.0 - 9.0
215/70R16*	100S	SL	OWL	15490950000	27.9	8.7 (6.5)	5.5 - 7.0
225/70R16*	103S	SL	OWL	15490770000	28.4	9.0 (6.5)	6.0 - 7.0
235/70R16*	106T	SL	OWL	15490960000	29	9.4 (7.0)	6.0 - 8.0
245/70R16*	107S	SL	OWL	15490740000	29.5	9.8 (7.0)	6.0 - 8.0
265/70R16*	112S	SL	OWL	15490880000	30.6	10.7 (8.0)	7.0 - 9.0
235/65R16*	103T	SL	BSW	15490930000	28	9.4 (7.0)	6.5 - 7.5
255/65R16*	109S	SL	OWL	15490780000	29.1	10.2(7.5)	7.0 - 9.0
245/70R17*	110S	SL	OWL	15490700000	30.5	9.8 (7.0)	6.5 - 8.0
265/70R17*	115T	SL	OWL	15490890000	31.6	10.7 (8.0)	7.0 - 9.0
265/70R17*	115T	SL	BSW	15490900000	31.6	10.7 (8.0)	7.0 - 9.0
225/65R17*	102T	SL	BSW	15491040000	28.5	9.0 (6.5)	6.0 - 8.0
235/65R17*	108H	XL	BSW	15490820000	29	9.4 (7.0)	6.5 - 8.5
235/65R17*	108T	XL	OWL	15490830000	29	9.4 (7.0)	6.5 - 8.5
245/65R17*	107T	SL	OWL	15490800000	29.5	9.8 (7.0)	7.0 - 8.5
255/65R17*	110S	SL	OWL	15490710000	30.1	10.2(7.5)	7.0 - 9.0
265/65R17*	112T	SL	OWL	15490910000	30.6	10.7 (8.0)	7.5 - 9.5
265/65R17*	112T	SL	BSW	15491010000	30.6	10.7 (8.0)	7.5 - 9.5
275/60R17*	110S	SL	OWL	15490810000	30	11.0 (8.0)	7.5 - 9.5
255/70R18*	113T	SL	OWL	15491000000	32.1	10.2(7.5)	6.5 - 8.5
265/70R18*	116S	SL	BSW	15490920000	32.6	10.7 (8.0)	7.0 - 9.0
235/65R18*	106T	SL	BSW	15491020000	30	9.4 (7.0)	6.5 - 8.5
235/65R18*	106H	SL	BSW	15496040000	30	9.4 (7.0)	6.5 - 8.5
255/65R18*	111S	SL	BSW	15491110000	31.1	10.2 (7.5)	7.0 - 9.0
265/65R18*	114S	SL	OWL	15491090000	31.5	10.7 (8.0)	7.5 - 9.5
275/65R18*	116T	SL	OWL	15491100000	32.1	10.9 (8.0)	7.5 - 9.5
235/60R18*	107H	XL	BSW	15491080000	29.1	9.4 (7.0)	6.5 - 8.5
245/60R18*	105T	SL	BSW	15491070000	29.6	9.8 (7.0)	7.0 - 8.5
265/60R18*	110T	SL	OWL	15490980000	30.5	10.7 (8.0)	7.5 - 9.5
275/60R18*	113H	SL	BSW	15490990000	31	11.0 (8.0)	7.5 - 9.5
255/55R18*	109H	XL	BSW	15490840000	29	10.4 (8.0)	7.0 - 9.0
255/60R19*	109H	SL	BSW	15493960000	31.1	10.2(7.5)	7.0 - 9.0

\*INDICATES SIZE HAS A RIM PROTECTOR



# Tire Size Lineup

## CROSSCONTACT™ LX20 (continued)

SIZE	LOAD/SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	OVERALL TIRE/WHEEL DIA-METER (in.)	OVERALL SECTION WIDTH (measuring rim) (in.)	APPROVED RIM WIDTHS (in.)
245/55R19*	103S	SL	BSW	15493970000	29.6	10.0 (7.5)	7.0 - 8.5
255/50R19*	107H	XL	BSW	15491060000	29	10.4 (8.0)	7.0 - 9.0
275/60R20*	115S	SL	OWL	15490860000	33	11.0 (8.0)	7.5 - 9.5
255/55R20*	107H	SL	BSW	15496060000	31	10.4 (8.0)	7.0 - 9.0
P275/55R20	111S	SL	BSW	15493040000	31.9	11.2 (8.5)	7.5 - 9.5
265/50R20*	107T	SL	BSW	15496050000	30.4	10.9 (8.5)	7.5 - 9.5
285/50R20*	112H	SL	BSW	15491050000	31.2	11.7 (9.0)	8.0 - 10.0
285/45R22*	114H	XL	BSW	15494600000	32.1	11.2 (9.5)	9.0 - 10.5

\*INDICATES SIZE HAS A RIM PROTECTOR

## TERRAINCONTACT™ A/T

SIZE	LOAD/SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	OVERALL TIRE/WHEEL DIA-METER (in.)	OVERALL SECTION WIDTH (measuring rim) (in.)	APPROVED RIM WIDTHS (in.)
LT245/75R16*	120/116S	E	OWL	15506580000	30.5	9.8 (7.0)	6.5 - 8.0
LT265/75R16*	123/120S	E	OWL	15506590000	31.6	10.5 (7.5)	7.0 - 8.0
265/75R16*	116T	SL	OWL	15506790000	31.6	10.5 (7.5)	7.0 - 9.0
LT285/75R16*	126/123S	E	OWL	15506600000	32.8	11.3 (8.0)	7.5 - 9.0
265/70R16*	112T	SL	OWL	15506770000	30.6	10.7 (8.0)	7.0 - 9.0
LT235/80R17*	120/117S	E	BSW	15506610000	31.8	9.3 (6.5)	6.0 - 7.0
LT245/75R17*	121/118S	E	OWL	15506640000	31.5	9.7 (7.0)	6.0 - 7.5
255/75R17*	115S	SL	OWL	15506830000	32.1	10.0 (7.0)	6.5 - 8.5
LT245/70R17*	119/116S	E	OWL	15506630000	30.5	9.8 (7.0)	6.5 - 8.0
245/70R17*	110T	SL	OWL	15506810000	30.5	9.8 (7.0)	6.5 - 8.0
LT265/70R17*	121/118S	E	OWL	15506650000	31.6	10.7 (8.0)	7.0 - 9.0
265/70R17*	115S	SL	OWL	15506840000	31.6	10.7 (8.0)	7.0 - 9.0
LT285/70R17*	121/118S	E	BSW	15506670000	32.7	11.5 (8.5)	7.5 - 9.0
LT315/70R17*	121/118S	E	BSW	15506680000	34.4	12.7 (9.5)	8.5 - 10.0
245/65R17*	107T	SL	OWL	15506800000	29.5	9.8 (7.0)	7.0 - 8.5
255/65R17*	110S	SL	OWL	15506820000	30.1	10.2 (7.5)	7.0 - 9.0
225/60R17*	99H	SL	BSW	15507870000	27.6	9.0 (6.5)	6.0 - 8.0
255/70R18*	113T	SL	OWL	15506860000	32.1	10.2 (7.5)	6.5 - 8.5
LT265/70R18*	124/121S	E	OWL	15506690000	32.6	10.7 (8.0)	7.0 - 9.0
265/70R18*	116S	SL	OWL	15506900000	32.6	10.7 (8.0)	7.0 - 9.0
LT275/70R18*	125/122S	E	OWL	15506710000	33.2	10.9 (8.0)	7.0 - 8.5
265/65R18*	114T	SL	BSW	15506890000	31.5	10.7 (8.0)	7.5 - 9.5
LT275/65R18*	123/120S	E	OWL	15506700000	32.1	10.9 (8.0)	7.5 - 9.0
275/65R18*	116T	SL	OWL	15506910000	32.1	10.9 (8.0)	7.5 - 9.5
245/60R18*	105H	SL	BSW	15506850000	29.6	9.8 (7.0)	7.0 - 8.5
265/60R18*	110T	SL	BSW	15506870000	30.5	10.7 (8.0)	7.5 - 9.5
255/55R18*	109V	XL	BSW	15507880000	29	10.4 (8.0)	7.0 - 9.0
255/55R19*	111V	XL	BSW	15507890000	30	10.4 (8.0)	7.0 - 9.0
LT275/65R20*	126/123S	E	BSW	15506730000	34.1	11.0 (8.0)	7.5 - 9.5
LT265/60R20*	121/118S	E	BSW	15506720000	32.5	10.7 (8.0)	7.5 - 9.5
275/60R20*	115S	SL	BSW	15506940000	33	11.0 (8.0)	7.5 - 9.5
LT285/60R20*	125/122S	E	BSW	15506740000	33.5	11.5 (8.5)	8.0 - 10.0
275/55R20*	113T	SL	BSW	15506930000	31.9	11.2 (8.5)	7.5 - 9.5
265/50R20*	107T	SL	BSW	15506920000	30.4	10.9 (8.5)	7.5 - 9.5
285/45R22*	114H	XL	BSW	15506950000	32.1	11.2 (9.5)	9.0 - 10.5

\*INDICATES SIZE HAS A RIM PROTECTOR

# Tire Size Lineup

## WINTERCONTACT™ SI

SIZE	LOAD/SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	OVERALL TIRE/WHEEL DIAMETER (in.)	OVERALL SECTION WIDTH (measuring rim) (in.)	APPROVED RIM WIDTHS (in.)
185/65R15	92T	XL	BSW	15390550000	24.5	7.4 (5.5)	5.0 - 6.5
195/65R15	95T	XL	BSW	15390460000	25	7.9 (6.0)	5.5 - 7.0
185/55R15	87H	XL	BSW	15390500000	23	7.9 (6.0)	5.5 - 7.0
215/70R16*	104T	XL	BSW	15390530000	27.9	8.7 (6.5)	5.5 - 7.0
205/65R16	99H	XL	BSW	15390570000	26.5	8.2 (6.0)	5.5 - 7.5
215/65R16*	102T	XL	BSW	15390520000	27	8.7 (6.5)	6.0 - 7.0
225/65R16*	104T	XL	BSW	15390640000	27.5	9.0 (6.5)	6.0 - 7.0
205/60R16	96H	XL	BSW	15390510000	25.7	8.2 (6.0)	5.5 - 7.5
215/60R16	99H	XL	BSW	15390480000	26.2	8.7 (6.5)	6.0 - 7.0
195/55R16	91H	XL	BSW	15390770000	24.4	7.9 (6.0)	5.5 - 7.0
205/55R16	94H	XL	BSW	15390470000	24.9	8.4 (6.5)	5.5 - 7.5
215/55R16	97H	XL	BSW	15390580000	25.3	8.9 (7.0)	6.0 - 7.0
225/65R17*	106T	XL	BSW	15390490000	28.5	9.0 (6.5)	6.0 - 8.0
235/65R17*	108T	XL	BSW	15390680000	29	9.4 (7.0)	6.5 - 8.5
225/60R17*	103H	XL	BSW	15390630000	27.6	9.0 (6.5)	6.0 - 8.0
215/55R17	98H	XL	BSW	15390590000	26.3	8.9 (7.0)	6.0 - 7.0
225/55R17	101H	XL	BSW	3449030000	26.8	9.2 (7.0)	6.0 - 8.0
235/55R17*	103H	XL	BSW	15390660000	27.2	9.6 (7.5)	6.5 - 8.5
205/50R17*	93H	XL	BSW	15390560000	25.1	8.4 (6.5)	5.5 - 7.5
225/50R17*	98H	XL	BSW	15390620000	25.9	9.2 (7.0)	6.0 - 8.0
215/45R17*	91H	XL	BSW	3449020000	24.6	8.5 (7.0)	7.0 - 8.0
225/45R17*	94H	XL	BSW	15390610000	25	8.9 (7.5)	7.0 - 8.5
235/45R17*	97H	XL	BSW	15390740000	25	9.3 (8.0)	7.5 - 9.0
245/45R17*	99H	XL	BSW	15390930000	25.7	9.6 (8.0)	7.0 - 9.0
235/65R18*	110H	XL	BSW	15390540000	30	9.4 (7.0)	6.5 - 8.5
235/60R18*	107H	XL	BSW	15390670000	29.1	9.4 (7.0)	6.5 - 8.5
245/60R18*	109H	XL	BSW	15390690000	29.6	9.8 (7.0)	7.0 - 8.5
235/55R18*	104H	XL	BSW	15390710000	28.2	9.6 (7.5)	6.5 - 8.5
255/55R18*	109H	XL	BSW	15390960000	29	10.4 (8.0)	7.0 - 9.0
235/50R18*	101H	XL	BSW	15390650000	27.3	9.6 (8.0)	6.5 - 8.5
225/45R18*	95V	XL	BSW	15390890000	26	8.9 (7.5)	7.0 - 8.5
235/45R18*	98H	XL	BSW	15390900000	26.3	9.3 (8.0)	7.5 - 9.0
225/40R18*	92V	XL	BSW	15390880000	25.1	9.0 (8.0)	7.5 - 9.0
245/40R18*	97H	XL	BSW	15390750000	25.7	9.8 (8.5)	8.0 - 9.5
235/55R19*	105H	XL	BSW	15390720000	29.2	9.6 (7.5)	6.5 - 8.5
255/50R19*	107H	XL	BSW	15390730000	29	10.4 (8.0)	7.0 - 9.0
235/55R20*	105H	XL	BSW	15390910000	30.2	9.6 (7.5)	6.5 - 8.5
245/50R20*	105H	XL	BSW	15390760000	29.7	10.0 (7.5)	7.0 - 8.5
265/50R20*	111T	XL	BSW	15390980000	30.4	10.9 (8.5)	7.5 - 9.5

\*INDICATES SIZE HAS A RIM PROTECTOR



# What is UTQG?

## (Uniform Tire Quality Grading)

Comparative ratings which measure tread, traction and temperature for almost all passenger car tires.

### EXAMPLE:

<b>UTQG Rating:</b>	<b>Treadwear</b>	<b>Traction</b>	<b>Temperature</b>
<b>All Sizes</b>	<b>280</b>	<b>A</b>	<b>A</b>

**UTQG applies to all passenger car tires except deep tread, winter type snow tires, space-saver or temporary-use spare tires, and limited production tires**

Treadwear is the wear rate of a tire when tested under controlled conditions. Treadwear is designated by a two or three-digit number representing a percentage of a standard value when a tire is tested in accordance with specified procedures. The higher the number, the better the treadwear.

Traction is a tire's ability to stop on wet pavement under controlled conditions. Traction is indicated by "A", "B", or "C", with "A" signifying the highest traction rating.

Temperature resistance is a tire's resistance to the generation of heat and its ability to dissipate heat when tested under controlled conditions. Temperature is indicated by "A", "B", or "C", with "A" signifying the highest level of performance.