



**WINNER for  
BEST NEW PACKAGING,  
PERFORMANCE CATEGORY  
AAPEX 2015**

## Technician Grade Dielectric Grease

Award-winning **CRC Dielectric Grease** features a patented finger-actuated delivery system. Simply turn the dial on the Select-A-Bead® nozzle to choose the best bead-width for your job. Includes an off position to prevent expelling product. The unique double-piston pressurized can allows for smooth, uniform dispensing from start to finish without air pockets.

**This unique non-curing compound is perfect for sealing, protecting and insulating electrical wiring and connections.**

- Improves electrical performance by reducing arcing, voltage drop and other power-robbing conditions
- Provides maximum control through patented actuator and an easy-depress lever, ensuring uninterrupted product flow and eliminating finger-fatigue
- Waterproofs electrical connections and contacts, and resists oxidation



- ▲ Excellent dielectric properties
- ▲ No waste; no mess
- ▲ Waterproofs contacts
- ▲ Lubricates rubber and plastics
- ▲ Tamper-evident closure
- ▲ No spatter or air pockets
- ▲ Excellent chemical resistance
- ▲ Non-conductive; non-flammable

**Wide Temperature Range: -70°F to 400°F (-57°C to 204°C)**

**USAGE:** For use on electrical connections, including circuit breakers, contacts, spark plug boots, trailer connectors, HEI distributor, battery terminals, lubrication of plastic, rubber parts and o-rings and ignition systems. When finished, remove unwanted grease with petroleum distillates or chlorinated solvents - CRC QD® Electronic Cleaner works great!

Part No.	Package Type	Net Wt.	Units/Case	Unit Dimensions	Case Dimensions
05113	Pressurized Can	3.3 oz.	12	8.75"H x 2"W x 2"D	9.4"H x 8"W x 7.9"D
05113X6	Pressurized Can	3.3 oz.	6	8.75"H x 2"W x 2"D	9.4"H x 4.5"W x 7.4"D
05107	Carded	.28 oz.	12	6.25"H x 4.5"W x 0.75"D	4.87"H x 5.18"W x 6.43"D
05109	Tube	.5 oz.	12	7.88"H x 2.75"W x 1"D	8.13"H x 6"W x 4"D

