



## PRODUCT DATA SHEET

Silaramic® [Brake System Grease](#), 5 Wt Oz  
Part Number: 05361



### Product Description

A synthetic, dry-film, ceramic lubricant formulated to reduce brake noise and vibrations by dampening all brake vibrating frequencies. Will not run off or wash out. Works in extreme temp ranges from -50 to 3000°F. Protects against uneven pad wear.

### Applications

All brake systems and brake components, including calipers, bushings, holes, pins, inserts, anchors, bolts, calipers and boots

### Unit Package Description

5 Ounce Tube

### Brand

CRC

### Generic Description 1

Brake System Grease

### Net Fill

5 Wt Oz

### UPC Code

078254053615

### Unit Dimensions

6.25H x 2W x 2D in

### Units Per Case

12

### Case Dimensions

8H x 6.38W x 7.63D in

### Cases Per Pallet

175

### Case Weight

5 lbs

### I 2 of 5 Code

30078254053616

### Appearance

Off White Semi Solid Grease

### Base Type

Polydimethylsiloxane

### Flash point (F)

550°F

### Flash point (C)

288°C

### Flammability Class - CPSC

None

### Spec Gravity Concentrate

1.0

### NLGI Grade

2

### Timken OK Load [Lbs.]

Not Determined

### Plastic Safe

Yes

### Evaporation Rate

Very Slow

### Dielectric Strength

Not Determined



## PRODUCT DATA SHEET



Working Temp (F)	-50 to 3000°F
Working Temp (C)	-45.6 to 1648.89°C
4 Ball EP	Not Determined
4 Ball Wear	Not Determined
Drop Point	None
Elastomer Compatibility	Compatible
Leakage	0.2
Low Temp Torque	Not Determined
Oil Separation	0.2
Oxidation Stability	Not Determined
Pour Point (F)	Not Determined
Water Washout	0.25
Worked Penetration	265 to 295
Propellant	None
DOT Proper Shipping Name	Not Regulated
VOC % (Federal)	0
VOC g/L (Federal)	0
VOC Lbs./Gal. (Federal)	0
VOC Category	Not Regulated
Removal (How To)	Remove with petroleum solvents.