

12490

SCION XB

EXCLUDES RELEASE SERIES


GROSS LOAD CAPACITY WHEN USED AS A WEIGHT CARRYING HITCH: 3,500 LBS. TRAILER WEIGHT & 350 LBS. TONGUE WEIGHT.

\*\*\*DO NOT EXCEED VEHICLE MANUFACTURER'S RECOMMENDED TOWING CAPACITY.\*\*\*

WARNING: ALL NON-TRAILER LOADS APPLIED TO THIS PRODUCT MUST BE SUPPORTED BY AUXILIARY STABILIZING STRAPS.

Parts List			
ITEM	QTY	PART NUMBER	DESCRIPTION
1	6	M12-1.25 x 30mm	HEX BOLT
2	6	1/2"	CONICAL TOOTHED WASHER


**WELDNUT CLEANING**



To remove debris from weldnuts in frame, spray lubricant or compressed air into hole. For heavy debris, use a small wire brush. (Be careful not to damage threads).

TOOLS REQUIRED
RATCHET
TORQUE WRENCH
19mm SOCKET
17mm SOCKET

FRONT  
↕  
REAR



**HITCH WEIGHT:** 28 LBS.  
**INSTALL TIME**  
 PROFESSIONAL: 20 MINUTES  
 NOVICE (DIY): 45 MINUTES  
**INSTALL NOTES:**  
 - REMOVE TOW HOOK  
 - NO DRILLING REQUIRED

DESIGNED FOR USE WITH BALLMOUNT #55001 / 45501

**INSTALLATION STEPS**

- 1) Remove OEM tow hook from vehicle (if present) and return to owner.
- 2) Raise hitch back into position on vehicle and install hex bolts and conical tooth washers.
- 3) Torque all 12mm fasteners to 86 lb-ft.

**PERIODICALLY CHECK THIS RECEIVER HITCH TO ENSURE THAT ALL FASTENERS ARE TIGHT AND THAT ALL STRUCTURAL COMPONENTS ARE SOUND.**

Curt Manufacturing Inc., warrants this product to be free of defects in material and/or workmanship at the time of retail purchase by the original purchaser. If the product is found to be defective, Curt Manufacturing Inc., may repair or replace the product, at their option, when the product is returned, prepaid, with proof of purchase. Alteration to, misuse of, or improper installation of this product voids the warranty. Curt Manufacturing Inc.'s liability is limited to repair or replacement of products found to be defective, and specifically excludes liability for incidental or consequential loss or damage.