# INSTALLATION INSTRUCTIONS

WARNING: NEVER EXCEED YOUR VEHICLE MANUFACTURER'S RECOMMENDED TOWING CAPACITY

## **ROOFTOP CARGO BAG**



## **WARNINGS**

Read manual carefully before installation or use of this product. The warnings, cautions and instructions discussed in this instruction manual cannot cover all possible conditions or situations that could occur. It must be understood by the operator that common sense and caution are factors which cannot be built into the product and are the responsibility of the end user.

This expandable cargo bag is designed to mount to an existing rooftop carrier. Lashing straps hold the cargo storage bag to the rooftop carrier.

When traveling, periodically check straps to ensure load is securely held. Any excess webbing should be tucked away and tied off to prevent flapping while driving.

After removing contents from the cargo storage bag, remove unit from the rooftop carrier and store for safekeeping. Do not leave empty cargo storage bag on vehicle.

Do not exceed the roof rack's rated load capacity.

## **MAINTENANCE**

It is recommended that the general condition of any cargo bag be examined before it is used. Keep the cargo bag in good repair. Have necessary repairs made by qualified service personnel.

## **ASSEMBLY**

#### Step '

Spread out the cargo storage bag onto the rooftop carrier.

#### Step 2

Unzip the cargo bag and begin loading, placing the larger, heavier objects in first. Continue to load the bag, placing smaller, lighter items on the top to create a compact load.

### Step 3

Close the zipper, making sure the flap is pulled down to completely cover the entire zipper. Seal the bag with the provided hook and loop closures.

#### Step 4


Attach one end of the lashing strap to the rooftop carrier's side bars, as shown in Figure 1.

#### Step 5

Now pull the strap through the loop on top of the cargo bag, as shown in Figure 2. Repeat Step 4 by attaching the other end of lashing strap to the adjacent side of the rooftop carrier.

#### Step 6

Take up slack in straps until the cargo bag is securely attached to the rooftop carrier.






Figure 1

Figure 2

