

98-07 TOYOTA LANDCRUISER & 98-07 LEXUS LX470

Parts List			List	Attaches to existing
ITEM	QTY	PART NUMBER	DESCRIPTION	/ weldnuts in frame
1	4	M12 - 1.25 x 40 HEX	HEX BOLT	(3) places, both sides
2	4	1/2"	CONICAL TOOTHED WASHER	
3	6	M14 - 1.5 x 40 HEX	HEX BOLT	
4	6	9/16	LOCK WASHER	
5	6	9_16 WASHER	FLAT WASHER	
MICHWEIGHT: 40 LBS. MICHWEIGHT: 40 LBS. MICHWEIGHT: 60 MINUTES MICHWEIGHT: 10 LBS. MICHWEIGHT: 10 LBS. MICHWE				ns s.

INSTALLATION STEPS

- 1) Remove the tow hook and (2) tiedowns from rear of vehicle frame, return them along with two (2) fasteners to the vehicle owner. The remaining (2) fasteners will be used in the hitch installation.
- 2) Raise hitch into position while inserting exhaust pipe through large opening in hitch crossmember (postition hitch as shown making sure the rearmost hole in frame is not used).
- 3) Secure hitch by installing fasteners as shown.
- 4) Torque all 12mm hardware to 72 ft-lbs. Torque all 14mm hardware to 110ft-lbs.

PERIODICALLY CHECK THIS RECEIVER HITCH TO ENSURE THAT ALL FASTENERS ARE TIGHT AND THAT ALL STRUCTURAL COMPONENTS ARE SOUND.

Curt Manufacturing Inc., warrants this product to be free of defects in material and/or workmanship at the time of retail purchase by the original purchaser. If the product is found to be defective, Curt Manufacturing Inc., may repair or replace the product, at their option, when the product is returned, prepaid, with proof of purchase. Alteration to, misuse of, or improper installation of this product voids the warranty. Curt Manufacturing Inc.'s liability is limited to repair or replacement of products found to be defective, and specifically excludes liability for incidental or consequential loss or damage.

Learn more about trailer hitches and towing we have.