

## 1. Product and Company Identification

**Product Code:** C260, C261  
**Product Name:** 6XT Diesel Fuel Treatment

## 2. Hazards Identification

Flammable Liquids, Category 4  
Skin Corrosion/Irritation, Category 3  
Carcinogenicity, Category 1B  
Aquatic Toxicity (Chronic), Category 3  
Aquatic Toxicity (Acute), Category 3  
Serious Eye Damage/Eye Irritation, Category 2A  
Germ Cell Mutagenicity, Category 1B



**GHS Signal Word:** **Danger**

**GHS Hazard Phrases:** H227: Combustible liquid.  
H316: Causes mild skin irritation.  
H319: Causes serious eye irritation.  
H340: May cause genetic defects.  
H350: May cause cancer.  
H402: Harmful to aquatic life.  
H412: Harmful to aquatic life with long lasting effects.

**GHS Precaution Phrases:** P201: Obtain special instructions before use.  
P202: Do not handle until all safety precautions have been read and understood.  
P210: Keep away from heat/sparks/open flames/hot surfaces - No smoking.  
P264: Wash hands thoroughly after handling.  
P273: Avoid release to the environment.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P281: Use personal protective equipment as required.

**GHS Response Phrases:** P301+330+331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
P303+361+353: IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.  
P363: Wash contaminated clothing before reuse.  
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P309+311: Call a POISON CENTER or doctor/physician if exposed or you feel unwell.

**GHS Storage and Disposal Phrases:** P403+235: Store in cool/well-ventilated place.  
P501: Dispose of contents/container in accordance with



# SAFETY DATA SHEET

## 6XT Diesel Fuel Treatment

local/regional/national/international regulation.

P405: Store locked up.

### Potential Health Effects (Acute and Chronic):

**Medical Conditions Generally Aggravated By Exposure:** Pre-existing skin conditions and respiratory disorders may be aggravated by exposures to components of this product.

## 3. Composition/Information on Ingredients

CAS #	Hazardous Components (Chemical Name)	Concentration
68476-30-2	Fuel oil, no. 2	90.0 -95.0 %
64742-94-5	Solvent naphtha (petroleum), Heavy arom.	1.3 -3.0 %
111-76-2	Ethanol, 2-Butoxy-	2.0 %
64742-95-6	SC-100 Solvent	1.0 -2.0 %
95-63-6	1,2,4-Trimethylbenzene	0.2 -1.0 %
91-20-3	Naphthalene	0.21 -0.99 %
104-76-7	1-Hexanol, 2-Ethyl-	0.07 -0.33 %
1330-20-7	Xylene (mixed isomers)	< 0.066 %
98-82-8	Cumene	< 0.033 %
108-67-8	Mesitylene	< 0.026 %

## 4. First Aid Measures

**Emergency and First Aid Procedures:** If swallowed, do not induce vomiting. Rinse mouth. If inhaled, remove to fresh air. If not breathing, give artificial respiration. In case of skin contact, wash with soap and large amounts of water. Remove contaminated clothing. If in eyes, flush eyes with large amounts of tepid water for at least 15 minutes. Call physician immediately if adverse reaction occurs.

**Signs and Symptoms Of Exposure:** Exposure to high concentrations may produce headache, giddiness, vertigo and aesthetic stupor.

## 5. Fire Fighting Measures

**Flash Pt:** 60.60 C (141.1 F) Method Used: Pensky-Marten Closed Cup

**Explosive Limits:** LEL: No data. UEL: No data.

**Autoignition Pt:** No data.

**Suitable Extinguishing Media:** For small fires, Class B fire extinguishing media such as CO<sub>2</sub>, dry chemical, foam (AFFF/ATC) or water spray can be used. For large fires, water spray, fog or foam (AFFF/ATC) can be used. Fire fighting should be attempted only by those who are adequately trained and equipped with proper protective equipment.

**Fire Fighting Instructions:** Use NIOSH/MSHA approved positive pressure self-contained breathing apparatus and protective equipment. Avoid using straight water streams. Water spray and foam (AFFF/ATC) must be applied carefully to avoid frothing and spray from as far a distance as possible. Avoid excessive water spray application. Keep surrounding area cool with water spray from a distance and prevent further ignition of combustible material. Keep run-off out of sewers and water sources.

**Flammable Properties and Hazards:** This product has been determined to be a combustible liquid per the OSHA Hazard Communication Standard and should be handled accordingly. For additional fire related information, see NFPA 30 or the North American Emergency Response Guide 128.



# SAFETY DATA SHEET

## 6XT Diesel Fuel Treatment

### 6. Accidental Release Measures

**Steps To Be Taken In Case Material Is Released Or Spilled:** Keep public away. Isolate and evacuate area. Shut off source if safe to do so. Eliminate all ignition sources. Advise authorities and National Response Center if substance has entered a watercourse or sewer. Notify local health and pollution control agencies, if appropriate. Contain liquid with sand or soil. Recover and return free product to proper containers. Use suitable absorbent materials such as vermiculite, sand, or clay to clean up residual liquids.

### 7. Handling and Storage

**Precautions To Be Taken in Handling:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces - No smoking. Wash hands thoroughly after handling. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. Use personal protective equipment as required. Keep out of the reach of children.

**Precautions To Be Taken in Storing:** Store locked up. Store in cool/well-ventilated place.

### 8. Exposure Controls/Personal Protection

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
68476-30-2	Fuel oil, no. 2	No data.	TLV: 100 mg/m3	No data.
64742-94-5	Solvent naphtha (petroleum), Heavy arom.	No data.	No data.	No data.
111-76-2	Ethanol, 2-Butoxy-	PEL: 50 ppm	TLV: 20 ppm	No data.
64742-95-6	SC-100 Solvent	No data.	No data.	No data.
95-63-6	1,2,4-Trimethylbenzene	No data.	No data.	No data.
91-20-3	Naphthalene	PEL: 10 ppm	TLV: 10 ppm STEL: 15 ppm	No data.
104-76-7	1-Hexanol, 2-Ethyl-	No data.	No data.	No data.
1330-20-7	Xylene (mixed isomers)	PEL: 100 ppm	TLV: 100 ppm STEL: 150 ppm	No data.
98-82-8	Cumene	PEL: 50 ppm	TLV: 50 ppm	No data.
108-67-8	Mesitylene	No data.	No data.	No data.

**Respiratory Equipment (Specify Type):** Use approved organic vapor chemical cartridge or supplied air respirators when material produces vapors that exceed permissible limits or excessive vapors are generated. Observe respirator protection factor criteria cited in ANSI Z88.2. Self-contained breathing apparatus should be used for fire fighting.

**Eye Protection:** No special eye protection is normally required. Where splashing is possible, wear safety glasses with side shields.

**Protective Gloves:** Neoprene, nitrile, PVA, polyvinyl chloride and polyurethane gloves to prevent skin contact.

**Other Protective Clothing:** No data available.

**Engineering Controls (Ventilation etc.):** Local or general exhaust required when using at elevated temperatures that generate vapors or mists.

**Work/Hygienic/Maintenance Practices:** No special clothing is normally required. Select protective clothing depending on industrial operations. Use mechanical ventilation equipment that is explosion-proof.



## 9. Physical and Chemical Properties

<b>Physical States:</b>	[ ] Gas [ X ] Liquid [ ] Solid
<b>Appearance and Odor:</b>	Transparent, reddish brown liquid with petroleum odor.
<b>Melting Point:</b>	No data.
<b>Boiling Point:</b>	360.00 F (182.2 C) - 550.00 F (287.8 C)
<b>Autoignition Pt:</b>	No data.
<b>Flash Pt:</b>	60.60 C (141.1 F) Method Used: Pensky-Marten Closed Cup
<b>Explosive Limits:</b>	LEL: No data. UEL: No data.
<b>Specific Gravity (Water = 1):</b>	0.836 - 0.856
<b>Density:</b>	6.972 - 7.139 at 70.0 F (21.1 C)
<b>Vapor Pressure (vs. Air or mm Hg):</b>	No data.
<b>Vapor Density (vs. Air = 1):</b>	No data.
<b>Evaporation Rate:</b>	No data.
<b>Solubility in Water:</b>	No data.
<b>Viscosity:</b>	water thin
<b>Percent Volatile:</b>	10.0 % by weight.

## 10. Stability and Reactivity

<b>Stability:</b>	Unstable [ ] Stable [ X ]
<b>Conditions To Avoid - Instability:</b>	This material is stable at 70F, 760 mm pressure.
<b>Incompatibility - Materials To Avoid:</b>	Strong oxidizers such as nitrates, perchlorates, chlorine, flourine.
<b>Hazardous Decomposition Or Byproducts:</b>	Combustion produces carbon monoxide, aldehydes, aromatic and other hydrocarbons.
<b>Possibility of Hazardous Reactions:</b>	Will occur [ ] Will not occur [ X ]
<b>Conditions To Avoid - Hazardous Reactions:</b>	No data available.

## 11. Toxicological Information

**Toxicological Information:** Lifetime skin painting studies in animals with similar distillate fuels have produced weak to moderate carcinogenic activity following prolonged and repeated exposure. Similar middle distillates, when tested at nonirritating dose levels, did not show any significant carcinogenic activity indicating that this tumorigenic response is likely related to chronic irritation and not to dose. Repeated dermal application has produced severe irritation and systemic toxicity in subacute toxicity studies. Some components of this product, have been shown to produce a species specific, sex hormonal dependent kidney lesion in male rats from repeated oral or inhalation exposure. Subsequent research has shown that the kidney damage develops via the formation of a alpha-2u-globulin, a mechanism unique to the male rat. Humans do not form alpha-2u-globulin, therefore, the kidney effects resulting from this mechanism are not relevant in humans. Some components of this product were found to be positive in a few mutagenicity tests while negative in the majority of others. The exact relationship between these results and human health is not known.

Summary of health effect data on distillate fuel components:

This products sub-components may contain >.01% naphthalene. Exposure to



# SAFETY DATA SHEET

## 6XT Diesel Fuel Treatment

Page: 5

Revision: 02/12/2015

Supersedes Revision: 10/10/2014

naphthalene at 30 ppm for two years caused lung tumors in female mice. Male mice with the same exposure did not develop tumors. Exposure to 10-60 ppm naphthalene for 2 years caused tumors in the tissue lining of the nose and respiratory tract in male and female rats. Oral administration of 133-267 mg/kg/day of naphthalene in mice for up to 90 days did not produce mortality, systemic toxicity, adversely affect organ or body weight or produce changes in blood. Repeated oral administration of naphthalene produced an anemia in dogs. Repeated intraperitoneal doses of naphthalene produced lung damage in mice. Repeated high doses of naphthalene has caused the formation of cataracts and retinotoxicity in the eyes of rats and rabbits due to accumulation of 1,2-naphthoquinone, a toxic metabolite. Effects in human eyes is uncertain and not well documented. Pregnant rats administered intraperitoneal doses of naphthalene during gestation gave birth to offspring that had delayed heart and bone development. Pregnant mice given near lethal doses of naphthalene showed no significant maternal toxicity and a reduction in the number of pups per litter, but no gross abnormalities in offspring. Suppressed spermiogenesis and progeny development have been reported in mice, rats and guinea pigs after exposure to high concentrations of naphthalene in their drinking water. Certain groups or individuals, i.e., infants, Semites, Arabs, Asians and Blacks, with a certain blood enzyme deficiency (glucose-6-phosphate dehydrogenase) are particularly susceptible to hemolytic agents and can rapidly develop hemolytic anemia and systemic poisoning from ingestion or inhalation of naphthalene.

CAS# 68476-30-2:

Other Studies:, TDLo, Skin, Species: Rabbit, 100.0 ML/KG, 12 D.

Results:

Skin and Appendages: Skin: After systemic exposure: Dermatitis, irritative.

Nutritional and Gross Metabolic: Weight loss or decreased weight gain.

Related to Chronic Data - death.

- "Toxicology of Petroleum Hydrocarbons, Proceedings of the Symposium, 1st, 1982," MacFarland, H.N., et al., eds., Washington, DC, American Petroleum Institute, 1983 Volume, Vol/p/yr: 1,1, 1983

Acute toxicity, LD50, Oral, Rat, 12.00 GM/KG.

Results:

Behavioral: Somnolence (general depressed activity).

- Advances in Modern Environmental Toxicology., Senate Press, Inc., P.O. Box 252, Princeton Junction, NJ 08550, Vol/p/yr: 6,1, 1984

Acute toxicity, LD (Lethal dose), Skin, Species: Rabbit, 5.000 GM/KG.

Results:

Behavioral: Tremor.

Behavioral: Convulsions or effect on seizure threshold.

- Advances in Modern Environmental Toxicology., Senate Press, Inc., P.O. Box 252, Princeton Junction, NJ 08550, Vol/p/yr: 6,1, 1984

Tumorigenic Effects:, TDLo, Skin, Mouse, 243.0 GM/KG, 97 W.

Results:

Tumorigenic: Carcinogenic by RTECS criteria.

Skin and Appendages: Other: Tumors.

- Fundamental and Applied Toxicology., Academic Press, Inc., 1 E. First St., Duluth, MN 55802, Vol/p/yr: 9,297, 1987

Standard Draize Test, Skin, Species: Rabbit, 500.0 MG, 24 H, Moderate.

Results:



# SAFETY DATA SHEET

## 6XT Diesel Fuel Treatment

Revision: 02/12/2015  
Supersedes Revision: 10/10/2014

Brain and Coverings: Changes in surface EEG.

- "Toxicology of Petroleum Hydrocarbons, Proceedings of the Symposium, 1st, 1982,"  
MacFarland, H.N., et al., eds., Washington, DC, American Petroleum Institute, 1983  
Volume, Vol/p/yr: 1,1, 1983

Standard Draize Test, Eyes, Species: Rabbit, 100.0 MG, 30 S, Mild.

Results:

Behavioral: Somnolence (general depressed activity).

- "Toxicology of Petroleum Hydrocarbons, Proceedings of the Symposium, 1st, 1982,"  
MacFarland, H.N., et al., eds., Washington, DC, American Petroleum Institute, 1983  
Volume, Vol/p/yr: 1,1, 1983

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
68476-30-2	Fuel oil, no. 2	n.a.	2B	A3	n.a.
64742-94-5	Solvent naphtha (petroleum), Heavy arom.	n.a.	n.a.	n.a.	n.a.
111-76-2	Ethanol, 2-Butoxy-	n.a.	3	A3	n.a.
64742-95-6	SC-100 Solvent	n.a.	n.a.	n.a.	n.a.
95-63-6	1,2,4-Trimethylbenzene	n.a.	n.a.	n.a.	n.a.
91-20-3	Naphthalene	Possible	2B	A4	n.a.
104-76-7	1-Hexanol, 2-Ethyl-	n.a.	n.a.	n.a.	n.a.
1330-20-7	Xylene (mixed isomers)	n.a.	3	A4	n.a.
98-82-8	Cumene	n.a.	2B	n.a.	n.a.
108-67-8	Mesitylene	n.a.	n.a.	n.a.	n.a.

## 12. Ecological Information

### General Ecological Information:

Product can cause fouling of shoreline and may be harmful to aquatic life in low concentrations. The 96 hour LL50 values for an accomadated fraction (WAF) of fuel oil ranged from 3.2 to 65 mg/l in fish and 2-210 mg/l in invertebrates. EL 50 values for inhibition of algal growth ranged from 1.8 to 2.9 mg/l for No. 2 fuel oil and from 10 to 78 mg/l for diesel fuel. This product does not concentrate or accumulate in the food chain. If released to soil and water, this product is expected to biodegrade under both aerobic and anaerobic conditions.

Environmental Hazards: TOXIC TO AQUATIC ORGANISMS. MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT.

Environmental Fate: THIS PRODUCT CONTAINS COMPONENTS WHICH MAY BE PERSISTENT IN THE ENVIRONMENT.

## 13. Disposal Considerations

### Waste Disposal Method:

Dispose of contents/container in accordance with local/regional/national/international regulation.



**14. Transport Information**

**LAND TRANSPORT (US DOT):**

**DOT Proper Shipping Name:** Not-Restricted  
**DOT Hazard Class:**  
**UN/NA Number:**

**LAND TRANSPORT (European ADR/RID):**

**ADR/RID Shipping Name:** Not-Restricted  
**UN Number:**  
**Hazard Class:**

**MARINE TRANSPORT (IMDG/IMO):**

**IMDG/IMO Shipping Name:** Not-Restricted  
**UN Number:**  
**Hazard Class:**

**Packing Group:**

**Marine Pollutant:** No

**AIR TRANSPORT (ICAO/IATA):**

**ICAO/IATA Shipping Name:** Not-Restricted

**15. Regulatory Information**

**EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists**

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
68476-30-2	Fuel oil, no. 2	No	No	No
64742-94-5	Solvent naphtha (petroleum), Heavy arom.	No	No	No
111-76-2	Ethanol, 2-Butoxy-	No	No	Yes-Cat. N230
64742-95-6	SC-100 Solvent	No	No	No
95-63-6	1,2,4-Trimethylbenzene	No	No	Yes
91-20-3	Naphthalene	No	Yes 100 LB	Yes
104-76-7	1-Hexanol, 2-Ethyl-	No	No	No
1330-20-7	Xylene (mixed isomers)	No	Yes 100 LB	Yes
98-82-8	Cumene	No	Yes 5000 LB	Yes
108-67-8	Mesitylene	No	No	No

**CAS # Hazardous Components (Chemical Name)**

**Other US EPA or State Lists**

68476-30-2	Fuel oil, no. 2	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No
64742-94-5	Solvent naphtha (petroleum), Heavy arom.	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No
111-76-2	Ethanol, 2-Butoxy-	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: TAC, Title 8; MA Oil/HazMat: Yes; MI CMR, Part 5: Part 5; NC TAP: Yes - Cat.; NJ EHS: Yes - 0275; NY Part 597: No; PA HSL: Yes - 1; SC TAP: Yes - Cat.; WI Air: Yes
64742-95-6	SC-100 Solvent	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No



# SAFETY DATA SHEET

## 6XT Diesel Fuel Treatment

Revision: 02/12/2015

Supersedes Revision: 10/10/2014


95-63-6	1,2,4-Trimethylbenzene	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory, 4 Test; CA PROP.65: No; CA TAC, Title 8: TAC; MA Oil/HazMat: Yes; MI CMR, Part 5: No; NC TAP: No; NJ EHS: Yes - 2716; NY Part 597: No; PA HSL: Yes - E; SC TAP: No; WI Air: No
91-20-3	Naphthalene	CAA HAP,ODC: HAP; CWA NPDES: Yes; TSCA: Yes - Inventory, 4 Test, 8A PAIR; CA PROP.65: Yes; CA TAC, Title 8: TAC, Title 8; MA Oil/HazMat: Yes; MI CMR, Part 5: Part 5; NC TAP: Yes; NJ EHS: Yes - 1322; NY Part 597: Yes; PA HSL: Yes - E; SC TAP: Yes; WI Air: Yes
104-76-7	1-Hexanol, 2-Ethyl-	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory, 8D TERM; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: Yes; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: Yes - 1; SC TAP: No; WI Air: No
1330-20-7	Xylene (mixed isomers)	CAA HAP,ODC: HAP; CWA NPDES: Yes; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: TAC, Title 8; MA Oil/HazMat: Yes; MI CMR, Part 5: CMR, Part 5; NC TAP: Yes; NJ EHS: Yes - 2014; NY Part 597: Yes; PA HSL: Yes - E; SC TAP: Yes; WI Air: Yes
98-82-8	Cumene	CAA HAP,ODC: HAP; CWA NPDES: No; TSCA: Yes - Inventory, 4 Test; CA PROP.65: Yes; CA TAC, Title 8: TAC, Title 8; MA Oil/HazMat: Yes; MI CMR, Part 5: Part 5; NC TAP: Yes; NJ EHS: Yes - 0542; NY Part 597: Yes; PA HSL: Yes - E; SC TAP: Yes; WI Air: Yes
108-67-8	Mesitylene	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory, 4 Test; CA PROP.65: No; CA TAC, Title 8: Title 8; MA Oil/HazMat: Yes; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No
<b>CAS #</b>	<b>Hazardous Components (Chemical Name)</b>	<b>International Regulatory Lists</b>
68476-30-2	Fuel oil, no. 2	Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes
64742-94-5	Solvent naphtha (petroleum), Heavy arom.	Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes
111-76-2	Ethanol, 2-Butoxy-	Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes
64742-95-6	SC-100 Solvent	Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes
95-63-6	1,2,4-Trimethylbenzene	Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes
91-20-3	Naphthalene	Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes
104-76-7	1-Hexanol, 2-Ethyl-	Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes
1330-20-7	Xylene (mixed isomers)	Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes
98-82-8	Cumene	Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes - 081-01
108-67-8	Mesitylene	Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes



### 16. Other Information

Revision Date: 02/12/2015

Hazard Rating System:



**Additional Information About This Product:** No data available.

**Company Policy or Disclaimer:**

Cyclo Industries, Inc. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. Individuals receiving this information must exercise their independent judgment in determining its appropriateness for a particular purpose. Cyclo Industries, Inc. makes no representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose with respect to the information set forth herein or to the product to which the information refers. Accordingly, Cyclo Industries, Inc. will not be responsible for damages resulting from use of or reliance upon this information.