

Truek and Jeep Accessories

KJ71034BK / KJ71034TN 2011 & up JEEP JK Lower Switch Panel JEEP JK upper dash bezel





Instruction Sheet: P20906-02 2013 Daystar Products International Inc.

Introduction



is your number one source for Made In The USA quality, Comfort RideTM leveling kits. Now backed with our exclusive *Go Everywhere* © Lifetime Lim-

ited Warranty. To assure your safety and prop-er installation of this product, take a moment to read all instructions and Prod-uct Safety Information before trying to install your Daystar® product. Current OEM suspension design is complex: meaning safe and proper installation requires understanding OEM service techniques for disassembly and assembly of the components indicated together with the instructions and warnings set out below and in the OEM service manual and your owner's manual. Daystar® strongly recommends seeking advice from or having this product installed by a professional mechanic who can inspect your suspension, confirm compatibility with your tire and wheel choice and, if needed, reset alignment to optimize your steering and the features of your Daystar® Comfort Ride kit. We are here to help if you have remaining technical questions after reading these instructions.

Product Safety Information

Throughout these instructions important safety information is generally preceded by one of three signal words indicating the relative risk of injury. The signal words mean:

! WARNING A hazardous situation which, if not avoided, could result in death or serious injury. You can be Killed or Seriously Hurt if you don't follow instructions.

! CAUTION A hazardous situation which, if not avoided, could result in minor or moderate injury. You can be moderately HURT and also may suffer property damage if you don't follow instructions.

NOTICE Careful attention is required to this instruction or operation but does generally not relate to personal injury. Damage to your product or other property may result if you don't follow instructions.

!WARNING

Familiarize yourself with all vehicle manufactures' and Daystar warnings and limited warranties before driving your vehicle. Also be aware many states / countries have laws governing on-road vehicle modifications. You are responsible for assuring the safety and legality of your vehicle.

Tools Needed

Quantity	Description
1	Masking tape (low adhesive tack)
1	Gloves
1	Trim removal tool (plastic flat pry tool)
1	pliers
1	Razor knife or Ezacto knife
1	File

Part List Bill of Materials

Quan- tity	Part Number	Description
1	KJ71034BK or KJ71034TN	Lower switch panel

!Warning: Always work with appropriate personal safety gear including safety glasses, gloves and hearing protection if using air powered tools.

Begin by inspecting the components & hardware for damage. Then compare components & hardware to the bill of materials for completeness. If anything is missing/damaged, do not proceed with the installation.

Installation Instructions

- 1. Set vehicle parking brake and pull the 4wd lever back to neutral and place the trans in 2nd gear.
- 2. **NOTICE:** This part KJ71034BK or KJ71034TN Will **NOT** fit vehicle With manual transmission.
- 3. Remove factory center console.
- 4. Place tape around center dash panel to protect edged of Dash board and panel. **NOTICE:** Use painters low tack Masking tape so not to transfer tape glue to dash.
- 5. Use plastic trim pry tools to remove center panel trim, push in and slide tool to side to unclip and pull out
- 6. With panel removed use pliers to remove 2 clips, on back. **NOTICE:** Take care not to break the clips.
- 7. The Daystar switch panel will hold 1 to 5 switches ,trim out holes for the switches your going to use.
- 8. Working from back side of panel use a razor blade knife and Cutout the switch holes **NOTICE:** cut hole smaller and use a file to adjust hole to proper size for snug fit of switches.
- 9. Install the 2 clips on the switch panel, (push clip down onto back of panel studs).
- 10. Wire switches to desired items, per their instructions.
- 11. Install the Daystar switch panel by putting lower pins in first then align rear clips and push in till they snaps into place. **NOTICE:**

Pull wire harness back into dash opening to relieve pressure of harness pushing panel out and un clipping panel.





Daystar Rocker Switch Wiring Diagram Back Side of switch

Blank		7	Ground for lamp	
Power In	-2-		Blank	
Power Out	_3_		Blank	