

DeatschWerks

94-98 240SX (S14) and 99+ Silvia (S15) DW200/300 Fuel Pump Installation Guide

9-201/301-1024

94-98 240SX (S14) and 99+ Silvia (S15) DW200/300 Fuel Pump Installation Guide



Parts List:

- DW200/300
- Fuel Hose
- Hose Clamps (x2)
- Fuel Sock
- 10" Electrical Connector
- Fuel Pump Isolator

DeatschWerks

94-98 240SX (S14) and 99+ Silvia (S15) DW200/300 Fuel Pump Installation Guide

94-98 S14 and 99+ S15 DW200/300 Fuel Pump Install

PLEASE READ – this guide is intended to aid in the installation of our products. It is recommended that factory manuals or instructions are followed to remove the fuel pump assembly from the vehicle. Some instructions in this guide are generic. The factory manual should supersede any contradiction.

Below is a picture of suggested tools that will make the installation process easier.



94-98 240SX (S14) and 99+ Silvia (S15) DW200/300 Fuel Pump Installation Guide

1 – remove the fuel pump from the assembly



2 – the hose supplied in the DW installation kit may need to be shortened for proper fitment



94-98 240SX (S14) and 99+ Silvia (S15) DW200/300 Fuel Pump Installation Guide

3 – prep the DW pump for installation



4 – wire the electrical connector's leads to the assembly wires

5 – install the DW pump into the assembly



DeatschWerks

94-98 240SX (S14) and 99+ Silvia (S15) DW200/300 Fuel Pump Installation Guide

6 – reinstall the assembly into the fuel tank and attach a length of hose to the outlet of the pump assembly allowing it to drain into a fuel safe container and prime the fuel pump assembly

7 – cycle the key to the on position as many times as required to prime the pump assembly and evacuate the air introduced during the pump installation process

8 – attach supply line to the outlet of the pump assembly

