DELINTE -

Series	Size	LI SI	Approved	Tread Depth		Overall		Section Width		Max.Load		Max.Pressure		Revs	1012 20
			Rim	1/32"		Dian inch	neter mm	inch	mm	lbs	kg	psi	kPa	Per Mile	UTQG
80	155/80R13	79 T	4.0-4.5-5.0	9.2	7.3	22.8	578	6.2	157	963	437	44	300	913	420/A/A
	145/70R13	71 T	3.5- 4.5 -5.0	9.2	7.3	21.0	534	5.9	150	761	345	44	300	988	420/A/A
	155/70R13	75 T	4.0-4.5-5.0	9.2	7.3	21.6	548	6.2	157	853	387	44	300	963	420/A/A
	165/70R13	79 T/H	4.0- 5.0 -5.5	9.2	7.3	22.1	562	6.7	170	963	437	44	300	939	420/A/A
	175/70R13	82 T/H	4.5-5.0-6.0	9.2	7.3	22.7	576	7.0	177	1047	475	44	300	916	420/A/A
70	165/70R14	81 T/H	4.0- 5.0 -5.5	9.3	7.4	23.1	588	6.7	170	1019	462	44	300	897	420/A/A
70	175/70R14	88 T/H XL	5.0-5.5-6.0	9.3	7.4	23.7	602	7.0	177	1235	560	49	340	876	420/A/A
	185/70R14	88 T/H	4.5-5.5-6.0	9.3	7.4	24.3	616	7.4	189	1235	560	44	300	856	420/A/A
	195/70R14	91 T/H	5.0-6.0-6.5	9.3	7.4	24.8	630	7.9	201	1356	615	44	300	837	420/A/A
	215/70R15	98 H	5.5- 6.5 -7.0	9.6	7.6	26.9	683	8.7	221	1653	750	44	300	772	420/A/A
	215/70R16	100 H	5.5- 6.5 -7.0	9.6	7.6	27.9	708	8.7	221	1764	800	44	300	745	420/A/A
	155/65R13	73 T	4.5-5.0-5.5	9.2	7.3	20.9	532	6.2	157	805	365	44	300	992	420/A/A
65	155/65R14	75 T	4.5-5.0-5.5	9.4	7.4	22.0	558	6.2	157	853	387	44	300	945	420/A/A
	165/65R13	77 T/H	4.5- 5.0 -6.0	9.2	7.3	21.4	544	6.7	170	908	412	44	300	970	420/A/A
	165/65R14	79 T/H	4.5- 5.0 -6.0	9.3	7.4	22.4	570	6.7	170	963	437	44	300	926	420/A/A
		82 H/T	5.0 -5.5-6.0	9.3	7.4	23.0	584	7.0	177	1047	475	44	300	903	420/A/A
	175/65R14	86 T XL	5.0 -5.5-6.0	9.3	7.4	23.0	584	7.0	177	1168	530	49	340	903	420/A/A
	185/65R14	86 T/H	5.0-5.5-6.5	9.3	7.4	23.5	596	7.4	189	1168	530	44	300	885	420/A/A
	175/65R15	84 T/H	5.0 -5.5-6.0	9.6	7.6	24.0	609	7.0	177	1102	500	44	300	866	420/A/A
	185/65R15	88 T/H	5.0-5.5-6.5	9.6	7.6	24.4	621	7.4	189	1235	560	44	300	850	420/A/A
60	195/65R15	91 H/V	5.5- 6.0 -7.0	9.6	7.6	25.0	635	7.9	201	1356	615	44	300	831	420/A/A
	195/65R15	95 H XL	5.5- 6.0 -7.0	9.6	7.6	25.0	635	7.9	201	1521	690	49	340	831	420/A/A
	205/65R15	94 H	5.5- 6.0 -7.5	9.6	7.6	25.5	647	8.2	209	1477	670	44	300	815	420/A/A
	205/65R16	99 H/V XL	5.5-6.0-7.5	9.6	7.6	26.5	672	8.2	209	1709	775	49	340	785	420/A/A
	215/65R16	102 H XL	6.0- 6.5 -7.5	9.6	7.6	27.0	686	8.7	221	1874	850	49	340	769	420/A/A
	225/65R16	100 H	6.0- 6.5 -8.0	9.6	7.6	27.5	698	9.0	228	1764	800	44	300	756	420/A/A
	165/60R14	75 H	4.5- 5.0 -6.0	9.3	7.4	21.8	554	6.7	170	853	387	44	300	952	420/A/A
	175/60R14	79 T	5.0 -5.5-6.0	9.3	7.4	22.3	566	7.0	177	963	437	44	300	932	420/A/A
	185/60R14	82 H	5.0- 5.5 -6.5	9.3	7.4	22.8	578	7.4	189	1047	475	44	300	913	420/A/A
	195/60R14	86 H	5.5- 6.0 -7.0	9.3	7.4	23.2	590	7.9	201	1168	530	44	300	894	420/A/A
	185/60R15	84 H	5.0- 5.5 -6.5	9.6	7.6	23.7	603	7.4	189	1102	500	44	300	875	420/A/A
	195/60R15	88 H/V	5.5- 6.0 -7.0	9.6	7.6	24.2	615	7.9	201	1235	560	44	300	858	420/A/A
	205/60R15	91 V	5.5- 6.0 -7.0	9.6	7.6	24.7	627	8.2	209	1356	615	44	300	841	420/A/A
-	205/60R16	92 H/V	5.5-6.0-7.5	9.6	7.6	25.7	652	8.2	209	1389	630	44	300	809	420/A/A
	215/60R16	99 H/V XL	6.0- 6.5 -7.5	5.0	7.6	26.1	664	8.7	221	1709	775	49	340	794	420/A/A
	225/60R16	98 H	6.0- 6.5 -8.0	9.6	7.6	26.6	676	9.0	228	1653	750	44	300	780	420/A/A
		100 H XL	6.0- 6.5 -7.5	9.6	7.6	27.2	690	8.7	221	1764	800	49	340	765	420/A/A
	215/60R17	96 H	6.0- 6.5 -7.5	9.6	7.6	27.2	690	8.7	221	1565	710	44	300	765	420/A/A
	225/60R18	100 H/V	6.0- 6.5 -8.0	9.6	7.6	28.6	727	9.0	228	1764	800	49	340	726	420/A/A

	185/55R15	82 V	5.0- 6.0 -6.5	9.6	7.6	23.0	585	7.6	194	1047	475	44	300	902	420/A/A
55	195/55R15	85 V	5.5- 6.0 -7.0	9.6	7.6	23.4	595	7.9	201	1135	515	44	300	887	420/A/A
	195/55ZR16	87 W	5.5- 6.0 -7.0	9.6	7.6	24.4	620	7.9	201	1201	545	44	300	851	420/A/A
	205/55ZR16	91 W/V		9.6	7.6	24.9	632	8.4	214	1356	615	44	300	835	420/A/A
	203/332K10	94 W XL	5.5- 6.5 -7.5	9.0	7.0		032		214	1477	670	49	340	835	420/A/A
	215/55ZR16	97 W XL	6.0- 7.0 -7.5	9.6	7.6	25.3	642	8.9	226	1609	730	49	340	822	420/A/A
	225/55ZR16	99 W XL	6.0- 7.0 -8.0	9.6	7.6	25.7	654	9.2	233	1709	775	49	340	807	420/A/A
	205/55ZR17	95 W XL	5.5- 6.5 -7.5	9.8	7.8	25.9	658	8.4	214	1521	690	49	340	802	500/A/A
		94 W		0.6	76	26.2	660	0.0	226	1477	670	44	300	790	420/A/A
	215/55ZR17	98 W XL	6.0- 7.0 -7.5	9.6	7.6	26.3	668	8.9	226	1653	750	49	340	790	420/A/A
	225/55ZR17	101 W XL	6.0- 7.0 -8.0	9.6	7.6	26.8	680	9.2	233	1819	825	49	340	776	420/A/A
	225/55ZR18	102 W XL	6.0-7.0-8.0	9.6	7.6	27.8	705	9.2	233	1874	850	49	340	748	420/A/A
	235/55ZR18	104 W XL	6.5- 7.5 -8.5	9.6	7.6	28.1	715	9.6	245	1984	900	49	340	738	420/A/A
50 45	195/50R15	82 V	5.5- 6.0 -7.0	9.6	7.6	22.7	577	7.9	201	1047	475	44	300	914	420/A/A
	205/50ZR16	87 W	5.5- 6.5 -7.5	9.6	7.6	24.1	612	8.4	214	1201	545	44	300	862	420/A/A
	205/50ZR17	93 W XL	5.5- 6.5 -7.5	9.6	7.6	25.1	638	8.4	214	1433	650	49	340	827	420/A/A
	215/50ZR17	95 W XL	6.0-7.0-7.5	9.6	7.6	25.5	648	8.9	226	1521	690	49	340	814	420/A/A
	225/50ZR17	98 W XL	6.0- 7.0 -8.0	9.6	7.6	25.9	658	9.2	233	1653	750	49	340	802	420/A/A
	225/50ZR18	99 W XL	6.0- 7.0 -8.0	9.6	7.6	26.9	683	9.2	233	1709	775	49	340	772	420/A/A
	235/50ZR18	101 W XL	6.5- 7.5 -8.5	9.6	7.6	27.3	693	9.6	245	1819	825	49	340	761	420/A/A
	185/45R15	75 V	6.0 -7.0	10.1	8.0	21.5	547	7.2	183	853	387	44	300	964	420/A/A
	195/45R15	78 V	6.0- 6.5 -7.5	10.1	8.0	21.9	557	7.7	195	937	425	44	300	947	420/A/A
	195/45R16	84 V XL	6.0- 6.5 -7.5	9.8	7.8	22.9	582	7.7	195	1102	500	49	340	906	420/A/A
	215/45ZR17	91 W XL	7.0 -7.5-8.0	9.6	7.6	24.6	626	8.4	213	1356	615	49	340	843	420/A/A
	225/45ZR17	94 W XL	7.0- 7.5 -8.5	9.6	7.6	25.0	634	8.9	225	1477	670	49	340	832	420/A/A
	235/45ZR17	97 W XL	7.5- 8.0 -9.0	9.6	7.6	25.4	644	9.3	236	1609	730	49	340	819	420/A/A
	245/45ZR17	99 W XL	7.5- 8.0 -9.0	9.6	7.6	25.7	652	9.6	243	1709	775	49	340	809	420/A/A
	225/45ZR18	95 W XL	7.0- 7.5 -8.5	9.6	7.6	25.9	659	8.9	225	1521	690	49	340	801	420/A/A
	235/45ZR18	98 W XL	7.5- 8.0 -9.0	9.6	7.6	26.3	669	9.3	236	1653	750	49	340	789	420/A/A
	245/45ZR18	100 W XL	7.5 -8.0- 9.0	9.6	7.6	26.7	677	9.6	243	1764	800	49	340	779	420/A/A
	165/40R17	72 V XL	6.0	9.8	7.8	22.2	564	6.7	170	783	355	49	340	935	420/A/A
40	205/40ZR17	84 W XL	7.0-7.5-8.0	9.6	7.6	23.5	596	8.3	212	1102	500	49	340	885	420/A/A
	245/40ZR17	95 W XL	8.0- 8.5 -9.5	9.6	7.6	24.7	628	9.8	248	1521	690	49	340	840	420/A/A
	165/40R18	85 V XL		9.8	7.8	23.2	589	6.7	170	1135					
			6.0	9.6	7.6	24.8	629	8.6	218		515	49	340	896	420/A/A
	215/40ZR18	89 W XL	7.0- 7.5 -8.5							1279	580	49	340	839	420/A/A
	225/40ZR18	92 W XL	7.5- 8.0 -9.0	9.6	7.6	25.1	637	9.1	230	1389	630	49	340	828	420/A/A
	235/40ZR18	95 W XL	8.0- 8.5 -9.5	9.6	7.6	25.4	645	9.5	241	1521	690	49	340	818	420/A/A
	245/40ZR18	97 W XL	8.0- 8.5 -9.5	9.6	7.6	25.7	653	9.8	248	1609	730	49	340	808	420/A/A
35	185/35R17	82 V XL	6.5	9.8	7.8	21.9	556	7.9	200	1047	475	49	340	949	420/A/A
	205/35R18	81 H XL	7.5	9.8	7.8	23.7	601	8.3	212	1019	462	49	340	878	420/A/A
	215/35ZR18	84 W XL	7.0- 7.5 -8.5	9.6	7.6	23.9	607	8.6	218	1102	500	49	340	869	420/A/A
	255/35ZR18	94 W XL	8.5 -9.0 -10.0	9.6	7.6	25.0	635	10.2	260	1477	670	49	340	831	420/A/A

Bold designates measuring rim width. These data can be changed by manufacturer without prior notice.