

# DELINTE

| Series | Size       | LI SI     | PR      | Approved Rim         | Tread Depth |      | Overall Diameter |     | Section Width |     | Max.Load         |      | Max.Load         |      | Max.Pressure |     | Revs Per Mile |
|--------|------------|-----------|---------|----------------------|-------------|------|------------------|-----|---------------|-----|------------------|------|------------------|------|--------------|-----|---------------|
|        |            |           |         |                      | 1/32"       | MM   | inch             | mm  | inch          | mm  | lbs <sup>S</sup> | kg   | lbs <sup>D</sup> | kg   | psi          | kPa |               |
| 65     | 205/65R15C | 102/100 T | 6PR/LRC | 5.5- <b>6.0</b> -6.5 | 12.6        | 10   | 25.5             | 647 | 8.2           | 209 | 1874             | 850  | 1764             | 800  | 55           | 375 | 815           |
|        | 195/65R16C | 104/102 T | 8PR/LRD | <b>5.5-6.0</b>       | 11.6        | 9.2  | 26.0             | 660 | 7.9           | 201 | 1984             | 900  | 1874             | 850  | 69           | 475 | 799           |
|        | 205/65R16C | 107/105 T | 8PR/LRD | 5.5- <b>6.0</b> -6.5 | 12.2        | 9.7  | 26.5             | 672 | 8.2           | 209 | 2149             | 975  | 2039             | 925  | 69           | 475 | 785           |
|        | 215/65R16C | 109/107 T | 8PR/LRD | 6.0- <b>6.5</b> -7.0 | 12.2        | 9.7  | 27.0             | 686 | 8.7           | 221 | 2271             | 1030 | 2149             | 975  | 69           | 475 | 769           |
|        | 225/65R16C | 112/110 T | 8PR/LRD | 6.0- <b>6.5</b> -7.0 | 12.2        | 9.7  | 27.5             | 698 | 9.0           | 228 | 2469             | 1120 | 2337             | 1060 | 69           | 475 | 756           |
|        | 235/65R16C | 115/113 T | 8PR/LRD | 6.5- <b>7.0</b> -7.5 | 12.2        | 9.7  | 28.0             | 712 | 9.4           | 240 | 2679             | 1215 | 2535             | 1150 | 69           | 475 | 741           |
| 70     | 195/70R15C | 104/102 S | 8PR/LRD | 5.0-5.5- <b>6.0</b>  | 11.6        | 9.2  | 25.8             | 655 | 7.9           | 201 | 1984             | 900  | 1874             | 850  | 65           | 450 | 805           |
|        | 205/70R15C | 106/104 S | 8PR/LRD | 5.5- <b>6.0</b> -6.5 | 11.6        | 9.2  | 26.3             | 669 | 8.2           | 209 | 2094             | 950  | 1984             | 900  | 65           | 450 | 789           |
|        | 215/70R15C | 109/107 S | 8PR/LRD | 5.5- <b>6.5</b> -7.0 | 11.6        | 9.2  | 26.9             | 683 | 8.7           | 221 | 2271             | 1030 | 2149             | 975  | 69           | 475 | 772           |
|        | 225/70R15C | 112/110 S | 8PR/LRD | 6.0- <b>6.5</b> -7.0 | 12.9        | 10.2 | 27.4             | 697 | 9.0           | 228 | 2469             | 1120 | 2337             | 1060 | 69           | 475 | 757           |
| 75     | 185/75R16C | 104/102 S | 8PR/LRD | <b>5.0</b> -5.5-6.0  | 11.6        | 9.2  | 26.9             | 684 | 7.2           | 184 | 1984             | 900  | 1874             | 850  | 69           | 475 | 771           |
|        | 215/75R16C | 113/111 S | 8PR/LRD | 5.5- <b>6.0</b> -7.0 | 12.9        | 10.2 | 28.7             | 728 | 8.5           | 216 | 2535             | 1150 | 2403             | 1090 | 69           | 475 | 725           |
| 80     | 185R14C    | 102/100 R | 8PR/LRD | 5.5- <b>5.5</b> -6.5 | 11.6        | 9.2  | 25.6             | 650 | 7.4           | 188 | 1875             | 850  | 1765             | 800  | 65           | 450 | 812           |
|        | 195R14C    | 106/104 R | 8PR/LRD | 5.5- <b>5.5</b> -6.5 | 11.6        | 9.2  | 26.2             | 666 | 7.8           | 198 | 2095             | 950  | 1985             | 900  | 65           | 450 | 792           |
|        | 195R15C    | 106/104 S | 8PR/LRD | 5.5- <b>5.5</b> -6.5 | 11.6        | 9.2  | 27.0             | 685 | 7.9           | 200 | 2095             | 950  | 1985             | 900  | 65           | 450 | 770           |

Bold designates measuring rim width. These data can be changed by manufacturer without prior notice.