

DELINTE

Series	Size	LI SI	PR	Approved Rim	Tread Depth		Overall Diameter		Section Width		Max.Load		Max.Load		Max.Pressure		Revs Per Mile
					1/32"	MM	inch	mm	inch	mm	lbs ^S	kg	lbs ^D	kg	psi	kpa	
60	LT265/60R20	121/118S	10PR/LRE	7.5- 8.0 -9.5	16.1	12.8	32.5	826	10.7	272	3195	1450	2910	1320	80	550	639
	LT285/60R20	125/122S	10PR/LRE	8.0- 8.5 -10.0	17.3	13.7	33.5	850	11.5	292	3640	1650	3305	1500	80	550	621
65	275/65R17	115V	-	7.5- 8.0 -9.5	16.1	12.8	31.1	790	11	279	2679	1215	-	-	44	300	668
	285/65R17	116H	-	8.0- 8.5 -10.0	17.3	13.7	31.6	802	11.5	292	2756	1250	-	-	44	300	658
	LT275/65R18	123/120S	10PR/LRE	7.5- 8.0 -9.0	16.1	12.8	32.1	815	11	279	3415	1550	3085	1400	80	550	647
	LT275/65R20	126/123S	10PR/LRE	7.5- 8.0 -9.5	16.1	12.8	34.1	866	11	279	3750	1700	3415	1550	80	550	609
70	LT235/70R16	104/101S	6PR/LRC	6.0- 7.0 -7.5	14.1	11.2	29	736	9.5	240	1985	900	1820	825	50	350	717
	245/70R16	107H	-	6.5- 7.0 -8.0	16.1	12.8	29.5	750	9.8	248	2149	975	-	-	44	300	703
	LT265/70R16	121/118 S	10PR/LRE	7.0- 8.0 -8.5	16.1	12.8	30.6	778	10.7	272	3195	1450	2910	1320	80	550	678
	LT245/70R17	119/116S	10PR/LRE	6.5- 7.0 -8.0	16.1	12.8	30.6	776	9.8	248	3000	1360	2755	1250	80	550	680
	LT265/70R17	121/118S	10PR/LRE	7.0- 8.0 -8.5	16.1	12.8	31.7	804	10.7	272	3195	1450	2910	1320	80	550	656
	LT285/70R17	121/118Q	10PR/LRE	7.5- 8.5 -9.0	17.3	13.7	32.8	832	11.5	292	3195	1450	2910	1320	80	550	634
	LT265/70R18	124/121S	10PR/LRE	7.0- 8.0 -9.0	16.1	12.8	32.6	829	10.7	272	3525	1600	3195	1450	80	550	636
	LT275/70R18	125/122S	10PR/LRE	7.0- 8.0 -8.5	16.1	12.8	33.2	843	11	279	3640	1650	3305	1500	80	550	626
75	215/75R15	100T	-	5.5- 6.0 -7.0	14.1	11.2	27.7	703	8.5	216	1764	800	-	-	44	300	750
	LT235/75R15	104/101S	6PR/LRC	6.0- 6.5 -7.0	14.1	11.2	28.9	733	9.3	235	1985	900	1820	825	50	350	720
	LT235/75R15	110/107S	8PR/LRD	6.0- 6.5 -7.0	14.1	11.2	28.9	733	9.3	235	2335	1060	2150	975	65	450	720
	LT225/75R16	115/112 S	10PR/LRE	6.0 -7.0	14.1	11.2	29.3	744	8.8	223	2680	1215	2470	1120	80	550	709
	LT245/75R16	120/116S	10PR/LRE	6.5- 7.0 -8.0	16.1	12.8	30.5	774	9.8	248	3042	1380	2778	1260	80	550	682
	LT265/75R16	123/120S	10PR/LRE	7.0- 7.5 -8.0	16.1	12.8	31.7	804	10.5	267	3415	1550	3085	1400	80	550	656
	LT285/75R16	126/123S	10PR/LRE	7.5- 8.0 -9.0	17.3	13.7	32.8	834	11.3	286	3750	1700	3415	1550	80	550	633
		LT245/75R17	121/118S	10PR/LRE	6.5- 7.0 -7.5	16.1	12.8	31.5	800	9.8	248	3195	1450	2910	1320	80	550
80	LT235/80R17	120/117S	10PR/LRE	6.0- 6.5 -7.5	14.1	11.2	31.8	808	9.3	235	3085	1400	2835	1285	80	550	653
85	LT215/85R16	115/112S	10PR/LRE	5.5- 6.0 -7.0	14.1	11.2	30.4	772	8.5	216	2680	1215	2470	1120	80	550	683
	LT235/85R16	120/116Q	10PR/LRE	6.0- 6.5 -7.5	14.1	11.2	31.8	806	9.3	235	3042	1380	2778	1260	80	550	655
-	31x10.5R15LT	109S	6PR/LRC	7.0- 8.5 -9.0	16.1	12.8	30.5	775	10.5	268	2270	1030	-	-	50	350	681

Bold designates measuring rim width. These data can be changed by manufacturer without prior notice.