

DELINTE⁺

WE INVENT. YOU DRIVE.



PRODUCT CATALOG

OFF-ROAD OFFERINGS / STAGGERED FITMENTS / PERFORMANCE

POWERLINES / ALL-SEASON ASSURANCE

EXPERIENCE THE DELINTE COLLECTIVE



DELINTE FITMENTS

BANDIT M/T DX9 4
BANDIT R/T DX12 8
BANDIT A/T DX10 12

BANDIT X/T DX20 16
BANDIT H/T DX11 20
DYNAMX SPORT 2 DS2 24

SPORT TOURING 1 DST1 28
SPORT TOURING 2 DST2 32
DS8 36

DH2 40
WARRANTIES 44



BANDIT^{DX9} M.T



The Bandit M/T DX9 is a true Mud-Terrain tire with extended tread wear. Light truck drivers depend on their tires to get the job done. Our aggressive tread design features block edge steps, open shoulders, and stone ejectors, for excellent off-road traction while maintaining great on-road performance in both wet and dry conditions. With easy balancing and sizes that range from 15-24 inch wheel diameters, you can depend on the Bandit M/T.

3-PLY PUNCTURE GUARD Three tough layers of polyester cord fabric and high-strength steel belts that effectively guard against rock and debris punctures and provide additional off-road traction, especially for rock climbing and off-camber situations

F-RATED SIZE OPTIONS* 12-Ply construction, engineered for serious hauling capacity for specific sizes

EXTREME OUTSIDE BLOCKS The Bandit Mud-Terrain outside blocks are designed for extended wear with an aggressive look

OPTIMIZED TREAD TRACTION Designed with an optimized void ratio to allow for a high surface area, improving mud traction and promoting long, even tread wear, while effectively cleaning out rocks in off-road conditions

THREE-STEP TREAD BLOCK Serrated shoulder block design to enhance snow and off-road traction

STABILITY ENGINEERING The advanced engineering of the shoulder and sidewall design details give the M_T uniformity and control stability

M+S RATED The M+S rating on the tire sidewall indicates engineering for better traction in the mud and snow

*Specific sizes only



**LIGHT TRUCK
TECH BOX**
TERRAIN
MUD
WHEEL DIAMETER
**15", 16", 17", 18",
20", 22", 24"**
AVAILABLE SIZES
20
ADDITIONAL FEATURES
F-Rated



**OHV+
TRAIL
READY**



**M+S
RATED**



BANDIT M.T

DX9



WHEEL DIAMETER	ARTICLE	SIZE	LOAD INDEX/ SPEED RATING	PLY RATING/ LOAD RANGE	RIM WIDTH RANGE	TREAD DEPTH	OUTSIDE DIAMETER	SECTION WIDTH	MAX LOAD	MAX LOAD (DUAL)	MAX PRESSURE	RPM	UTQG	WEIGHT
					inches	32nds	inches	inches	lbs.	lbs.	psi			lbs.
15	009418	33x12.50R15LT	108Q	6PR/LRC	8.5-10.0-11.0	19	32.8	12.5	2205	/	35	634	/	59.0
	009425	35x12.50R15LT	113Q	6PR/LRC	8.5-10.0-11.0	19	34.8	12.5	2535	/	35	597	/	64.0
16	821188	LT245/75R16	108/104Q	6PR/LRC	6.5-7.0-8.0	17	30.5	9.8	2205	2006	50	682	/	44.0
	821195	LT285/75R16	116/113Q	6PR/LRC	7.5-8.0-9.0	18	32.8	11.3	2755	2535	50	633	/	57.0
	823304	LT285/75R16	126/123S	10PR/LRE	7.5-8.0-9.0	18	32.8	11.3	3750	3415	80	633	/	57.0
	823328	LT305/70R16	124/121S	10PR/LRE	8.0-9.0-9.5	18	32.8	12.2	3525	3195	65	633	/	60.0
17	009432	35x12.50R17LT	121Q	10PR/LRE	8.5-10.0-11.0	19	34.8	12.5	3195	/	65	597	/	66.0
	823311	LT285/70R17	121/118Q	10PR/LRE	7.5-8.5-9.0	18	32.8	11.5	3195	2910	80	634	/	57.0
18	009449	33x12.50R18LT	118Q	10PR/LRE	8.5-10.0-11.0	19	32.8	12.5	2910	/	65	634	/	62.0
	009456	35x12.50R18LT	123Q	10PR/LRE	8.5-10.0-11.0	19	34.8	12.5	3415	/	65	597	/	68.0
	009463	LT285/65R18	125/122Q	10PR/LRE	8.0-8.5-10.0	19	32.8	11.5	3640	3305	80	633	/	58.0
20	009470	33x12.50R20LT	114Q	10PR/LRE	8.5-10.0-11.0	18	32.8	12.5	2600	/	65	634	/	61.0
	009487	35x12.50R20LT	121Q	10PR/LRE	8.5-10.0-11.0	19	34.8	12.5	3195	/	65	597	/	65.0
	823335	LT275/60R20	123/120S	10PR/LRE	7.5-8.0-9.5	18	33.0	11.0	3415	3085	80	630	/	58.0
	823359	37x13.50R20LT	129R	12PR/LRF	8.5-11.0	18	36.5	13.6	4080	/	80	568	/	74.0
22	823342	LT325/50R22	122S	10PR/LRE	9.0-10.0-12.0	18	34.8	13.2	3305	/	65	596	/	71.0
	823366	33x12.50R22LT	123R	12PR/LRF	8.5-10.0-11.0	18	32.5	12.5	3415	/	80	639	/	63.0
	823373	37x13.50R22LT	129Q	12PR/LRF	8.5-11.0	18	36.5	13.6	4080	/	80	568	/	78.0
24	823380	35x13.50R24LT	126Q	12PR/LRF	8.5-11.0	18	34.8	13.6	3750	/	80	597	/	73.0
	823397	37x13.50R24LT	129Q	12PR/LRF	8.5-11.0	18	36.5	13.6	4080	/	80	568	/	77.0

This data can be changed by manufacturer without prior notice.

The Bandit R/T DX12 is a Rough-Terrain tire that gives your overlander or luxury prerunner real on-road comfort. The DX12 technology optimizes the life of the tire, allowing you to drive it daily as well as on off-road adventures. The cutting-edge performance is complemented by its versatile dual-designed sidewall, giving you stylistic control and versatility.

BANDIT^{DX12} R.T



F-RATED SIZE OPTIONS* For serious hauling with hybrid comfort, this tire comes with additional hauling capability in specific sizes

3-PLY PUNCTURE GUARD Three tough layers of polyester cord fabric and angled high-strength steel belts that hold up against rocks and sharp debris

HYBRID TREAD DESIGN Engineered to give you both comfort on the highways and traction in dirt, mud, sand, or snow

DUAL SIDEWALL DESIGN Giving you the option to select the look you want with two unique sidewall designs

RUGGED TREAD PATTERN Containing rugged hammer and chisel blocks that work the terrain to provide outstanding off-road traction

STONE EJECTORS Help remove dirt and mud to improve traction and eject stones, preventing block damage

EXCELLENT WET HANDLING PERFORMANCE Deep cut-through grooves and large multi-shape blocks ensure maximum contact on the ground for enhanced performance both on and off the road

AGGRESSIVE SHOULDER BLOCKS Large shoulder blocks provide greater stability in all driving conditions and enhance damage resistance

M+S RATED The M+S rating on the tire sidewall indicates engineering for better traction in the mud and snow

*Specific sizes only



**LIGHT TRUCK
TECH BOX**
TERRAIN
ROUGH
WHEEL DIAMETER
**16", 17", 18", 20",
22", 24"**
AVAILABLE SIZES
19
ADDITIONAL FEATURES
F-Rated



**OHV+
TRAIL
READY**



**M+S
RATED**



BANDIT R-T

DX12



WHEEL DIAMETER	ARTICLE	SIZE	LOAD INDEX/ SPEED RATING	PLY RATING/ LOAD RANGE	RIM WIDTH RANGE	TREAD DEPTH	OUTSIDE DIAMETER	SECTION WIDTH	MAX LOAD	MAX LOAD (DUAL)	MAX PRESSURE	RPM	UTQG	WEIGHT
						inches								
16	823793	LT285/75R16	126/123S	10PR/LRE	7.5-8.0-9.0	15	32.8	11.3	3750	3415	80	633	/	53.0
	823816	LT315/70R17	121/118S	10PR/LRE	8.0-9.5-11.0	15	34.4	12.7	3195	2910	65	604	/	62.0
17	823847	LT305/65R17	121/118S	10PR/LRE	8.5-9.0-11.0	15	32.6	12.2	3195	2910	65	637	/	56.0
	823809	LT305/70R18	126/123S	10PR/LRE	8.5-9.0-10.0	15	34.8	12.2	3750	3415	65	596	/	61.0
18	823823	LT285/65R18	125/122S	10PR/LRE	8.0-8.5-10.0	15	32.6	11.5	3640	3305	80	638	/	54.0
	823830	LT325/65R18	127/124S	10PR/LRE	9.0-9.5-12.0	15	34.6	13.0	3860	3525	65	600	/	64.0
	823861	LT305/60R18	121/118S	10PR/LRE	8.5-9.0-11.0	15	32.4	12.2	3195	2910	65	641	/	58.0
20	823854	LT325/60R20	126/123S	10PR/LRE	9.0-9.5-12.0	15	35.4	13.0	3750	3415	65	587	/	67.0
	823878	LT275/60R20	123/120S	10PR/LRE	7.5-8.0-9.5	15	33.0	11.0	3415	3085	80	630	/	53.0
	823885	LT285/55R20	122/119S	10PR/LRE	8.0-9.0-10.0	15	32.4	11.7	3305	3000	80	642	/	58.0
	823892	LT305/55R20	121/118S	10PR/LRE	8.5-9.5-11.0	15	33.2	12.4	3195	2910	65	625	/	62.0
	823915	37x12.50R20LT	127R	12PR/LRF	8.5-10.0-11.0	15	36.5	12.5	3860	/	80	568	/	69.0
	823922	33x12.50R20LT	123R	12PR/LRF	8.5-10.0-11.0	15	32.5	12.5	3415	/	80	639	/	61.0
22	823939	35x12.50R20LT	126R	12PR/LRF	8.5-10.0-11.0	15	34.5	12.5	3750	/	80	602	/	61.0
	823946	33x12.50R22LT	123R	12PR/LRF	8.5-10.0-11.0	15	32.5	12.5	3415	/	80	639	/	60.0
	823953	35x12.50R22LT	126R	12PR/LRF	8.5-10.0-11.0	15	34.5	12.5	3750	/	80	602	/	67.0
	823960	37x13.50R22LT	129Q	12PR/LRF	8.5-11.0	15	36.5	13.6	4080	/	80	568	/	72.0
24	823908	LT325/45R24	127/124S	12PR/LRF	9.0-11.0-12.0	15	35.5	12.8	3860	3525	80	585	/	67.0
	823977	37x13.50R24LT	129Q	12PR/LRF	8.5-11.0	15	36.5	13.6	4080	/	80	568	/	73.0

This data can be changed by manufacturer without prior notice.

The Bandit A/T DX10 sets the standard for All-Terrain tires with its extended tread wear. This aggressive tread pattern will give your truck or utility vehicle a more rugged look. The A/T is 3-Peak Mountain Snowflake Rated for confidence on the road or in the snow.

BANDIT^{DX10} A.T



D-SHIELD 50K WARRANTY Protecting your tires for up to 50K of mileage, which also includes the Delinte Road Hazard Warranty Plan

BENCH-SHAPED SHOULDER RIBS Engineered to give more stability during high-speed turns, in dry or wet conditions

FIVE-BLOCK TREAD PATTERN Designed to evacuate water and reduce noise on a variety of road terrains

F-RATED SIZE OPTIONS* For serious hauling with hybrid comfort, this tire comes with additional hauling capability in specific sizes

3-PEAK MOUNTAIN SNOWFLAKE (3PMSF) RATED For extra control even in severe snow conditions

HIGH-STABILITY EDGES Specially-designed tread block edges improve stability and optimize performance in all driving conditions

ZIG-ZAG MIDDLE BLOCK Zig-zag pattern design of the middle tread rib reduces noise while sloped edges help repel rocks and improve traction


*Specific sizes only

LIGHT TRUCK TECH BOX

TERRAIN
ALL
WHEEL DIAMETER
**15" 16" 17" 18",
20" 22" 24"**
AVAILABLE SIZES
49
MILEAGE WARRANTY
50K
COVERAGE
ROAD HAZARD
ADDITIONAL FEATURES
**F-Rated
Snow-Rated**



SEVERE SNOW RATED



BANDIT A.T

DX10

WHEEL DIAMETER	ARTICLE	SIZE	LOAD INDEX/ SPEED RATING	PLY RATING/ LOAD RANGE	RIM WIDTH RANGE	TREAD DEPTH	OUTSIDE DIAMETER	SECTION WIDTH	MAX LOAD	MAX LOAD (DUAL)		MAX PRESSURE	RPM	UTQG	WEIGHT
										lbs.	lbs.				
					inches	32nds	inches	inches	lbs.	lbs.	psi				lbs.
15	009524	215/75R15	100T	/	5.5-6.0-7.0	12	27.7	8.5	1765	1610	44	750	500/A/A	28.0	
	009531	LT235/75R15	104/101S	6PR/LRC	6.0-6.5-7.0	13	28.9	9.3	1985	1820	50	720	/	37.0	
	009746	31x10.50R15LT	109S	6PR/LRC	7.0-8.5-9.0	15	30.5	10.6	2270	/	50	681	/	42.0	
16	009494	LT215/85R16	115/112S	10PR/LRE	5.5-6.0-7.0	13	30.4	8.5	2680	2470	80	683	/	38.0	
	009500	LT235/85R16	120/116Q	10PR/LRE	6.0-6.5-7.5	13	31.7	9.3	3042	2778	80	655	/	43.0	
	009548	LT235/75R15	110/107S	8PR/LRD	6.0-6.5-7.0	13	28.9	9.3	2335	2150	65	720	/	37.0	
	009555	LT225/75R16	115/112S	10PR/LRE	6.0-7.0	13	29.3	8.8	2680	2470	80	709	/	37.0	
	009562	LT245/75R16	120/116S	10PR/LRE	6.5-7.0-8.0	15	30.5	9.8	3042	2778	80	682	/	42.0	
	009579	LT265/75R16	123/120S	10PR/LRE	7.0-7.5-8.0	15	31.7	10.5	3415	3085	80	656	/	47.0	
	009586	LT285/75R16	126/123S	10PR/LRE	7.5-8.0-9.0	16	32.8	11.3	3750	3415	80	633	/	55.0	
	009609	LT235/70R16	104/101S	6PR/LRC	6.0-7.0-7.5	13	29.0	9.4	1985	1820	50	717	/	38.0	
	009616	245/70R16	107H	/	6.5-7.0-8.0	12	29.5	9.8	2149	/	44	703	500/A/A	35.0	
	009623	LT265/70R16	121/118S	10PR/LRE	7.0-8.0-8.5	15	30.6	10.7	3195	2910	80	678	/	46.0	
	823410	LT315/75R16	127/124S	10PR/LRE	8.0-8.5-11.0	15	34.6	12.3	3860	3525	65	601	/	60.0	
	823489	LT305/70R16	124/121S	10PR/LRE	8.0-9.0-9.5	15	32.8	12.2	3525	3195	65	633	/	55.0	
823496	245/70R16	111S	/	6.5-7.0-8.0	12	29.5	9.8	2403	/	49	703	500/A/A	37.0		
17	009517	LT235/80R17	120/117S	10PR/LRE	6.0-6.5-7.5	13	31.8	9.3	3085	2835	80	653	/	42.0	
	009593	LT245/75R17	121/118S	10PR/LRE	6.5-7.0-7.5	15	31.5	9.8	3195	2910	80	659	/	44.0	
	009630	LT245/70R17	119/116S	10PR/LRE	6.5-7.0-8.0	15	30.6	9.8	3000	2755	80	680	/	42.0	
	009647	LT265/70R17	121/118S	10PR/LRE	7.0-8.0-8.5	15	31.7	10.7	3195	2910	80	656	/	47.0	
	009654	LT285/70R17	121/118Q	10PR/LRE	7.5-8.5-9.0	16	32.8	11.5	3195	2910	80	634	/	56.0	
	009685	275/65R17	115V	/	7.5-8.0-9.5	15	31.1	11.0	2679	/	44	668	500/A/A	43.0	
	823472	LT315/70R17	121/118S	10PR/LRE	8.0-9.5-11.0	15	34.4	12.7	3195	2910	65	604	/	63.0	
	823588	LT305/65R17	121/118S	10PR/LRE	8.5-9.0-11.0	15	32.6	12.2	3195	2910	65	637	/	61.0	
18	009661	LT265/70R18	124/121S	10PR/LRE	7.0-8.0-9.0	15	32.6	10.7	3525	3195	80	636	/	50.0	
	009678	LT275/70R18	125/122S	10PR/LRE	7.0-8.0-8.5	15	33.2	11.0	3640	3305	80	626	/	51.0	
	009708	LT275/65R18	123/120S	10PR/LRE	7.5-8.0-9.0	15	32.1	11.0	3415	3085	80	647	/	50.0	
	010728	LT285/65R18	125/122T	10PR/LRE	8.0-8.5-10.0	16	32.6	11.5	3640	3305	80	638	/	53.0	
	823465	LT305/70R18	126/123S	10PR/LRE	8.5-9.0-10.0	15	34.8	12.2	3750	3415	65	596	/	59.0	
	823564	LT285/65R18	125/122R	10PR/LRE	8.0-8.5-10.0	16	32.6	11.5	3640	3305	80	638	/	54.0	
	823571	LT325/65R18	127/124S	10PR/LRE	9.0-9.5-12.0	15	34.6	13.0	3860	3525	65	600	/	59.0	
823656	LT305/60R18	121/118S	10PR/LRE	8.5-9.0-11.0	15	32.4	12.2	3195	2910	65	641	/	54.0		
20	009715	LT275/65R20	126/123S	10PR/LRE	7.5-8.0-9.5	15	34.1	11.0	3750	3415	80	609	/	55.0	
	009722	LT265/60R20	121/118S	10PR/LRE	7.5-8.0-9.5	15	32.5	10.7	3195	2910	80	639	/	49.0	
	009739	LT285/60R20	125/122S	10PR/LRE	8.0-8.5-10.0	16	33.5	11.5	3640	3305	80	621	/	55.0	
	823632	LT275/60R20	123/120S	10PR/LRE	7.5-8.0-9.5	15	33.0	11.0	3415	3085	80	630	/	57.0	
	823649	275/60R20	118H	/	7.5-8.0-9.5	12	33.0	11.0	2910	/	49	630	500/A/A	46.0	
	823663	LT325/60R20	126/123S	10PR/LRE	9.0-9.5-12.0	15	35.4	13.0	3750	3415	65	587	/	66.0	
	823687	LT285/55R20	122/119S	10PR/LRE	8.0-9.0-10.0	15	32.4	11.7	3305	3000	80	642	/	54.0	
	823694	LT305/55R20	121/118S	10PR/LRE	8.5-9.5-11.0	15	33.2	12.4	3195	2910	65	625	/	58.0	
	823700	275/55R20	118H	/	7.5-8.5-9.5	12	31.9	11.2	2910	/	49	651	500/A/A	44.0	
	823717	LT275/55R20	120/117S	10PR/LRE	7.5-8.5-9.5	15	31.9	11.2	3085	2835	80	651	/	51.0	
	823724	LT265/50R20	121/118S	10PR/LRE	7.5-8.5-9.5	15	30.5	10.9	3195	2910	80	682	/	49.0	
823755	35x12.50R20LT	126R	12PR/LRF	8.5-10.0-11.0	15	34.5	12.5	3750	/	80	602	/	64.0		
823786	37x12.50R20LT	127R	12PR/LRF	8.5-10.0-11.0	15	36.5	12.5	3860	/	80	568	/	67.0		
22	823731	285/45R22	116H	/	9.0-9.5-10.5	12	32.1	11.2	2756	/	49	647	500/A/A	44.0	
	823762	33x12.50R22LT	123S	12PR/LRF	8.5-10.0-11.0	15	32.5	12.5	3415	/	80	639	/	60.0	
	823779	35x12.50R22LT	126R	12PR/LRF	8.5-10.0-11.0	15	34.5	12.5	3750	/	80	602	/	64.0	
24	823748	285/40R24	118H	/	9.5-10.0-11.0	12	33.0	11.4	2910	/	49	630	500/A/A	46.0	

This data can be changed by manufacturer without prior notice.



The Bandit X/T DX20 is a hybrid Crossover-Terrain tire created for popular overlanding CUV/SUV and light truck vehicles in 79 sizes. It debuts with a strong tread pattern and the option to choose the look you want with a dual sidewall design. This Crossover-Terrain CUV/SUV/LT tire offers more extreme X/T features with the reliability and durability you need for OHV or overlanding.

BANDIT DX20 X.T



MADE SPECIFICALLY FOR OE REPLACEMENT

FITMENTS: Subaru® Outback, Toyota® RAV4, Subaru® Crosstrek, Honda® CR-V, Jeep® Renegade Trailhawk, Mazda® CX-5, Nissan® Rogue, Ford® Escape & Jeep Cherokee.

This tire is comparable to the Nitto® Nomad Grappler, Falken® Wildpeak A/T Trail or the Toyo® Open Country A/T III.

AGGRESSIVE TREAD DESIGN Block edge steps, open shoulders, and stone ejectors deliver excellent off-road traction while maintaining both wet and dry on-road performance

ALL-WEATHER ENGINEERING Continuous shoulder zig-zag grooves and center x-shaped grooves improve evacuation of rain, mud, and snow, and overall handling in all weather conditions

THREE-STEP TREAD BLOCK Works together with a serrated shoulder block design to enhance snow and off-road traction

STONE EJECTORS Help remove mud to improve traction and eject stones to prevent block damage

DUAL SIDEWALL DESIGN Shoulder block design extends from tread shoulder block to sidewall, protecting against sharp rocks and providing additional off-road and off-camber traction

D-TECH SILICA COMPOUND Reinforcing tread compound enhances tire performance and traction in low temperatures and snow

STEEL CORD BELT Ultra-high strength steel cord tread belt improves puncture resistance, steering response, and tread wear

F-RATED SIZE OPTIONS* For serious hauling with hybrid comfort, this tire comes with additional hauling capability in specific sizes

M+S RATED The M+S rating on the tire sidewall indicates engineering for better traction in the mud and snow

* Specific sizes only



CUV/SUV/LIGHT TRUCK TECH BOX
 WHEEL DIAMETER
15", 16", 17", 18", 19", 20", 22", 24"
 AVAILABLE SIZES
79
 MILEAGE WARRANTY
55K
 COVERAGE
ROAD HAZARD



BANDIT X-T

DX20

WHEEL DIAMETER	ARTICLE	SIZE	LOAD INDEX/ SPEED RATING	PLY RATING/ LOAD RANGE	RIM WIDTH RANGE	TREAD DEPTH	OUTSIDE DIAMETER	SECTION WIDTH	MAX LOAD	MAX LOAD (DUAL)		MAX PRESSURE	RPM	UTQG	WEIGHT
										lbs.	lbs.				
15	834157	31x10.50R15LT	109Q	6PR/LRC	7.0-8.5-9.0	17	30.5	10.6	2270	/	50	681	/	42.8	
	834164	P235/75R15	105T	/	6.0-6.5-8.0	12	28.9	9.3	2039	/	44	720	660AA	35.5	
16	833907	215/65R16	98H	/	6.0-6.5-7.5	12	27.0	8.7	1653	/	44	769	660AA	30.2	
	833914	LT285/75R16	126/123Q	10PR/LRE	7.5-8.0-9.5	18	32.8	11.3	3750	3415	80	633	/	60.4	
	833921	LT305/70R16	124/121S	10PR/LRE	8.0-9.0-10.0	18	32.8	12.2	3525	3195	65	633	/	59.5	
	833938	LT315/75R16	127/124S	10PR/LRE	8.0-8.5-10.5	18	34.6	12.3	3860	3525	65	601	/	67.7	
	834171	205/70R16	97H	/	5.0-6.0-7.0	12	27.3	8.2	1609	/	44	760	660AA	31.5	
	834188	215/70R16	100H	/	5.5-6.5-7.0	12	27.9	8.7	1764	/	44	745	660AA	31.7	
	834195	LT295/75R16	123/120Q	8PR/LRD	7.5-8.0-10.0	17	33.4	11.6	3415	3085	65	622	/	58.2	
17	833594	215/65R17	99H	/	6.0-6.5-7.5	12	28.0	8.7	1709	/	44	741	660AA	31.1	
	833600	225/55R17	101V	/	6.0-7.0-8.0	12	26.8	9.2	1819	/	50	776	660AA	29.8	
	833617	225/60R17	99H	/	6.0-6.5-8.0	12	27.6	9.0	1709	/	44	751	660AA	32.0	
	833624	225/65R17	102H	/	6.0-6.5-8.0	12	28.5	9.0	1874	/	44	729	660AA	33.3	
	833631	235/65R17	108H	/	6.5-7.0-8.5	12	29.1	9.4	2205	/	50	715	660AA	34.6	
	833648	245/65R17	107H	/	7.0-7.0-8.5	12	29.5	9.8	2149	/	44	703	660AA	37.5	
	833655	LT285/70R17	121/118Q	10PR/LRE	7.5-8.5-9.5	18	32.8	11.5	3195	2910	80	634	/	56.4	
	833662	LT315/70R17	121/118S	10PR/LRE	8.0-9.5-10.5	18	34.4	12.7	3195	2910	65	604	/	68.6	
	833945	215/60R17	100H	/	6.0-6.5-7.5	12	27.2	8.7	1764	/	50	765	660AA	31.1	
	833952	235/55R17	103W	/	6.5-7.5-8.5	12	27.2	9.6	1929	/	50	765	660AA	33.1	
	833969	235/60R17	102H	/	6.5-7.0-8.5	12	28.1	9.4	1874	/	44	739	660AA	36.2	
	833976	35x12.50R17LT	121Q	10PR/LRE	8.0-10.0-10.5	19	34.5	12.5	3195	/	65	602	/	69.7	
	833983	37x12.50R17LT	124Q	8PR/LRD	8.0-10.0-10.5	18	36.5	12.5	3525	/	50	568	/	73.0	
	833990	LT265/70R17	121/118Q	10PR/LRE	7.0-8.0-9.0	18	31.7	10.7	3195	2910	80	656	/	51.8	
	834003	LT285/75R17	121/118Q	10PR/LRE	7.5-8.0-9.5	17	33.9	11.3	3195	2910	80	613	/	61.5	
834010	LT295/70R17	121/118Q	10PR/LRE	7.5-8.5-10.0	18	33.3	11.8	3195	2910	80	624	/	59.7		
834201	LT305/65R17	121/118S	10PR/LRE	9.0-11.0	17	32.6	12.2	3195	2910	65	637	/	61.1		

WHEEL DIAMETER	ARTICLE	SIZE	LOAD INDEX/ SPEED RATING	PLY RATING/ LOAD RANGE	RIM WIDTH RANGE	TREAD DEPTH	OUTSIDE DIAMETER	SECTION WIDTH	MAX LOAD	MAX LOAD (DUAL)		MAX PRESSURE	RPM	UTQG	WEIGHT
										lbs.	lbs.				
18	833679	225/55R18	102W	/	6.0-7.0-8.0	12	27.8	9.2	1874	/	50	748	660AA	32.2	
	833686	225/60R18	104V	/	6.0-6.5-8.0	12	28.6	9.0	1984	/	50	726	660AA	33.5	
	833693	235/60R18	107V	/	6.5-7.0-8.5	12	29.1	9.4	2149	/	50	714	660AA	36.8	
	833709	235/65R18	110H	/	6.5-7.0-8.5	12	30.0	9.4	2337	/	50	691	660AA	36.4	
	833716	245/60R18	105V	/	7.0-8.5	12	29.6	9.8	2039	/	44	702	660AA	38.6	
	833723	33x12.50R18LT	118Q	10PR/LRE	8.5-10.0-11.0	18	32.5	12.5	2910	/	65	639	/	62.6	
	833747	35x12.50R18LT	123Q	10PR/LRE	8.5-10.0-11.0	19	34.5	12.5	3415	/	65	602	/	69.2	
	833761	LT285/65R18	125/122Q	10PR/LRE	8.5-10.0	18	32.6	11.5	3640	3305	80	638	/	62.2	
	834027	215/55R18	99V	/	6.0-7.0-7.5	12	27.3	8.9	1709	/	50	761	660AA	31.5	
	834034	235/50R18	101W	/	6.5-7.5-8.5	12	27.3	9.6	1819	/	50	761	660AA	32.2	
	834041	235/55R18	104V	/	6.5-7.5-8.5	12	28.1	9.6	1984	/	50	738	660AA	34.6	
	834058	255/55R18	109W	/	7.0-8.0-9.0	12	29.0	10.4	2271	/	50	716	660AA	38.6	
	834065	255/65R18	111H	/	7.0-7.5-9.0	12	31.1	10.2	2403	/	44	669	660AA	42.1	
	834072	265/65R18	114H	/	7.5-8.0-9.5	12	31.5	10.7	2601	/	44	659	660AA	45.2	
	834089	275/65R18	116H	/	7.5-8.0-9.5	12	32.1	11.0	2756	/	44	647	660AA	46.3	
	834218	37x13.50R18LT	128Q	10PR/LRE	9.0-11.0-11.5	19	36.5	13.6	3970	/	65	568	/	76.5	
	834225	LT275/70R18	125/122S	10PR/LRE	7.0-8.0-9.0	17	33.2	11.0	3640	3305	80	626	/	56.9	
	834232	LT285/75R18	129/126Q	10PR/LRE	7.5-8.0-9.5	17	34.8	11.3	4080	3750	80	596	/	63.9	
834249	LT295/70R18	129/126Q	10PR/LRE	7.5-8.5-10.0	17	34.3	11.8	4080	3750	80	606	/	61.9		
834256	LT305/60R18	121/118S	10PR/LRE	9.0-11.0	17	32.4	12.2	3195	2910	65	641	/	62.6		
834263	LT305/70R18	126/123S	10PR/LRE	8.0-9.0-10.0	17	34.8	12.2	3750	3415	65	596	/	64.8		
834270	LT325/60R18	124/121S	10PR/LRE	9.5-11.5	18	33.3	13.0	3525	3195	65	623	/	67.2		
834287	LT325/65R18	127/124S	10PR/LRE	9.5-11.5	18	34.6	13.0	3860	3525	65	600	/	70.3		
19	834096	235/55R19	105W	/	6.5-7.5-8.5	12	29.2	9.6	2039	/	50	712	660AA	37.7	
	834102	255/55R19	111V	/	7.0-8.0-9.0	12	30.0	10.4	2403	/	50	691	660AA	40.8	
	834294	225/55R19	99H	/	6.0-7.0-8.0	12	28.8	9.2	1709	/	44	722	660AA	33.7	
	834300	245/55R19	103W	/	7.0-7.5-8.5	12	29.6	10.0	1929	/	44	701	660AA	38.4	
	834317	255/60R19	109H	/	7.0-7.5-9.0	12	31.1	10.2	2271	/	44	669	660AA	40.1	
	833778	245/50R20	102W	/	7.0-7.5-8.5	12	29.7	10.0	1874	/	44	700	660AA	37.7	
	833785	275/55R20	113T	/	7.5-8.5-9.5	12	31.9	11.2	2535	/	44	651	660AA	45.4	
20	833792	35x12.50R20LT	121Q	10PR/LRE	8.5-10.0-11.0	19	34.5	12.5	3195	/	65	602	/	71.6	
	833815	37x12.50R20LT	126Q	10PR/LRE	8.5-10.0-11.0	19	36.5	12.5	3750	/	65	568	/	75.2	
	833839	LT305/55R20	121/118S	10PR/LRE	9.0-9.5-11.0	17	33.2	12.4	3195	2910	65	625	/	65.9	
	834119	255/50R20	109W	/	7.0-8.0-9.0	12	30.1	10.4	2271	/	50	690	660AA	40.6	
	834126	265/50R20	107T	/	7.5-8.5-9.5	12	30.5	10.9	2149	/	44	682	660AA	39.3	
	834133	LT285/55R20	122/119Q	10PR/LRE	8.5-9.0-10.0	17	32.4	11.7	3305	3000	80	642	/	63.7	
	834324	255/55R20	110V	/	7.0-8.0-9.0	12	31.0	10.4	2337	/	50	669	660AA	41.9	
22	833846	275/50R22	111H	/	7.5-8.5-9.5	12	32.9	11.2	2403	/	44	632	660AA	48.3	
	833853	33x12.50R22LT	109Q	10PR/LRE	8.5-10.0-11.0	18	32.5	12.5	2270	/	65	639	/	62.8	
	833877	35x12.50R22LT	117Q	10PR/LRE	8.5-10.0-11.0	19	34.5	12.5	2835	/	65	602	/	73.0	
	834140	37x12.50R22LT	127Q	12PR/LRF	8.5-10.0-11.0	19	36.5	12.5	3860	/	80	568	/	75.0	
	834331	285/45R22	114T	/	9.0-9.5-10.5	12	32.1	11.2	2601	/	50	647	660AA	46.7	
	834348	285/50R22	115T	/	8.0-9.0-10.0	12	33.3	11.7	2679	/	44	624	660AA	49.8	
24	834355	LT285/50R22	121/118Q	10PR/LRE	8.0-9.0-10.0	17	33.3	11.7	3195	2910	80	624	/	60.8	
	834362	LT285/55R22	124/121Q	10PR/LRE	8.5-9.0-10.0	17	34.4	11.7	3525	3195	80	604	/	63.7	
	833891	33x12.50R24LT	104Q	10PR/LRE	10.5-11.5-12.5	18	32.5	12.6	1985	/	65	639	/	62.8	
834379	285/40R24	118V	/	9.5-10.0-11.0	12	33.0	11.4	2910	/	50	630	660AA	47.6		

This data can be changed by manufacturer without prior notice.

The Bandit H/T DX11 is a durable Premium Highway-Terrain tire engineered to decrease road noise, and comes in 45 sizes. With the 50K D-Shield Mileage Warranty, this highway tire also comes with Road Hazard Coverage for even more confidence.

BANDIT H.T DX11



D-SHIELD 50K WARRANTY Protecting your tires for up to 50K of mileage, which also includes the Delinte Road Hazard Warranty Plan

MULTI-LEVEL BLOCKS With ultimate tread block rigidity which maximizes traction in a variety of highway conditions and improves overall handling performance

STAGGERED BLOCK DESIGN Improves tread block rigidity, optimizing handling performance and ride quality

NOISE REDUCING SHOULDER Intelligent shoulder design tackles typical road noise head-on while also providing excellent traction in all conditions

HIGH STABILITY CENTER RIB In combination with optimized sipes, the high-stability center rib enhances steering, handling, and braking performance

CENTER TRACTION GROOVES Four wide center grooves effectively evacuate water to enhance wet traction and provide driving confidence

M+S RATED The M+S rating on the tire sidewall indicates engineering for better traction in the mud and snow



**LIGHT TRUCK
TECH BOX**

**TERRAIN
HIGHWAY**

**WHEEL DIAMETER
16", 17", 18", 20",
22"**

**AVAILABLE SIZES
45**

**MILEAGE WARRANTY
50K**

**COVERAGE
ROAD HAZARD**

**M+S
RATED**



BANDIT H.T

DX11



WHEEL DIAMETER	ARTICLE	SIZE	LOAD INDEX/ SPEED RATING	PLY RATING/ LOAD RANGE	RIM WIDTH RANGE	TREAD DEPTH	OUTSIDE DIAMETER	SECTION WIDTH	MAX LOAD	MAX LOAD (DUAL)	MAX PRESSURE	RPM	UTQG	WEIGHT
						32nds	inches	inches	lbs.	lbs.	psi		lbs.	
16	809582	LT235/85R16	120/116S	10PR/LRE	6.0-6.5-7.5	11	31.6	8.9	3042	2778	80	658	/	43.0
	009753	LT215/85R16	115/112S	10PR/LRE	5.5-6.0-7.0	11	30.4	9.0	2680	2470	80	683	/	38.0
	009777	LT225/75R16	115/112S	10PR/LRE	6.0-7.0	11	29.3	8.8	2680	2470	80	709	/	37.0
	009784	LT245/75R16	120/116S	10PR/LRE	6.5-7.0-8.0	12	30.5	9.8	3042	2778	80	682	/	42.0
	009791	LT265/75R16	123/120S	10PR/LRE	7.0-7.5-8.0	12	31.7	10.5	3415	3085	80	656	/	47.0
	823199	215/70R16	100H	/	5.5-6.5-7.0	10	27.9	8.7	1764	/	44	745	500/A/A	28.0
	823984	225/70R16	103H	/	6.0-6.5-7.5	10	28.4	9.0	1929	/	44	731	500/A/A	29.0
	823991	235/70R16	106H	/	6.0-7.0-8.0	10	29.0	9.4	2094	/	44	717	500/A/A	32.0
	824004	245/70R16	107H	/	6.5-7.0-8.0	10	29.5	9.8	2149	/	44	703	500/A/A	34.0
	824011	255/70R16	109H	/	6.5-7.5-8.5	10	30.1	10.2	2271	/	44	690	500/A/A	28.0
	824028	265/70R16	112H	/	7.0-8.0-9.0	10	30.6	10.7	2469	/	44	678	500/A/A	37.0
	824066	235/65R16	107H	/	6.5-7.0-8.5	10	28.0	9.4	2149	/	49	741	500/A/A	37.0
17	009760	LT235/80R17	120/117S	10PR/LRE	6.0-6.5-7.5	11	31.8	9.3	3085	2835	80	653	/	42.0
	009807	LT245/75R17	121/118S	10PR/LRE	6.5-7.0-7.5	12	31.5	9.8	3195	2910	80	659	/	44.0
	009814	LT245/70R17	119/116S	10PR/LRE	6.5-7.0-8.0	12	30.6	9.8	3000	2755	80	680	/	42.0
	009821	LT265/70R17	121/118S	10PR/LRE	7.0-8.0-8.5	12	31.7	10.7	3195	2910	80	656	/	47.0
	823205	245/70R17	110H	/	6.5-7.0-8.0	10	30.6	9.8	2337	/	44	680	500/A/A	36.0
	823212	225/65R17	102H	/	6.0-6.5-8.0	10	28.5	9.0	1874	/	44	729	500/A/A	29.0
	824035	255/70R17	112H	/	6.5-7.5-8.5	10	31.1	10.2	2469	/	44	668	500/A/A	36.0
	824042	265/70R17	115H	/	7.0-8.0-9.0	10	31.7	10.7	2679	/	44	656	500/A/A	39.0
	824073	235/65R17	108H	/	6.5-7.0-8.5	10	29.1	9.4	2205	/	49	715	500/A/A	31.0
	824080	245/65R17	107H	/	7.0-8.5	10	29.5	9.8	2149	/	44	703	500/A/A	33.0
	824097	255/65R17	110H	/	7.0-7.5-9.0	10	30.1	10.2	2337	/	44	690	500/A/A	35.0
	824103	265/65R17	112H	/	7.5-8.0-9.5	10	30.6	10.7	2469	/	44	680	500/A/A	38.0
824127	225/60R17	99H	/	6.0-6.5-8.0	10	27.6	9.0	1709	/	44	751	500/A/A	26.0	
18	817501	265/65R18	116H	/	7.5-8.0-9.5	10	31.5	10.7	2756	/	49	659	500/A/A	39.0
	817525	275/65R18	118H	/	7.5-8.0-9.5	10	32.1	11.0	2910	/	49	647	500/A/A	39.0
	009838	LT265/70R18	124/121S	10PR/LRE	7.0-8.0-9.0	12	32.6	10.7	3525	3195	80	636	/	50.0
	009845	LT275/70R18	125/122S	10PR/LRE	7.0-8.0-8.5	14	33.2	11.0	3640	3305	80	626	/	51.0
	009852	LT275/65R18	123/120S	10PR/LRE	7.5-8.0-9.0	14	32.1	11.0	3415	3085	80	647	/	50.0
	824059	255/70R18	113H	/	6.5-7.5-8.5	10	32.1	10.2	2535	/	44	647	500/A/A	39.0
	824110	235/65R18	110H	/	6.5-7.0-8.5	10	30.0	9.4	2337	/	49	691	500/A/A	34.0
	824134	235/60R18	107V	/	6.5-7.0-8.5	10	29.1	9.4	2149	/	49	714	500/A/A	32.0
	824141	245/60R18	105V	/	7.0-8.5	10	29.6	9.8	2039	/	44	702	500/A/A	33.0
	824158	265/60R18	114H	/	7.5-8.0-9.5	10	30.5	10.7	2601	/	49	681	500/A/A	38.0
	824165	235/55R18	104V	/	6.5-7.5-8.5	10	28.1	9.6	1984	/	49	738	500/A/A	31.0
	824172	255/55R18	109V	/	7.0-8.0-9.0	10	29.0	10.4	2271	/	49	716	500/A/A	32.0
824189	255/55ZR18	109W	/	7.0-8.0-9.0	10	29.0	10.4	2271	/	49	716	500/A/A	32.0	
20	809575	275/55R20	117H	/	7.5-8.5-9.5	10	31.9	11.2	2833	/	49	651	500/A/A	40.0
	809599	275/60R20	115H	/	7.5-8.0-9.5	10	33.0	11.0	2679	/	44	630	500/A/A	40.0
	009869	LT275/65R20	126/123S	10PR/LRE	7.5-8.0-9.5	14	34.1	11.0	3750	3415	80	609	/	55.0
	009876	LT265/60R20	121/118S	10PR/LRE	7.5-8.0-9.5	12	32.5	10.7	3195	2910	80	639	/	49.0
22	009883	LT285/60R20	125/122S	10PR/LRE	8.0-8.5-10.0	14	33.5	11.5	3640	3305	80	621	/	55.0
	817518	285/45R22	116H	/	9.0-9.5-10.5	10	32.1	11.2	2756	/	49	647	500/A/A	41.0
824196	275/45R22	114V	/	8.5-9.0-10.5	10	31.8	10.7	2601	/	49	654	500/A/A	40.0	

This data can be changed by manufacturer without prior notice.

NEW POWERLINE



The **DS2** is the first of its kind Ultra-High Performance Powerline tire, available in multiple wheel diameters with over 100 different sizes, accommodating many different vehicle makes and models. The DS2 features Delinte's proprietary QST Technology which accelerates water evacuation for enhanced performance in wet conditions. The DS2 also comes with a reliable 55K mileage warranty.

STAGGERED FITMENTS The DS2 is a Powerline tire that comes in a vast amount of size offerings and staggered fitments

ULTRA-WIDE TREAD GROOVES Four extra-wide tread grooves accelerate water evacuation using QST Technology, which improves performance in wet conditions

INTELLIGENT TREAD DESIGN Optimized tread engineering with a large contact footprint increases control in all driving conditions, effectively reducing pattern noise and providing a comfortable ride

ANGLED TREAD Innovative tread design with 3D angled voids maximizes braking performance, and adds extra road traction

SYMMETRICAL SHOULDER BLOCKS Wide, symmetrical shoulder blocks give optimum stability during higher speed performance driving

D-SHIELD 55K WARRANTY The Delinte 55K Mileage & Road Hazard Warranty Plan provides driving confidence for the life of the tire

QST TECHNOLOGY Delinte's proprietary Qirin Scale Technology suppresses the formation of water turbulence in the grooves of the tire, allowing faster water evacuation, and improving performance in wet conditions

M+S RATED The M+S rating on the tire sidewall indicates engineering for better traction in the mud and snow

**DYNAMX
SPORT 2^{DS2}**

PASSENGER CAR
TECH BOX
PERFORMANCE
ULTRA-HIGH
WHEEL DIAMETER
14" - 20"
MILEAGE WARRANTY
55K
COVERAGE
ROAD HAZARD



ULTRA-HIGH

WHEEL DIAMETER	ARTICLE	SIZE	LOAD INDEX/ SPEED RATING	RIM WIDTH RANGE	TREAD DEPTH	OUTSIDE DIAMETER	SECTION WIDTH	MAX LOAD	MAX PRESSURE	RPM	UTQG	WEIGHT
				inches	32nds	inches	inches	lbs.	psi			lbs.
14	853578	165/65R14	79H	4.5-5.0-6.0	9	22.4	6.7	963	44	926	500AA	13.9
	853585	175/65R14	82H	5.0-6.0	9	23.0	7	1047	44	903	500AA	14.9
	849595	185/65R14	86H	5.0-5.5-6.5	9	23.5	7.4	1168	44	885	500AA	17.6
15	849601	195/65R15	91H	5.5-6.0-7.0	9	25.0	7.9	1356	44	831	500AA	19.1
	849281	185/65R15	88H	5.0-5.5-6.5	9	24.4	7.4	1235	44	850	500AA	17.7
	849618	205/65R15	94H	5.5-6.0-7.5	9	25.5	8.2	1477	44	815	500AA	20.5
	849625	195/60R15	88H	5.5-6.0-7.0	9	24.2	7.9	1235	44	858	500AA	17.9
	849632	215/70R15	98H	5.5-6.5-7.0	10	26.9	8.7	1653	44	772	500AA	23.9
	849304	185/60R15	84H	5.0-5.5-6.5	9	23.7	7.4	1102	44	875	500AA	16.4
	849649	175/65R15	84H	5.0-6.0	9	24.0	7	1102	44	866	500AA	15.9
	849656	195/50R15	82V	5.5-6.0-7.0	9	22.7	7.9	1047	44	914	500AA	17.5
	849663	195/55R15	85V	5.5-6.0-7.0	9	23.4	7.9	1135	44	887	500AA	17.6
	16	849366	205/55ZR16	94W	5.5-6.5-7.5	9	24.9	8.4	1477	50	835	500AA
849670		215/60R16	99V	6.0-6.5-7.5	9	26.1	8.7	1709	50	794	500AA	21.0
850119		205/60R16	92H	5.5-6.0-7.5	9	25.7	8.2	1389	44	809	500AA	20.0
849687		215/70R16	100H	5.5-6.5-7.0	9	27.9	8.7	1764	44	745	500AA	24.3
849694		225/60R16	98H	6.0-6.5-8.0	9	26.6	9	1653	44	780	500AA	23.8
849700		205/65R16	99H	5.5-6.0-7.5	9	26.5	8.2	1709	50	785	500AA	21.8
849359		215/55ZR16	97W	6.0-7.0-7.5	9	25.3	8.9	1609	50	822	500AA	21.7
849717		215/65R16	102H	6.0-6.5-7.5	9	27.0	8.7	1874	50	769	500AA	23.0
849724		205/70R16	98H	5.0-6.0-7.0	9	27.3	8.2	1653	50	760	500AA	24.0
849731		225/65R16	100H	6.0-6.5-8.0	9	27.5	9	1764	44	756	500AA	25.8
849748		225/55ZR16	99W	6.0-7.0-8.0	9	25.7	9.2	1709	50	807	500AA	23.0
850126		195/55R16	91W	5.5-6.0-7.0	9	24.4	7.9	1356	50	851	500AA	19.0
849755		195/50R16	88V	5.5-6.0-7.0	9	23.7	7.9	1235	50	876	500AA	18.8
17		849342	215/55ZR17	98W	6.0-7.0-7.5	9	26.3	8.9	1653	50	790	500AA
	849427	215/45ZR17	91W	7.0-8.0	9	24.6	8.4	1356	50	843	500AA	20.4
	849328	225/50ZR17	98W	6.0-7.0-8.0	9	25.9	9.2	1653	50	802	500AA	24.4
	849274	225/45ZR17	94W	7.0-7.5-8.5	9	25.0	8.9	1477	50	832	500AA	21.7
	849441	225/55ZR17	101W	6.0-7.0-8.0	9	26.8	9.2	1819	50	776	500AA	26.2
	849380	205/50ZR17	93W	5.5-6.5-7.5	9	25.1	8.4	1433	50	827	500AA	21.5
	849311	215/50ZR17	95W	6.0-7.0-7.5	9	25.5	8.9	1521	50	814	500AA	22.7
	849762	235/45ZR17	97W	7.5-8.0-9.0	9	25.4	9.3	1609	50	819	500AA	22.9
	849779	235/60R17	105H	6.5-7.0-8.5	9	28.1	9.4	2039	50	739	500AA	27.8
	849786	235/55ZR17	103W	6.5-7.5-8.5	9	27.2	9.6	1929	50	765	500AA	27.0
	849403	215/60R17	100H	6.0-6.5-7.5	9	27.2	8.7	1764	50	765	500AA	23.9
	849793	205/40ZR17	84W	7.0-7.5-8.0	9	23.5	8.3	1102	50	885	500AA	17.9
	849809	245/45ZR17	99W	7.5-8.0-9.0	9	25.7	9.6	1709	50	809	500AA	24.7
	849816	245/40ZR17	95W	8.0-8.5-9.5	9	24.7	9.8	1521	50	840	500AA	22.6
849540	205/45ZR17	88W	6.5-7.0-7.5	9	24.3	8.1	1235	50	856	500AA	19.2	
18	849298	225/40ZR18	92W	7.5-8.0-9.0	9	25.1	9.1	1389	50	828	500AA	21.9
	849458	235/45ZR18	98W	7.5-8.0-9.0	9	26.3	9.3	1653	50	789	500AA	24.0
	849397	225/45ZR18	95W	7.0-7.5-8.5	9	25.9	8.9	1521	50	801	500AA	22.8
	849823	235/50ZR18	101W	6.5-7.5-8.5	9	27.3	9.6	1819	50	761	500AA	25.6
	849830	245/45ZR18	100W	7.5-8.0-9.0	9	26.7	9.6	1764	50	779	500AA	25.6
	849847	225/55ZR18	102W	6.0-7.0-8.0	9	27.8	9.2	1874	50	748	500AA	26.5
	849854	235/55ZR18	104W	6.5-7.5-8.5	9	28.1	9.6	1984	50	738	500AA	28.1
	849861	235/40ZR18	95W	8.0-8.5-9.5	9	25.4	9.5	1521	50	818	500AA	23.4
	849878	245/40ZR18	97W	8.0-8.5-9.5	9	25.7	9.8	1609	50	808	500AA	25.0
	849885	225/50ZR18	99W	6.0-7.0-8.0	9	26.9	9.2	1709	50	772	500AA	25.0
	849892	255/35ZR18	94W	8.5-9.0-10.0	9	25.0	10.2	1477	50	831	500AA	24.8
	849908	215/40ZR18	89W	7.0-7.5-8.5	9	24.8	8.6	1279	50	839	500AA	19.8
	849915	225/60R18	100V	6.0-6.5-8.0	9	28.6	9	1764	44	726	500AA	26.7
	849410	215/55R18	99V	6.0-7.0-7.5	9	27.3	8.9	1709	50	761	500AA	23.8
849922	215/35ZR18	84W	7.0-7.5-8.5	9	23.9	8.6	1102	50	869	500AA	19.0	

WHEEL DIAMETER	ARTICLE	SIZE	LOAD INDEX/ SPEED RATING	RIM WIDTH RANGE	TREAD DEPTH	OUTSIDE DIAMETER	SECTION WIDTH	MAX LOAD	MAX PRESSURE	RPM	UTQG	WEIGHT	
				inches	32nds	inches	inches	lbs.	psi			lbs.	
19	849939	235/40ZR19	98Y	8.0-8.5-9.5	9	26.4	9.5	1653	50	786	500AA	24.5	
	849946	245/40ZR19	98W	8.0-8.5-9.5	9	26.7	9.8	1653	50	777	500AA	25.6	
	850133	245/45ZR19	102Y	7.5-8.0-9.0	9	27.7	9.6	1764	50	750	500AA	27.4	
	849953	235/35ZR19	91W	8.0-8.5-9.5	9	25.5	9.5	1356	50	815	500AA	22.9	
	849960	225/45ZR19	96W	7.0-7.5-8.5	9	27.0	8.9	1565	50	770	500AA	24.2	
	849977	245/35ZR19	97W	8.0-8.5-9.5	9	25.8	9.8	1609	50	805	500AA	24.2	
	849984	225/40ZR19	93W	7.5-8.0-9.0	9	26.1	9.1	1433	50	796	500AA	22.1	
	849564	255/35ZR19	96W	8.5-9.0-10.0	9	26.0	10.2	1565	50	798	500AA	26.0	
	849991	275/30ZR19	96W	9.0-9.5-10.0	9	25.6	10.9	1565	50	813	500AA	25.9	
	850003	265/30ZR19	93W	9.0-9.5-10.0	9	25.3	10.7	1433	50	820	500AA	23.7	
	853649	275/40ZR19	103Y	9.0-9.5-11.0	9	27.7	10.9	1929	50	750	500AA	32.0	
	853653	285/35ZR19	101Y	9.5-10.0-11.0	9	26.9	11.4	1819	50	772	500AA	30.7	
	20	850010	245/35ZR20	95W	8.0-8.5-9.5	9	26.8	9.8	1521	50	776	500AA	25.2
		850027	225/35ZR20	93W	7.5-8.0-9.0	9	26.2	9.1	1433	50	792	500AA	22.5
850034		245/40ZR20	99W	8.0-8.5-9.5	9	27.7	9.8	1709	50	749	500AA	25.6	
850041		225/30ZR20	85W	8	9	25.4	9.1	1135	50	819	500AA	20.1	
850058		255/35ZR20	97W	8.5-9.0-10.0	9	27.0	10.2	1609	50	769	500AA	27.2	
850065		235/35ZR20	92W	8.0-8.5-9.5	9	26.5	9.5	1389	50	785	500AA	23.7	
850072		275/35ZR20	102W	9.0-9.5-11.0	9	27.6	10.9	1764	50	754	500AA	29.2	
850089		275/30ZR20	97W	9.0-9.5-10.0	9	26.5	10.9	1609	50	783	500AA	27.5	
850096		245/30ZR20	97W	8.0-8.5-9.0	9	25.8	9.8	1609	50	804	500AA	23.8	
850102		285/30ZR20	99W	9.5-10.0-10.5	9	26.8	11.4	1709	50	776	500AA	28.2	

This data can be changed by manufacturer without prior notice.

NEW PRODUCT



The DST1 is an All-Season Ultra-High Performance tire designed for control and traction. This UHP is specifically engineered with tech features for maximum driving performance along with a low-noise design that ensures a comfortable ride. The DST1 also comes with a reliable 55K mileage warranty.

OPTIMIZED FOOTPRINT Optimized to improve fuel efficiency and mileage while enhancing the overall performance of the tire

LOW-NOISE DESIGN Engineered tread design reduces road noise, adding to the comfort of your ride

ANGLED CENTER RIBS The angle of the center ribs on the tread are engineered to deliver balanced performance during acceleration, braking, and cornering

3D SIPES Specifically for wet conditions, the 3D Sipes increase road traction, distributing the pressure evenly for better control

D-SHIELD 55K WARRANTY The Delinte 55K Mileage & Road Hazard Warranty Plan provides driving confidence for the life of the tire

M+S RATED The M+S rating on the tire sidewall indicates engineering for better traction in the mud and snow

SPORT TOURING 1DST1

PASSENGER CAR
TECH BOX
PERFORMANCE
ULTRA-HIGH
WHEEL DIAMETER
14" - 22"
MILEAGE WARRANTY
55K
COVERAGE
ROAD HAZARD



WHEEL DIAMETER	ARTICLE	SIZE	LOAD INDEX/ SPEED RATING	RIM WIDTH RANGE	TREAD DEPTH	OUTSIDE DIAMETER	SECTION WIDTH	MAX LOAD	MAX PRESSURE	RPM	UTQG	WEIGHT
				inches	32nds	inches	inches	lbs.	psi			lbs.
14	854629	185/65R14	86H	5.0-5.5-6.5	9	23.5	7.4	1168	44	885	560AA	15.9
	854636	185/70R14	88H	4.5-5.5-6.0	9	24.3	7.4	1235	44	856	560AA	17.1
	854643	195/60R14	86H	5.5-6.0-7.0	9	23.2	7.9	1168	44	894	560AA	16.2
	854674	195/70R14	91T	5.0-6.0-6.5	9	24.8	7.9	1356	44	837	560AA	18.5
15	854612	185/60R15	84H	5.0-5.5-6.5	9	23.7	7.4	1102	44	875	560AA	16.6
	854650	195/60R15	88H	5.5-6.0-7.0	9	24.2	7.9	1235	44	858	560AA	18.1
	854667	195/65R15	95H	5.5-6.0-7.0	9	25.0	7.9	1521	50	831	560AA	18.9
	854704	205/65R15	94H	5.5-6.0-7.5	9	25.5	8.2	1477	44	815	560AA	20.9
16	854681	205/55ZR16	94W	5.5-6.5-7.5	9	24.9	8.4	1477	50	835	560AA	20.2
	854698	205/60R16	92H	5.5-6.0-7.5	9	25.7	8.2	1389	44	809	560AA	20.0
	854711	205/65R16	99H	5.5-6.0-7.5	9	26.5	8.2	1709	50	785	560AA	21.8
	854728	205/70R16	98H	5.0-6.0-7.0	9	27.3	8.2	1653	50	760	560AA	24.0
	854742	215/65R16	102H	6.0-6.5-7.5	9	27.0	8.7	1874	50	769	560AA	23.0
	854827	225/60R16	98H	6.0-6.5-8.0	9	26.6	9.0	1653	44	780	560AA	23.8
17	854735	215/55ZR17	98W	6.0-7.0-7.5	9	26.3	8.9	1653	50	790	560AA	22.8
	854797	225/50ZR17	98W	6.0-7.0-8.0	9	25.9	9.2	1653	50	802	560AA	22.4
	854810	225/55ZR17	101W	6.0-7.0-8.0	9	26.8	9.2	1819	50	776	560AA	25.3
18	854766	225/40ZR18	92W	7.5-8.0-9.0	9	25.1	9.1	1389	50	828	560AA	21.2
	854773	225/45ZR18	95W	7.0-7.5-8.5	9	25.9	8.9	1521	50	801	560AA	22.3
	854803	225/50ZR18	99W	6.0-7.0-8.0	9	26.9	9.2	1709	50	772	560AA	25.0
	854858	235/45ZR18	98W	7.5-8.0-9.0	9	26.3	9.3	1653	50	789	560AA	22.9
	854865	235/50ZR18	101W	6.5-7.5-8.5	9	27.3	9.6	1819	50	761	560AA	25.6
	854896	245/45ZR18	100W	7.5-8.0-9.0	9	26.7	9.6	1764	50	779	560AA	27.0
	854926	255/35ZR18	94W	8.5-9.0-10.0	9	25.0	10.2	1477	50	831	560AA	24.8
	854957	255/40ZR18	99W	8.5-9.0-10.0	9	26.0	10.2	1709	50	798	560AA	27.0
	854988	275/40ZR18	99W	9.0-9.5-11.0	9	26.7	10.9	1709	44	779	560AA	28.4

WHEEL DIAMETER	ARTICLE	SIZE	LOAD INDEX/ SPEED RATING	RIM WIDTH RANGE	TREAD DEPTH	OUTSIDE DIAMETER	SECTION WIDTH	MAX LOAD	MAX PRESSURE	RPM	UTQG	WEIGHT
				inches	32nds	inches	inches	lbs.	psi			lbs.
19	854780	225/45ZR19	96W	7.0-7.5-8.5	9	27.0	8.9	1565	50	770	560AA	23.2
	854841	235/40ZR19	98Y	8.0-8.5-9.5	9	26.4	9.5	1653	50	786	560AA	23.5
	854872	245/40ZR19	98W	8.0-8.5-9.5	9	26.7	9.8	1653	50	777	560AA	25.2
	854902	245/45ZR19	102Y	7.5-8.0-9.0	9	27.7	9.6	1874	50	750	560AA	28.6
20	854964	255/40ZR19	100Y	8.5-9.0-10.0	9	27.0	10.2	1764	50	768	560AA	28.7
	842879	245/45ZR20	108W	7.5-8.0-9.0	9	28.7	9.6	2205	50	725	560AA	28.3
21	854889	245/40ZR20	99W	8.0-8.5-9.5	9	27.7	9.8	1709	50	749	560AA	26.7
	854933	255/35ZR21	98Y	8.5-9.0-10.0	9	28.0	10.2	1653	50	742	560AA	27.7
22	842886	245/30ZR22	96Y	8.0-8.5-9.0	9	27.8	9.8	1565	50	746	560AA	26.1
	842893	295/25ZR22	100Y	10.0-10.5-11.0	9	27.8	11.9	1764	50	746	560AA	34.6
	854759	225/30ZR22	89W	8.0	9	27.1	9.5	1279	50	767	560AA	24.5
	854834	235/30ZR22	90W	8.5	9	27.6	9.5	1323	50	753	560AA	25.0
	854919	255/30ZR22	95Y	8.5-9.0-9.5	9	28.1	10.2	1521	50	740	560AA	28.8
	854940	255/35ZR22	99Y	8.5-9.0-10.0	9	29.0	10.2	1709	50	716	560AA	29.1
854971	265/30ZR22	97W	9.0-9.5-10.0	9	26.5	10.9	1609	50	783	560AA	29.4	
854995	305/25ZR22	99Y	10.5-11.0-11.5	9	28.0	12.3	1709	50	742	560AA	31.9	

This data can be changed by manufacturer without prior notice.

NEW PRODUCT



The **DST2** is an All-Season Touring SUV/CUV tire. The All-Season engineering allows for all types of driving conditions from dry hot highways to wet or snowy road conditions. The low-noise design ensures a comfortable and quiet ride. The DST2 also comes with a reliable 55K mileage warranty.

3D SIPES Designed for wet conditions, 3D Sipes ensure contact with the road, distributing the pressure evenly on wet, dry, or snowy road surfaces

INTELLIGENT TREAD DESIGN Intelligent tread block pattern reduces road noise and provides a comfortable ride

OPTIMIZED TREAD CONTACT Distributes tread grip, reduces rolling resistance, and optimizes tread wear

WIDE TREAD GROOVES Evacuate water quickly for improved driving performance, reducing hydroplaning at high speeds

D-SHIELD 55K WARRANTY The Delinte 55K Mileage & Road Hazard Warranty Plan provides driving confidence for the life of the tire

M+S RATED The M+S rating on the tire sidewall indicates engineering for better traction in the mud and snow

SPORT TOURING 2DST2

PASSENGER CAR
TECH BOX
PERFORMANCE
ALL-SEASON
WHEEL DIAMETER
16" - 23"
MILEAGE WARRANTY
55K
COVERAGE
ROAD HAZARD



ALL SEASONS



WHEEL DIAMETER	ARTICLE	SIZE	LOAD INDEX/ SPEED RATING	RIM WIDTH RANGE	TREAD DEPTH	OUTSIDE DIAMETER	SECTION WIDTH	MAX LOAD	MAX PRESSURE	RPM	UTQG	WEIGHT
				inches	32nds	inches	inches	lbs.	psi			lbs.
16	853714	235/65R16	107H	6.5-7.0-8.5	10	28.0	9.4	2149	50	741	560AA	27.6
	842909	225/65R17	102H	6.0-6.5-8.0	10	31.9	11.2	2833	44	729	560AA	27.8
17	853691	235/55ZR17	103W	6.5-7.5-8.5	10	27.2	9.6	1929	50	765	560AA	27.0
	853707	235/60R17	105H	6.5-7.0-8.5	10	28.1	9.4	2039	50	739	560AA	27.8
18	853660	225/55ZR18	102W	6.0-7.0-8.0	10	27.8	9.2	1874	50	748	560AA	26.5
	853684	225/60R18	100V	6.0-6.5-8.0	10	28.6	9.0	1764	44	726	560AA	26.7
19	853677	225/55R19	99H	6.0-7.0-8.0	10	28.8	9.2	1709	44	722	560AA	28.2
20	842916	275/55R20	117V	7.5-8.5-9.5	10	31.9	11.2	2833	50	651	560AA	39.4
	853745	255/45ZR20	105W	8.0-8.5-9.5	10	29.1	10.0	2039	50	715	560AA	30.6
21	853721	245/35ZR21	96Y	8.0-8.5-9.5	10	27.8	9.8	1565	50	748	560AA	27.3
	853738	255/40ZR21	105Y	8.5-9.0-10.0	10	29.0	10.2	2039	50	716	560AA	32.4
	853752	265/40ZR21	105Y	9.0-9.5-10.5	10	29.3	10.7	2039	50	708	560AA	34.0
	853769	265/45ZR21	108W	8.5-9.0-10.0	10	30.4	10.5	2205	50	684	560AA	36.3
	853783	275/40ZR21	109W	9.0-9.5-11.0	10	29.6	10.9	2271	50	701	560AA	35.8
	853820	295/35ZR21	109Y	10.0-10.5-11.5	10	29.1	11.9	2271	50	714	560AA	37.2
	853837	295/40ZR21	111W	10.0-10.5-11.5	10	30.3	11.9	2403	50	686	560AA	39.7
	853844	315/35ZR21	111Y	10.5-11.0-12.5	10	29.6	12.6	2403	50	701	560AA	39.8
22	853851	315/40ZR21	115Y	10.5-11.0-12.5	10	30.9	12.6	2679	50	672	560AA	41.7
	842923	275/50R22	115H	7.5-8.5-9.5	10	32.9	11.2	2679	50	632	560AA	42.9
	850140	285/35R22	109Y	9.5-10.0-11.0	10	29.9	11.4	2271	50	695	560AA	38.2
	850157	315/30R22	111Y	10.5-11.0-11.5	10	29.5	12.6	2403	50	704	560AA	40.8
	853776	275/35ZR22	104Y	9.0-9.5-11.0	10	29.6	10.9	1984	50	702	560AA	33.1
	853790	275/50R22	111H	7.5-8.5-9.5	10	32.9	11.2	2403	44	632	560AA	42.9
23	853813	295/25ZR22	97W	10.0-10.5-11.0	9	27.8	11.9	1609	50	746	560AA	34.6
	853806	285/40ZR23	111Y	9.5-10.0-11.0	10	32.0	11.4	2403	50	650	560AA	41.2

This data can be changed by manufacturer without prior notice.



The **DS8** is an All-Season Ultra-High Performance tire designed for control and traction. With speed ratings H, V, W & Y, the DS8 is specifically designed to match the aesthetics of your vehicle and give you the freedom to perform.

STAGGERED FITMENTS High-performance wheel and tire setups that are larger in the rear than in the front of the vehicle

H, V, W & Y SPEED RATINGS Representing maximum driving speed for this tire, based on the manufacturer's recommendation

BIG BLOCK TREAD PATTERNS Maximize contact while wide-open throttle driving and evacuate water effectively for superior performance

ANGLED TREAD SLOTS Designed to move rain and snow out of the tire tread for better control in wet conditions

D-SHIELD 50K WARRANTY Protecting your tires for up to 50K of mileage, which also includes the Delinte Road Hazard Warranty Plan

M+S RATED The M+S rating on the tire sidewall indicates engineering for better traction in the mud and snow

DS8

PASSENGER CAR
TECH BOX

PERFORMANCE
ULTRA-HIGH

WHEEL DIAMETER
18" 19" 20" 21"
22" 24" 26" 28"
30" 32"

AVAILABLE SIZES
69

MILEAGE WARRANTY
50K
COVERAGE
ROAD HAZARD



WHEEL DIAMETER	ARTICLE	SIZE	LOAD INDEX/ SPEED RATING	RIM WIDTH RANGE	TREAD DEPTH	OUTSIDE DIAMETER	SECTION WIDTH	MAX LOAD	MAX PRESSURE	RPM	UTQG	WEIGHT
				inches	32nds	inches	inches	lbs.	psi			lbs.
18	805621	245/40R18	97W XL	8.0-8.5-9.5	10	25.7	9.8	1609	49	808	500/A/A	25.0
	805638	285/35R18	101W XL	9.5-10.0-11.0	10	25.9	11.4	1819	49	803	500/A/A	29.0
	805645	245/35R18	92W XL	8.0-8.5-9.5	10	24.8	9.8	1389	49	839	500/A/A	24.0
	805652	265/45R18	101W	8.5-9.0-10.0	10	27.4	10.5	1819	44	759	500/A/A	29.0
	805669	235/45R18	98W XL	7.5-8.0-9.0	10	26.3	9.3	1653	49	789	500/A/A	25.0
	805676	265/40R18	101Y XL	9.0-9.5-10.5	10	26.3	10.7	1819	49	789	500/A/A	29.0
19	805256	285/45R19	107Y XL	9.0-9.5-10.5	10	29.1	11.2	2149	44	714	500/A/A	33.0
	805263	255/50R19	107Y XL	7.0-8.0-9.0	10	29.1	10.4	2149	49	714	500/A/A	32.0
	805270	265/50R19	110W XL	7.5-8.5-9.5	10	29.5	10.9	2337	49	704	500/A/A	35.0
	805287	245/55R19	103W	7.0-7.5-8.5	10	29.6	10.0	1929	44	701	500/A/A	31.0
	805553	235/55R19	105W XL	6.5-7.5-8.5	10	29.2	9.6	2039	49	712	500/A/A	30.0
	805577	285/40R19	103Y	9.5-10.0-11.0	10	28.0	11.4	1929	44	742	500/A/A	34.0
	011459	255/55R19	111W XL	7.0-8.0-9.0	10	30.0	10.4	2403	49	691	500/A/A	34.0
	011695	225/55R19	99H	6.0-7.0-8.0	10	28.8	9.2	1709	44	722	500/A/A	30.0
	011763	255/45R19	100Y	8.0-8.5-9.5	10	28.1	10.0	1764	44	740	500/A/A	29.0
	20	804877	235/55R20	104W XL	6.5-7.5-8.5	10	30.2	9.6	1984	49	689	500/A/A
804914		295/40R20	108Y XL	10.0-10.5-11.5	10	29.3	11.9	2205	49	709	500/A/A	38.0
805294		265/45R20	108W	8.5-9.0-10.0	10	29.4	10.5	2205	49	707	500/A/A	33.0
805317		275/50R20	113W XL	7.5-8.5-9.5	10	30.9	11.2	2535	49	673	500/A/A	38.0
805324		275/60R20	115W	7.5-8.0-9.5	10	33.0	11.0	2679	44	630	500/A/A	40.0
805478		255/50R20	109Y XL	7.0-8.0-9.0	10	30.1	10.4	2271	49	690	500/A/A	35.0
805492		205/30R20	82W XL	6.5-7.0-7.5	10	24.9	8.6	1047	49	835	500/A/A	19.0
805508		215/30R20	82W XL	7.0-7.5-8.5	10	25.1	9.0	1047	49	827	500/A/A	21.0
805515		265/50R20	111W XL	7.5-8.5-9.5	10	30.5	10.9	2403	49	682	500/A/A	36.0
805683		275/55R20	117V XL	7.5-8.5-9.5	10	31.9	11.2	2833	49	651	500/A/A	40.0
805690		245/45R20	108W XL	7.5-8.0-9.0	10	28.7	9.6	2205	49	725	500/A/A	29.0
805706		275/45R20	114V XL	8.5-9.0-10.5	10	29.8	10.7	2601	49	698	500/A/A	35.0
805737		275/40R20	108W XL	9.0-9.5-11.0	10	28.7	10.9	2205	49	725	500/A/A	32.0
813817		245/50R20	102V	7.0-7.5-8.5	10	29.7	10.0	1874	44	700	500/A/A	31.0
011589	315/35R20	110W XL	10.5-11.0-12.5	10	28.7	12.6	2337	49	725	500/A/A	38.0	
011725	265/45R20	104W	8.5-9.0-10.0	10	29.4	10.5	1984	44	707	500/A/A	33.0	
21	804891	265/40R21	105Y XL	9.0-9.5-10.5	10	29.3	10.7	2039	49	708	500/A/A	35.0
	804907	295/35R21	109Y XL	10.0-10.5-11.5	10	29.1	11.9	2271	49	714	500/A/A	37.0
	804921	325/30R21	110Y XL	11.0-11.5-12.0	10	28.7	13.0	2337	49	724	500/A/A	38.0
	805034	285/35R21	108Y XL	9.5-10.0-11.0	10	28.9	11.4	2205	49	720	500/A/A	35.0
	805331	275/40R21	109W XL	9.0-9.5-11.0	10	29.6	10.9	2271	49	701	500/A/A	35.0
	805348	295/40R21	111W XL	10.0-10.5-11.5	10	30.3	11.9	2403	49	686	500/A/A	39.0
	805355	245/45R21	107W XL	7.5-8.0-9.0	10	29.6	9.6	2149	49	701	500/A/A	32.0
	805584	245/35R21	96Y XL	8.0-8.5-9.5	10	27.8	9.8	1565	49	748	500/A/A	28.0
	805591	245/40R21	100Y XL	8.0-8.5-9.5	10	28.7	9.8	1764	49	724	500/A/A	31.0
	805607	285/30R21	100Y XL	9.5-10.0-10.5	10	27.8	11.4	1764	49	748	500/A/A	33.0
22	805614	275/45R21	110Y XL	8.5-9.0-10.5	10	30.7	10.7	2337	49	675	500/A/A	38.0
	805362	265/35R22	106W XL	9.0-9.5-10.5	10	29.3	10.7	2094	49	708	500/A/A	32.0
	805379	295/30R22	110W XL	10.0-10.5-11.0	10	29.0	11.9	2337	49	716	500/A/A	33.0
	805485	315/30R22	107Y XL	10.5-11.0-11.5	10	29.5	12.6	2149	49	704	500/A/A	39.0
	805522	285/40R22	110V XL	9.5-10.0-11.0	11	31.0	11.4	2337	49	670	500/A/A	38.0
	805713	285/45R22	116V XL	9.0-9.5-10.5	10	32.1	11.2	2756	49	647	500/A/A	41.0
	805720	305/45R22	118V XL	9.5-10.0-11.5	10	32.8	11.9	2910	49	633	500/A/A	44.0
	805744	265/40R22	110V XL	9.0-9.5-10.5	10	30.4	10.7	2337	49	684	500/A/A	36.0
	805775	285/35R22	110W XL	9.5-10.0-11.0	10	29.9	11.4	2337	49	695	500/A/A	35.0
	805911	275/45R22	114V XL	8.5-9.0-10.5	10	31.8	10.7	2601	49	654	500/A/A	39.0
011602	305/40R22	114V XL	10.0-11.0-12.0	10	31.6	12.3	2601	49	657	500/A/A	40.0	

WHEEL DIAMETER	ARTICLE	SIZE	LOAD INDEX/ SPEED RATING	RIM WIDTH RANGE	TREAD DEPTH	OUTSIDE DIAMETER	SECTION WIDTH	MAX LOAD	MAX PRESSURE	RPM	UTQG	WEIGHT
				inches	32nds	inches	inches	lbs.	psi			lbs.
24	804884	245/25R24	101W XL	8.5-9.0-9.5	10	28.8	9.8	1819	49	721	500/A/A	27.0
	805386	245/30R24	103Y XL	8.0-8.5-9.0	10	28.8	9.8	1929	49	721	500/A/A	30.0
	805393	295/25R24	109Y XL	10.0-10.5-11.0	10	35.3	11.4	2271	49	589	500/A/A	37.0
	805782	295/35R24	114V XL	10.0-10.5-11.5	10	32.1	11.9	2601	49	646	500/A/A	40.0
	805799	305/35R24	114V XL	10.0-11.0-12.0	10	32.4	12.3	2601	49	640	500/A/A	41.0
	805805	255/30R24	102W XL	8.5-9.0-9.5	10	30.1	10.2	1389	49	690	500/A/A	33.0
26	805812	275/30R24	110W XL	9.0-9.5-10.0	11	30.6	10.9	2337	49	680	500/A/A	34.0
	805850	275/25R24	102W XL	10.0	10	29.4	11.1	1874	49	705	500/A/A	32.0
	805829	255/30R26	105W XL	8.5-9.0-9.5	10	32.1	10.2	2039	49	647	500/A/A	36.0
	805836	295/30R26	114W XL	10.0-10.5-11.0	10	33.0	11.9	2601	49	630	500/A/A	42.0
	805843	305/30R26	116W XL	10.5-11.0-11.5	10	33.2	12.3	2756	49	625	500/A/A	42.0
	805867	275/25R26	102W XL	10.0	10	29.4	11.1	1874	49	705	500/A/A	36.0
28	805874	275/25R28	114W XL	10.0	10	31.5	11.1	2601	49	660	500/A/A	39.0
	805881	295/25R28	116Y XL	10.0-10.5-11.0	10	33.8	11.9	2756	49	614	500/A/A	43.0
30	805898	275/20R30	114V XL	10.0	10	34.3	11.1	2601	49	605	500/A/A	40.0
	805904	275/25R30	114W XL	10.0	10	33.5	11.1	2601	49	621	500/A/A	41.0
32	805928	305/25R32	114W XL	10.5-11.0-11.5	10	38.0	12.3	2601	49	547	500/A/A	48.0

This data can be changed by manufacturer without prior notice.



SAVES MONEY

The **DH2** is an All-Season Performance tire developed to give you a long-lasting, quiet ride without road noise. It's an excellent choice for a quality replacement tire, and comes with the 50K D-Shield Warranty.



ASYMMETRICAL TREAD DESIGN Unique noise-minimizing grooves allow for easy tire rotation without changes in traction

TIRE SHOULDER DESIGN Ensures even tread wear and extends the life of the tire

D-SHIELD 50K WARRANTY Protecting your tires for up to 50K of mileage, which also includes the Delinte Road Hazard Warranty Plan

M+S RATED The M+S rating on the tire sidewall indicates engineering for better traction in the mud and snow

DH2

PASSENGER CAR
TECH BOX
PERFORMANCE
ALL-SEASON
WHEEL DIAMETER
**13" 14" 15" 16"
17" 18" 19" 20"
21" 22"**
AVAILABLE SIZES
94
MILEAGE WARRANTY
50K
COVERAGE
ROAD HAZARD



WHEEL DIAMETER	ARTICLE	SIZE	LOAD INDEX/ SPEED RATING	RIM WIDTH RANGE	TREAD DEPTH	OUTSIDE DIAMETER	SECTION WIDTH	MAX LOAD	MAX PRESSURE	RPM	UTQG	WEIGHT	
				inches	32nds	inches	inches	lbs.	psi			lbs.	
13	200231	165/65R13	77T	4.5-5.0-6.0	9	21.4	6.7	908	44	970	420/A/A	14.0	
	201030	165/70R13	79T	4.0-5.0-5.5	9	22.1	6.7	963	44	939	420/A/A	14.0	
	201122	165/65R13	77H	4.5-5.0-6.0	9	21.4	6.7	908	44	970	420/A/A	14.0	
	201238	175/70R13	82T	4.5-5.0-6.0	9	22.7	7.0	1047	44	916	420/A/A	16.0	
	200033	165/60R14	75T	4.5-5.0-6.0	9	21.8	6.7	853	44	952	420/A/A	14.0	
14	200125	185/60R14	82H	5.0-5.5-6.5	9	22.8	7.4	1047	44	913	420/A/A	16.0	
	200132	175/60R14	79T	5.0-5.5-6.0	9	22.3	7.0	963	44	932	420/A/A	15.0	
	200224	195/60R14	86H	5.5-6.0-7.0	9	23.2	7.9	1168	44	894	420/A/A	17.0	
	200330	165/65R14	79T	4.5-5.0-6.0	9	22.4	6.7	963	44	926	420/A/A	15.0	
	200439	175/65R14	82T	5.0-5.5-6.0	9	23.0	7.0	1047	44	903	420/A/A	15.0	
	200637	185/65R14	86T	5.0-5.5-6.5	9	23.5	7.4	1168	44	885	420/A/A	17.0	
	201221	165/65R14	79H	4.5-5.0-6.0	9	22.4	6.7	963	44	926	420/A/A	15.0	
	201320	175/65R14	82H	5.0-5.5-6.0	9	23.0	7.0	1047	44	903	420/A/A	15.0	
	201337	165/70R14	81T	4.0-5.0-5.5	9	23.1	6.7	1019	44	897	420/A/A	15.0	
	201436	175/70R14	88T XL	5.0-5.5-6.0	9	23.7	7.0	1235	49	876	420/A/A	16.0	
	201528	185/65R14	86H	5.0-5.5-6.5	9	23.5	7.4	1168	44	885	420/A/A	17.0	
	201535	185/70R14	88T	4.5-5.5-6.0	9	24.3	7.4	1235	44	856	420/A/A	17.0	
	201634	195/70R14	91T	5.0-6.0-6.5	9	24.8	7.9	1356	44	837	420/A/A	19.0	
	203027	175/70R14	88H	5.0-5.5-6.0	9	23.7	7.0	1235	49	876	420/A/A	16.0	
	203126	185/70R14	88H	4.5-5.5-6.0	9	24.3	7.4	1235	44	856	420/A/A	17.0	
	203225	195/70R14	91H	5.0-6.0-6.5	9	24.8	7.9	1356	44	837	420/A/A	19.0	
	15	200057	195/50R15	82V	5.5-6.0-7.0	9	22.7	7.9	1047	44	914	420/A/A	18.0
		200156	195/55R15	85V	5.5-6.0-7.0	9	23.4	7.9	1135	44	887	420/A/A	18.0
200255		195/60R15	88V	5.5-6.0-7.0	9	24.2	7.9	1235	44	858	420/A/A	19.0	
200323		185/60R15	84H	5.0-5.5-6.5	9	23.7	7.4	1102	44	875	420/A/A	18.0	
200354		205/60R15	91V	5.5-6.0-7.0	9	24.7	8.2	1356	44	841	420/A/A	20.0	
200422		195/60R15	88H	5.5-6.0-7.0	9	24.2	7.9	1235	44	858	420/A/A	19.0	
200736		175/65R15	84T	5.0-5.5-6.0	9	24.0	7.0	1102	44	866	420/A/A	17.0	
200835		185/65R15	88T	5.0-5.5-6.5	9	24.4	7.4	1235	44	850	420/A/A	18.0	
200958		195/65R15	91V	5.5-6.0-7.0	9	25.0	7.9	1356	44	831	420/A/A	20.0	
201627		175/65R15	84H	5.0-5.5-6.0	9	24.0	7.0	1102	44	866	420/A/A	17.0	
201726		185/65R15	88H	5.0-5.5-6.5	9	24.4	7.4	1235	44	850	420/A/A	18.0	
201924		195/65R15	91H	5.5-6.0-7.0	9	25.0	7.9	1356	44	831	420/A/A	20.0	
202020		195/65R15	95 H XL	5.5-6.0-7.0	9	25.0	7.9	1521	49	831	420/A/A	20.0	
202129		205/65R15	94H	5.5-6.0-7.5	9	25.5	8.2	1477	44	815	420/A/A	21.0	
203324		215/70R15	98H	5.5-6.5-7.0	9	26.9	8.7	1653	44	772	420/A/A	24.0	
16	200453	205/60R16	92V	5.5-6.0-7.5	9	25.7	8.2	1389	44	809	420/A/A	21.0	
	200521	205/60R16	92H	5.5-6.0-7.5	9	25.7	8.2	1389	44	809	420/A/A	21.0	
	200552	215/60R16	95V	6.0-6.5-7.5	9	26.1	8.7	1709	49	794	420/A/A	23.0	
	200620	215/60R16	95H	6.0-6.5-7.5	9	26.1	8.7	1709	49	794	420/A/A	23.0	
	200651	215/60R16	99V	6.0-6.5-7.5	9	26.1	8.7	1709	49	794	420/A/A	23.0	
	200729	215/60R16	99H	6.0-6.5-7.5	9	26.1	8.7	1709	49	794	420/A/A	23.0	
	200828	225/60R16	98H	6.0-6.5-8.0	9	26.6	9.0	1653	44	780	420/A/A	24.0	
	201511	205/50ZR16	87W	5.5-6.5-7.5	9	24.1	8.4	1201	44	862	420/A/A	20.0	
	202112	195/55ZR16	87W	5.5-6.0-7.0	9	24.4	7.9	1201	44	851	420/A/A	20.0	
	202211	205/55ZR16	91W	5.5-6.5-7.5	9	24.9	8.4	1356	44	835	420/A/A	21.0	
	202310	205/55ZR16	94W XL	5.5-6.5-7.5	9	24.9	8.4	1477	49	835	420/A/A	21.0	
	202327	205/65R16	99H	5.5-6.0-7.5	9	26.5	8.2	1709	49	785	420/A/A	22.0	
	202419	215/55ZR16	97W XL	6.0-7.0-7.5	9	25.3	8.9	1609	49	822	420/A/A	22.0	
	202426	215/65R16	102H XL	6.0-6.5-7.5	9	27.0	8.7	1874	49	769	420/A/A	24.0	
	202518	225/55ZR16	99W XL	6.0-7.0-8.0	9	25.7	9.2	1709	49	807	420/A/A	24.0	
	202525	225/65R16	100H	6.0-6.5-8.0	9	27.5	9.0	1764	44	756	420/A/A	24.0	
	203423	215/70R16	100H	5.5-6.5-7.0	9	27.9	8.7	1764	44	745	420/A/A	25.0	
	203522	205/65R16	95H	5.5-6.0-7.5	9	26.5	8.2	1521	44	785	420/A/A	22.0	
804938	205/70R16	98H	5.0-6.0-7.0	9	27.3	8.2	1653	49	760	420/A/A	25.0		

WHEEL DIAMETER	ARTICLE	SIZE	LOAD INDEX/ SPEED RATING	RIM WIDTH RANGE	TREAD DEPTH	OUTSIDE DIAMETER	SECTION WIDTH	MAX LOAD	MAX PRESSURE	RPM	UTQG	WEIGHT
				inches	32nds	inches	inches	lbs.	psi			lbs.
17	200217	205/40ZR17	84W XL	7.0-7.5-8.0	9	23.5	8.3	1102	49	885	420/A/A	19.0
	200316	245/40ZR17	95W XL	8.0-8.5-9.5	9	24.7	9.8	1521	49	840	420/A/A	23.0
	200750	215/60R17	100V XL	6.0-6.5-7.5	9	27.2	8.7	1764	49	765	420/A/A	25.0
	200811	215/45ZR17	91W XL	7.0-7.5-8.0	9	24.6	8.4	1356	49	843	420/A/A	20.0
	200910	225/45ZR17	94W XL	7.0-7.5-8.5	9	25.0	8.9	1477	49	832	420/A/A	21.0
	200927	215/60R17	100H XL	6.0-6.5-7.5	9	27.2	8.7	1764	49	765	420/A/A	25.0
	201016	235/45ZR17	97W XL	7.5-8.0-9.0	9	25.4	9.3	1609	49	819	420/A/A	24.0
	201115	245/45ZR17	99W XL	7.5-8.0-9.0	9	25.7	9.6	1709	49	809	420/A/A	25.0
	201610	205/50ZR17	93W	5.5-6.5-7.5	9	25.1	8.4	1433	49	827	420/A/A	21.0
	201719	215/50ZR17	95W XL	6.0-7.0-7.5	9	25.5	8.9	1521	49	814	420/A/A	22.0
	201818	225/50ZR17	98W XL	6.0-7.0-8.0	9	25.9	9.2	1653	49	802	420/A/A	24.0
	202617	215/55ZR17	94W	6.0-7.0-7.5	9	26.3	8.9	1477	44	790	420/A/A	23.0
	202716	215/55ZR17	98W XL	6.0-7.0-7.5	9	26.3	8.9	1653	49	790	420/A/A	23.0
	202914	225/55ZR17	101W XL	6.0-7.0-8.0	9	26.8	9.2	1819	49	776	420/A/A	26.0
	804952	235/60R17	105H XL	6.5-7.0-8.5	9	28.1	9.4	2039	49	739	420/A/A	29.0
18	200019	215/35ZR18	84W XL	7.0-7.5-8.5	9	23.9	8.6	1102	49	869	420/A/A	19.0
	200118	255/35ZR18	94W XL	8.5-9.0-10.0	9	25.0	10.2	1477	49	831	420/A/A	25.0
	200415	215/40ZR18	89W XL	7.0-7.5-8.5	9	24.8	8.6	1279	49	839	420/A/A	21.0
	200514	225/40ZR18	92W XL	7.5-8.0-9.0	9	25.1	9.1	1389	49	828	420/A/A	22.0
	200613	235/40ZR18	95W XL	8.0-8.5-9.5	9	25.4	9.5	1521	49	818	420/A/A	23.0
	200712	245/40ZR18	97W XL	8.0-8.5-9.5	9	25.7	9.8	1609	49	808	420/A/A	25.0
	201023	225/60R18	100H XL	6.0-6.5-8.0	9	28.6	9.0	1764	49	726	420/A/A	28.0
	201214	225/45ZR18	95W XL	7.0-7.5-8.5	9	25.9	8.9	1521	49	801	420/A/A	22.0
	201313	235/45ZR18	98W XL	7.5-8.0-9.0	9	26.3	9.3	1653	49	789	420/A/A	25.0
	201412	245/45ZR18	100W XL	7.5-8.0-9.0	9	26.7	9.6	1764	49	779	420/A/A	26.0
	201917	225/50ZR18	99W XL	6.0-7.0-8.0	9	26.9	9.2	1709	49	772	420/A/A	26.0
	202013	235/50ZR18	101W XL	6.5-7.5-8.5	9	27.3	9.6	1819	49	761	420/A/A	27.0
	203010	225/55ZR18	102W XL	6.0-7.0-8.0	9	27.8	9.2	1874	49	748	420/A/A	28.0
	203119	235/55ZR18	104W XL	6.5-7.5-8.5	9	28.1	9.6	1984	49	738	420/A/A	28.0
	19	804945	235/40ZR19	98Y	8.0-8.5-9.5	9	26.4	9.5	1653	49	786	420/A/A
804969		245/45ZR19	102Y	7.5-8.0-9.0	9	27.7	9.6	1874	49	750	420/A/A	26.0
804976		255/40ZR19	101Y	8.5-9.0-10.0	9	27.0	10.2	1819	49	768	420/A/A	28.0
804990		265/35ZR19	99Y	9.0-9.5-10.5	9	26.3	10.7	1709	49	789	420/A/A	29.0
805010		275/40ZR19	103Y	9.0-9.5-11.0	9	27.7	10.9	1929	49	750	420/A/A	31.0
805027		285/35ZR19	101Y	9.5-10.0-11.0	10	26.9	11.4	1819	49	772	420/A/A	31.0
20	805041	295/30ZR20	105Y	10.0-10.5-11.5	10	27.0	11.6	1609	49	769	420/A/A	30.3
21	805409	245/35ZR21	100Y XL	8.0-8.5-9.5	9	27.8	9.8	1764	49	748	420/A/A	28.0
	805416	275/30ZR21	102Y	8.5-9.0-10.5	9	27.5	10.8	1653	49	756	420/A/A	31.0
22	809469	335/25ZR22	105W XL	11.5-12.0-12.5	10	28.6	13.5	2039	49	726	420/A/A	36.0

This data can be changed by manufacturer without prior notice.

BECOME A DELINTE DEALER

Scan our code here and submit your information to become a Delinte dealer today.



DELINTE

WE INVENT. YOU DRIVE.

LIMITED TIRE WARRANTY SUMMARY OF LIMITED TIRE WARRANTY COVERAGE BY DELINTE TREAD PATTERN

PATTERN	ROAD HAZARD	MILEAGE WARRANTY
Bandit M/TDX9	No	N/A
Bandit R/TDX12	No	N/A
Bandit A/TDX10	Yes*	50,000
Bandit X/TDX20	Yes*	55,000
Bandit H/TDX11	Yes*	50,000
Dynamx Sport 2DS2	Yes*	55,000
Sport Touring 1DST1	Yes*	55,000
Sport Touring 2DST2	Yes*	55,000
DS8	Yes*	50,000
DH2	Yes*	50,000

Warranty or Road Hazard Claims MUST be processed directly with the Delinte Tire Retailer where the replacement tires were purchased (including internet retailers). Warranty claims will not be processed through the manufacturer.

Warranty coverage is for indicated Delinte tread patterns only.

*Limited Applications.

No coverage for commercial use.

Warranty and Road Hazard Protection program does not apply to tires sold in Canada and Mexico.

Effective July 1, 2017

For full details visit: DELINTETIRES.COM/WARRANTY



DELINTETIRES.COM

11210 W 43rd Ave

Hiialeah, FL 33018

Phone: 305-621-5101

#DELINTETIRES

The marks, slogans and logos appearing herein are the property of Sentury Tire USA and/or its affiliates. Sentury Tire USA ©2024.

All rights reserved. DL*CG*2024 v2