

# DIGITAILS


DIGITAL TAILLIGHTS

## 1981-83 MALIBU

Eight panel Sequential LED Taillight  
w/LED reverse kit installation instructions

### Kit Contents:

- **6** taillight LED panels
- **2** reverse LED panels
- **6** rubber grommets
- **1** power wire with T-Tap
- **3** Driver side LED harnesses, 24"
- **3** Passenger side LED harnesses, 48"
- **6** LED extension harnesses, 12"
- **3** harness crimp kits
- **16** mounting brackets




P/N 1101681

**Note**

The LED boards are shipped with the slide switch set to sequential mode. We recommend that all slide switches be set to the same setting (either standard or sequential).

Please follow all local laws concerning exterior lighting.



**Hint**

You may begin with the LED panel installation, however, you will need to complete the wiring modifications before the LED panels and housings are paired as one. Read over the entire instruction guide to determine the method that works best for you.

## LED PANEL INSTALLATION

**1. Cut off the power to your car.**


Disconnect the negative terminal from the battery, which will cut off the power in your car. To verify that the power is disconnected, press the brake pedal; your brake lights should not turn on.

**2. Remove the taillights.**

Remove the bulbs from the sockets. Put them aside since they will no longer be needed. Pull the light sockets out from the taillight housings. Remove the taillight housing assembly from the car.

**3. Identify the LED panels.**

Each Taillight LED panel is marked on its backside, which identifies where each respective LED panel is to be mounted. As example, shown is the **DRIVER side LEFT** pane labeled **DL**. This panel will be mounted in the left most pocket of the taillight housing. There is also the **DRIVER side CENTER** panel, labeled **DC**, and **DRIVER side RIGHT** panel labeled **DR**.




#### 4. Attach mounting brackets.

Both housings will require mounting brackets for the LED panels to attach to.


1. Start with the smallest pocket  
Measure down 5/8" from the vertical edge.

Lip edge



2. Attach an angle bracket with its face on the mark on the mark.

3. Repeat the procedure for the opposite wall in the pocket. The LED panel now has 2 ledges to sit on.



4. For the other 3 pockets, mount the brackets on the horizontal ends. Again, measure down 5/8" from the edge and attach the brackets.



#### 5. Plug in extension wires, grommets.

Feed the extension wires through the socket hole. Wrap the rubber grommet around the wires and press it into the socket hole. Once the LED panels are in place for good, you will still be able to easily plug and unplug the harness and remove the buckets.




#### Hint

It is best to use a small flat head screw driver to work the grommets onto the socket holes.

## 6. Attach the LED panels.

1. Remove the protective covering from the double sided strips on the angle brackets
2. Plug the **TAILLIGHT** LED panels into the harness extensions and one by one attach the LED panels in place.



*Be sure that the LEDs across all panels are in a nice straight line. This will ensure they look their best behind the lens.*

3. Plug the **REVERSE** LED panels into the stock sockets.



## WIRE SPLICING INSTALLATION

### 1. Review the wiring diagrams found on the last page.

Each LED panel needs five connections. Listed are the LED harness colors and their respective function. Note: Depending on make and harness, colors may not match.

**ORANGE** - Constant 12 volt power source.

**BLACK** - Grounded to body.

**YELLOW** - Driver side turn signal.









**GREEN** - Passenger side turn signal.

**BROWN** - Running/park signal.

### 2. Find and access the taillight wires.

Pick a point in the rear body panel between the driver's side quarter panel and the driver's side taillight housing assembly and remove the cloth tape to expose the taillight wires.

### 3. Splice the LED SIGNAL wires into the stock SIGNAL wires. Match the LED harness to the corresponding stock harness as shown below.

| LED Harness   | Function  | Stock harness  | Notes   |
|---|---|--|---|
|  Green  | Passenger side turn signal/<br>Brake light signal |  Green  | The light socket ends on the car harness can be removed.            |
|  Yellow | Driver side turn signal/<br>Brake light signal    |  Yellow | The light socket ends on the car harness can be removed.            |
|  Brown  | Running/Park signal                               |  Black  | Running light wires.  |
|  Orange | Constant 12 volt                                  |  | Find power at fuse panel/trunk light/dome light/fused battery feed. |
|  Black  | Ground  |  | Ground to Body/chassis  |

### Note about brake lights

There is no dedicated Brake light signal wire. When the brake pedal is pressed the brake switch sends power into the turn signal switch and then power through both the driver and passenger signal wires to activate the brake lights.

### 4. Connect all the ground wires.

Connect all the ground wires together. Bolt them to the trunk latch support along with the original rear body harness ground. The ground connection must be good in order to operate the LED tail lights.

5. Supply the LED panel harnesses with a constant 12 volt feed using the included **Orange** power wire and T-Tap.

An Orange power wire is supplied along with a T-Tap. The orange power wire must be powered with a constant 12 volt battery supply for the LED circuitry to operate properly. You can use the included T-Tap connector to splice to a constant power source, like the dome light, trunk light, fuse box, etc.

Splice the T-Tap connector over the constant power source, then plug the orange wire into the T-Tap. The other end of the orange power wire is tied in with the orange wires of all the LED panel harnesses.



1. Insert wire into T-Tap



2. Crimp with pliers



3. Plug connector into T-Tap

6. Tuck and secure the spliced wires.

Take the spliced sections and fold them over to one side and tape them in place. This will allow you to place the wiring into loom or wrap the LED panel wiring tightly away.



1. Fold wires to one side.



2. Secure with electrical tape.

### Note

A wire diagram of the LED panel's harness spliced into the car's stock harness is on the last page.

### Note

The LED light kits are designed for best performance when use an electronic no-load flasher. Shown here is an optional electronic no load flasher available from DIGI-TAILS, (PN 20-F2)




If you decide to use a stock bimetal flasher, we recommend a standard-duty flasher instead of a heavy-duty flasher. If your turn signal circuit includes front and rear LED turn signals, the circuit will not have enough resistance load to operate a heavy-duty bimetal flasher, so the no-load flasher will be required for both the turn signal and emergency flashers.

STOCK REAR BODY HARNESS

STOCK HARNESS COLORS. BROWN: GREEN: YELLOW

ALTHOUGH CLOSED END CONNECTORS ARE INCLUDED, IT IS RECOMMENDED THAT ALL SPLICED WIRES BE SOLDERED TOGETHER FOR BEST CONNECTION RELIABILITY.

POWER CONNECTION  
CONSTANT FUSED POWER SOURCE.  
(AT DOME LIGHT OR FUSEPANEL)  
DRAWS LOW CURRENT, LESS THAN 3 AMPS.



ALL 6 LED PANELS REQUIRE DRIVER AND PASSENGER SIGNALS.

LED REVERSE PANELS PLUG INTO THE STOCK SOCKET

DRIVER SIDE LED PANELS

PASSENGER SIDE LED PANELS