

TAIL as TURN™

100% PLUG AND PLAY

CONVERTS TAIL LIGHT INTO TURN SIGNAL

OPERATION

This module will analyze two input signals, and output one combined signal. In recommended use, it analyzes the brake light and turn signal signals, and outputs one combined "high" signal, which will function as both the brake and turn signal.

SPECIFICATIONS

Maximum current: 1A

Maximum voltage: 20V

Minimum voltage: 8V

Input circuit leakage voltage: <1V

Forward Voltage: <.6V

Operating Temperature: -40 to 95 degrees C

PACKAGE CONTENTS

One pair (two) Tail as Turn™ Modules,
with OEM quality connectors

COMPATIBILITY

2003-2007 Infiniti G35 Coupe

2008-2013 Infiniti G37 Coupe

2014-2015 Infiniti Q60

Not compatible with sedan models.

INSTALLATION



Begin by removing the center trim piece. Pull upwards firmly, from one side to the other. Four clips hold the trim piece in place.



For G37: Remove the locking screw directly behind the lamp using your hands or a flathead screwdriver. (no screw on G35)



Pull the trunk liner carpet back and identify the tail light connector, which is white in color. Disconnect it by depressing the tab and pulling straight back and out.



Take one of the modules, plug one side into the tail lamp and the other side into the harness. The module should now be inline, between the tail lamp and factory connector.



Place resistor through the hole in the metal panel, just next to the factory connector. This will prevent the resistor from touching the carpet liner, as it may become warm in operation.

Place trunk liner back into position, and refasten screw if needed. Repeat for the other side, and fasten plastic trim piece back into place.

[Learn more about other automotive electrical parts by Diode Dynamics on our website.](#)