TAIL AS TURN

100% PLUG AND PLAY
CONVERTS TAIL LIGHT INTO TURN SIGNAL

This document provides basic information regarding the operation and installation of the Tail as Turn™ Module for the Infiniti G35/G37 Sedan and O40/O50. We encourage you to view the installation video online as well.

OPERATION

This module will analyze two input signals, and output one combined signal. In recommended use, it analyzes the brake light and turn signal signals, and outputs one combined "high" signal, which will function as both the brake and turn signal.

SPECIFICATIONS

Maximum current: 1A Maximum voltage: 20V Minimum voltage: 8V

Input circuit leakage voltage: <1V

Forward Voltage: <.6V

Operating Temperature: -40 to 95 degrees C

PACKAGE CONTENTS

One pair (two) Tail as Turn™ Modules, with OEM quality connectors

COMPATIBILITY

2003-2008 Infiniti G35 Sedan 2009-2014 Infiniti G37 Sedan 2014+ Infiniti Q40/Q50 Not compatible with coupe models.

INSTALLATION



Begin by removing the locking screws located directly behind the tail lamp using your hands or a flathead screwdriver.



Pull the trunk liner carpet back and identify the tail light connector, which is white in color. Disconnect it by depressing the tab and pulling straight back and out.



Take one of the modules, plug one side into the tail lamp and the other side into the harness. The module should now be inline, between the tail lamp and factory connector.



Place trunk liner back into position, and refasten the screws if needed.

Repeat for the other side.

When it comes to quality automotive electrical parts, Diode Dynamics is the brand you can depend on.