



## Parts Included

Number	Quantity	Item Description	Part#
1	2	Upper Control Arm	DK-811901-UCA
2	8	Polyurethane Bushing	DK-PB62002
3	2	Moog Ball Joint	K80811
4	2	Upgraded Dust Boot	TBJB-120UP
5	4	Inner Bushing Sleeve	DK-IB8702206
6	8	Bushing Washer	DK-811902-W
7	4	Grease Fitting	DK-ZF0890
8	2	Castle Nut	DK-CN42006
9	2	Cotter Pin	N/A
10	2	Zip Tie	N/A
11	2	Grease Pack	N/A
12	1	Sticker Pack	N/A

Carefully read all instructions prior to installation. This product must be installed by a qualified mechanic. Do not install with a coil spacer lift or shocks that over articulate the upper control arms.


### Pre Installation

Take your vehicle and park it on level ground applying your parking brake. Then place wheel chocks behind the rear wheels. Break loose the lug nuts and jack up the front of the truck until the wheels are off the ground. Place jack stands securely under each side of the frame rails. Slightly jack up the passenger side suspension to release tension off the upper arm. Remove the wheel and leave the jack under the lower arm.

### Removal

First unbolt the ABS line from the OEM upper arm. Next remove the cotter pin from the ball joint and loosen the castle nut until flush with bottom of threads.

**Figure 1**



With a hammer hit the side of the spindle until the ball joint breaks free. Now remove the OEM upper arm bolt and take off the arm. When removing the bolt you will need to bend part of the inner fender well. Be cautious not to pinch any wires in the process.


**Figure 2**



### Installation

First inspect the dust boot for tears or any imperfections on the arm before installing. This product can't be returned if it has been installed. Once the product has been inspected then thread in the grease fittings. Place a small amount of grease in-between the bushings and the bushing washers (DK-811902-W).

**Figure 3**



Bolt the Dirt King upper control arm to the frame as shown in the diagram. Torque the OEM upper arm nut to 85ft lbs with red Loctite applied to the threads. Now clean the taper of the spindle and insert the ball joint. Torque the castle nut to 81ft lbs and put the cotter pin through the ball joint. Next remove the factory steel bracket from the ABS line. Zip tie the line to the arm making sure it has proper clearances. Do a visual check making sure everything is installed correctly. You can now reinstall the tire. Repeat these steps to the opposite side.

### Alignment

Your vehicle will need to be aligned by a qualified shop. Our arms have increased castor built in to compensate for lifting the vehicle. The additional castor helps improve handling.

### Maintenance

Over time you will need to grease the bushings and ball joints. We recommend Super Lube Synthetic Grease for the bushings and heavy duty bearing grease for the ball joints.

**Disclaimer:** All products are intended for off-road use only. Our suspension systems are not to be modified from its original design in any way. Dirt King Fabrication is not responsible or liable for any accidents, injuries or deaths that may occur from use any products offered. Customer assumes all liability in assuring that parts are correctly installed and maintained.

THE FOLLOWING TERMS AND CONDITIONS APPLY TO ALL ORDERS PLACED WITH DIRT KING FABRICATION (WEBSITE, PHONE, FAX, MAIL, OR E-MAIL), EITHER DIRECTLY OR THROUGH A DEALER, CONSTITUTE THE ACKNOWLEDGEMENT AND ACCEPTANCE OF ALL THE CONDITIONS LISTED BELOW:

All products sold or manufactured by Dirt King Fabrication are intended for off-road use only. Our suspension systems are not to be modified from its original design in any way. Dirt King Fabrication is not responsible or liable for any accidents, injuries or deaths that may occur from the use of any products offered. Installation of this system will alter the center of gravity of the vehicle and may increase the risk of a roll over as compared to stock. It is the responsibility of the customer to check if any products will void their vehicles warranty before installation. Customer assumes all liability in assuring that parts are correctly installed and maintained. We are not responsible for products that don't fit correctly on a vehicle which has been in an accident. Consult your local laws before installing any products.

### **Shipping & Delivery**

At this time, Dirt King Fabrication ships merchandise to locations within the United States and U.S. territories, including Alaska, Hawaii, Puerto Rico, Guam, and the US Virgin Islands. Additionally, Dirt King Fabrication ships merchandise to Canada and Mexico, but not to other international locations. The risk of loss and title for all merchandise ordered pass to you when the merchandise is delivered to the shipping carrier.

### **Return Policy**

- Returns are only accepted within 30 days of original purchase.
- Original copy of invoice must be provided
- We are not responsible for shipping on returned products.
- 15% restocking fee will be charged on all returns.
- Deposits on custom orders or products built to order are non-refundable.
- Parts must be returned in the original package and condition as they were sent.
- No returns on items that have been damaged or installed.

### **Missing or Defective Parts**

Dirt King Fabrication goes through various stages of quality control to insure all parts are included and packaged correctly however there may be an instance where something is looked over. If there is a missing or defective part a claim must be made with Dirt King Fabrication within 60 days of original purchase. Photos of the box's exterior and contents must be e-mailed along with a description of what's missing or defective. If the box has any holes, tears or damage from shipping Dirt King Fabrication will determine if it's a claim that must be made with the shipping carrier. For defective parts photos need to be taken prior to install.

### **Core Charges**

- All cores must be original OEM parts. Remanufactured parts will not be accepted.
- All cores must be received within 30 days of purchase for full credit.
- Partial or no credit will be issued if core is damaged or modified in any way.

### **Maintenance**

After initial installation parts may make a clunking or creaking sound until the heims, uniballs, and bushings settle and are broken in. After a 50 mile break in period you must go through and re-torque all of the bolts. Over time you will also need to apply a Teflon based dry lubricant spray to the uniballs and heims. The bushings will need to be greased through the grease fittings. This will increase the lifespan of the joints and help prevent them from making noise. Inspect these items periodically for unusual wear and replace if necessary. Replacement is necessary if any of the heims, uniballs, or bushings has an excessive amount of movement.

## **Driver Side**

- Grease the outside of the polyurethane bushings.
- Upper arm bolt to the frame torqued down to 85ft lbs with red loctite.
- Ball joint nut torqued down to 81ft lbs with cotter pin inserted.
- ABS line zip tied to the tab on the upper arm.
- Tire re-installed and lug nuts torqued down.

## **Passenger Side**

- Grease the outside of the polyurethane bushings.
- Upper arm bolt to the frame torqued down to 85ft lbs with red loctite.
- Ball joint nut torqued down to 81ft lbs with cotter pin inserted.
- ABS line zip tied to the tab on the upper arm.
- Tire re-installed and lug nuts torqued down.

## **Both Sides**

- Do a visual check on all your work and set alignment.

**Disclaimer:** All products are intended for off-road use only. Our suspension systems are not to be modified from its original design in any way. Dirt King Fabrication is not responsible or liable for any accidents, injuries or deaths that may occur from use any products offered. Customer assumes all liability in assuring that parts are correctly installed and maintained.