


Installation Instructions

DODGE RAM PET DIVIDER
PDDGPU14**
FITS MODEL YEARS 2014 AND UP
EXTENDED AND QUAD CABS

Thank you for purchasing a Dirtydog 4x4 pet divider. Please read these instructions fully to familiarize yourself with the installation. Set aside 20 minutes for the first time you install your pet divider. No tools are required for installation.

Step 1: Slide the aluminum bar into the top row of loops of the pet divider.



Step 2: Slide the J Hooks over both ends of the aluminum bar. The hook should face towards the front of the divider.(The front side has the Dirtydog label on it)



Step 3: Install shock cord hooks on the bottom of the pet divider as shown



Step 4: Hang the pet divider off the top of the trim at the top of the door pillar behind the front seat as shown in the photos.



Step 5 Attach the bottom shock cords to the metal seat bracket at the floor. The outer seat brackets can be a little tricky to get connected as there is a piece of plastic trim in the way. You want to be sure you hook it to the metal bracket and not the plastic trim or seat fabric. Attach the outside hooks first then do the middle hooks second.



Passenger side outer seat bracket



Drivers side inner bracket.

Step 6: Attach the side straps to the grab handles at the doors as shown. Tighten equally on both side. Your pet divider is now installed.



Your net comes with a 3 year warranty against manufacturing defects. Cuts, abrasions, sun faded items are not covered under the warranty.