



Installation Instructions

DD-P-TJ87

Pet Divider for Jeep TJ/YJ 1987 -2006

T2PD87F1**

Thank you for purchasing a Dirtydog Jeep Netting system. Please fully read these instructions and familiarize yourself with the product. Your pet divider comes fully assembled. First time installation takes about 10 minutes.

Slide the female side of the side release buckle onto 6 of the 8 straps provided



Install the male side of the buckle to the 6 straps on the pet divider as shown below



Start with the 2 top loops. Install 2 straps around the top roll bar. Use a tape measure to center or you can do this by eye and adjust later. Continue to do the 3 straps down each side. If you have the full netting system you will install the plastic buckles on the existing straps. Save the straps if you ever wish to install the pet divider without the rest of the netting system. Do not tighten the adjustment buckles at this time.

Strap adjustment depends on front seat position. Put the drivers seat and the passenger seat in the position you normally keep them as well as the normal recline position you prefer.

Once this is done you may now reach behind and tighten the straps evenly so the netting stays centered between the seats. These can be easier to accomplish if you are sitting in the back seat.

Now all you need to do is unbuckle 1 or 2 buckles to let best friend in or out. We always recommend you use an approved safety restraint system for your pet.

Care and Maintenance

Proper care and maintenance of your webbing will extend the life of your webbing. This product is resistant to UV rays but like anything if left in the sun long enough it will break down over time. Wash your webbing from time to time with regular soap and water. Do not use any harsh chemicals on it.

Should you get any snags or rips in the webbing, we recommend using a match or a lighter to melt the frayed ends and stop the webbing from unraveling.