

INSTALL/REMOVAL INSTRUCTIONS: CONSOLE LID

ATTENTION: Refer to the appropriate shop manual for your vehicle to obtain specific service procedures for this part. If you do not have a service manual or lack the skill to install this part, it is recommended that you seek the services of a qualified technician. Pay special attention to all cautions and warnings included in the shop manual. Read and follow all instructions carefully.



REMOVAL/INSTALL OF CONSOLE LID (924-873) Chevrolet Silverado, GMC Sierra, Chevrolet Suburban, Chevrolet Tahoe, GMC Yukon 2013–2007

General Tech Tip:

- A plastic pry tool is useful. It will not easily damage delicate trim like a screwdriver or metal pry bar.

**PLEASE WEAR
SAFETY GLASSES!**

**Tools required for removal
and installation of console lid:**

- **Plastic pry tool (Dorman FG# 49051)
or flat-blade screwdriver**
- **Phillips screwdriver or power
screwdriver with Phillips attachment**



Removal Instructions

STEP 1: Lift the console lid to the up position.



INSTALL/REMOVAL INSTRUCTIONS: CONSOLE LID

ATTENTION: Refer to the appropriate shop manual for your vehicle to obtain specific service procedures for this part. If you do not have a service manual or lack the skill to install this part, it is recommended that you seek the services of a qualified technician. Pay special attention to all cautions and warnings included in the shop manual. Read and follow all instructions carefully.

STEP 2: Using a Phillips screwdriver or power screwdriver with Phillips attachment, remove the eight (8) screws on the underside of the console lid.



STEP 3: Using a plastic pry tool or flat-blade screwdriver, pry the underside of the console lid from the console.



INSTALL/REMOVAL INSTRUCTIONS: CONSOLE LID

ATTENTION: Refer to the appropriate shop manual for your vehicle to obtain specific service procedures for this part. If you do not have a service manual or lack the skill to install this part, it is recommended that you seek the services of a qualified technician. Pay special attention to all cautions and warnings included in the shop manual. Read and follow all instructions carefully.

STEP 4: Press the latch through the hole to remove the underside of the console lid from the console.



STEP 5: Using a Phillips screwdriver or power screwdriver with Phillips attachment, remove the four (4) screws to disconnect the top of the console lid from the center console.



INSTALL/REMOVAL INSTRUCTIONS: CONSOLE LID

ATTENTION: Refer to the appropriate shop manual for your vehicle to obtain specific service procedures for this part. If you do not have a service manual or lack the skill to install this part, it is recommended that you seek the services of a qualified technician. Pay special attention to all cautions and warnings included in the shop manual. Read and follow all instructions carefully.

Installation Instructions

STEP 1: Using a Phillips screwdriver or power screwdriver with Phillips attachment, attach the four (4) screws to connect the top of the console lid to the center console.



STEP 2: Press the underside of the console lid onto the console, making sure to feed the latch through the hole at the top.



INSTALL/REMOVAL INSTRUCTIONS: CONSOLE LID

ATTENTION: Refer to the appropriate shop manual for your vehicle to obtain specific service procedures for this part. If you do not have a service manual or lack the skill to install this part, it is recommended that you seek the services of a qualified technician. Pay special attention to all cautions and warnings included in the shop manual. Read and follow all instructions carefully.

STEP 3: Using a Phillips screwdriver or power screwdriver with Phillips attachment, attach the eight (8) screws to connect the underside of the console lid.



STEP 4: Verify that all of the hardware is secure and close the console lid to ensure that it latches properly.

