
DuPont® Multi-Use Performance Lubricant with Teflon® fluoropolymer

PRODUCT INFORMATION SHEET

High-performance general purpose lubricant with extreme corrosion and wear protection.



Product Description

- Features Teflon® fluoropolymer for enhanced wear protection and lubricity.
- Contains calcium sulfonate for improved corrosion protection.
- Designed for general purpose use.
- Water-repelling silicone-free formula protects against rust.
- Formulated with Teflon® fluoropolymer to deliver longer lubricant life, higher temperature stability, and better resistance to water and chemical contaminants.
- Provides extreme pressure wear protection.
- Resists extreme cold temperatures (to -30°F).

Ideal for use in applications where:

- Parts are exposed to extreme cold, hot or outdoor conditions.
- High moisture applications where other lubricants are quickly washed off.
- Parts need to be coated to prevent rust & corrosion.

Outstanding Features

- Exceptional anti-corrosion characteristics.
- Temperature Range: -30°F to +300°F.
- Provides superior anti-stick and EP properties.
- Outstanding adhesion and long lubricant life.
- Water repelling, protects against rust and corrosion.
- Contains no silicones.

Typical Applications

 Use on any moving part including: Hinges, Mechanical Chains, Springs, Cables, Rollup Doors, Sliding Tracks, Pivots, Cams and Pulleys. Threaded Parts, Conveyor Rollers, Wheels, Windows, Locks and Latches. Hitches, Winches, Ramps, Gates, Tools & Table Saws.

Directions For Use

- 1. Provide adequate ventilation. Do not use near open flames.
- 2. Shake or stir well before use to mix solids.
- 3. Spray or brush the product on uniformly.
- 4. For precision application use extension straw.



Properties of Material

Base Lubricant Performance Grade Lubricating Wax

PTFE (Polytetrafluoroethylene) Synthesized Calcium Stearate

Anti-wear Additives

Rust & Corrosion Inhibitors

Appearance Nearly clear

Flash Point Aerosol: not available

Bulk Liquid: not available

NFPA

Flammability Rating

3 (Highly Flammable)

 Part Number
 Container Size
 Part Number
 Container Size

 DM1204101
 4 oz. Net Wt. Bottle
 DM0024101
 1.5 lb (24 oz) Jug

 D00110101
 11 oz. Net Wt. Aerosol
 DM0096101
 6 lb (96 oz) Jug

 DM0614101
 14 oz. Net Wt. Aerosol
 DM0480101
 30 lb (480 oz) Pail

Storage - Keep away from heat, sparks and flame. Store in a well ventilated place.

Handling - For safe handling information, consult the SDS.

