



481, DURAGLOSS WAX ERASER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 05/28/2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : 481, DURAGLOSS WAX ERASER
Product code : Part# 481 4oz, 482 32oz

1.2. Relevant identified uses of the substance or mixture and uses advised against

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Not classified

2.2. Label elements

GHS-US labelling

No labelling applicable

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
1-propanol	(CAS No) 71-23-8	1 - 2	Flam. Liq. 2, H225 Eye Dam. 1, H318 STOT SE 3, H336
butyl glycoether	(CAS No) 111-76-2	1 - 2	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation : Remove the victim into fresh air. If not breathing give artificial respiration. Get immediate medical advice/attention. Allow victim to breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Wash with water and soap. If skin irritation or rash occurs: Get medical advice/attention. Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.

481, DURAGLOSS WAX ERASER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- First-aid measures after eye contact : Move victim away from exposure and into fresh air. Rinse immediately with plenty of water for 15 minutes. Get medical advice/attention. Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.
- First-aid measures after ingestion : Do not induce vomiting. Call a physician or poison control center immediately. Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : Not expected to present a significant hazard under anticipated conditions of normal use.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Carbon dioxide. Dry chemical powder. Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

- Firefighting instructions : Water can be used to keep exposed containers cool, to protect;. Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
- Protection during firefighting : Complete protective clothing. Self-contained breathing apparatus. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Absorb spill on vermiculite floor absorbent or other absorbent material.

6.1.1. For non-emergency personnel

- Protective equipment : Protective clothing. Protective goggles.
- Emergency procedures : Stop spill at source, prevent from spreading. If runoff occurs, notify authorities as required. Pump or vacuum transfer spilled product to clean containers for recovery. Absorb unrecoverable product. Transfer contaminated absorbent, material to containers for disposal. Close container tightly and dispose of properly. Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Use personal protective equipment as required. Self-contained breathing apparatus. Safety glasses. Protective gloves. Equip cleanup crew with proper protection.
- Emergency procedures : Stop leak if safe to do so. Ventilate area.

6.2. Environmental precautions

Notify authorities if product enters sewers or public waters. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Containers of this material may be hazardous when emptied. All hazard precautions give should be observed.
- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store in a well-ventilated place. Keep away from heat, sparks, and flames. Emptied containers may retain product residues. Precautions apply to emptied containers. Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use.

481, DURAGLOSS WAX ERASER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Incompatible products : Strong bases. Strong acids.
Incompatible materials : Sources of ignition. Direct sunlight.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

481, DURAGLOSS WAX ERASER	
ACGIH	Not applicable
OSHA	Not applicable

1-propanol (71-23-8)		
ACGIH	ACGIH TWA (ppm)	100 ppm
ACGIH	ACGIH STEL (ppm)	100 ppm
ACGIH	Remark (ACGIH)	Eye & URT irr
OSHA	OSHA PEL (TWA) (mg/m ³)	500 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	200 ppm

butyl glycolether (111-76-2)		
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	ACGIH STEL (ppm)	20 ppm
OSHA	Not applicable	

8.2. Exposure controls

Personal protective equipment : Avoid all unnecessary exposure.

Hand protection : Gloves. Wear protective gloves.

Eye protection : Chemical goggles or safety glasses.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Wear appropriate mask.

Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : Clear, colorless liquid.

Colour : Clear Liquid

Odour : Sweet

Odour threshold : No data available

pH : 6 - 7

Relative evaporation rate (butylacetate=1) : No data available

Melting point : 196.6 °F

Freezing point : No data available

Boiling point : 206.6 °F

Flash point : > 160 °F

Auto-ignition temperature : 775.4 °F

Decomposition temperature : No data available

Flammability (solid, gas) : No data available

Vapour pressure : 68 F @ 19.29 MBAR (14.5 mmHg)

Relative vapour density at 20 °C : No data available

Relative density : 0.98 F @ 68.0 F

481, DURAGLOSS WAX ERASER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Solubility	: Soluble in water. Water: Solubility in water of component(s) of the mixture : • 1-propanol: Complete • butyl glycoether: Complete
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions. Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

1-propanol (71-23-8)	
LD50 oral rat	> 2000 mg/kg (Rat)
LD50 dermal rabbit	4049 mg/kg (Rabbit)
LC50 inhalation rat (mg/l)	9.8 mg/l/4h (Rat)
ATE US (dermal)	4049.000 mg/kg bodyweight
ATE US (vapours)	9.800 mg/l/4h
ATE US (dust,mist)	9.800 mg/l/4h

butyl glycoether (111-76-2)	
LD50 oral rat	1746 mg/kg bodyweight (Rat; Equivalent or similar to OECD 401; Experimental value)
LD50 dermal rat	> 2000 mg/kg bodyweight (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)
LC50 inhalation rat (mg/l)	2.2 mg/l/4h (Rat; Experimental value)
LC50 inhalation rat (ppm)	450 ppm/4h (Rat; Experimental value)
ATE US (oral)	1746.000 mg/kg bodyweight
ATE US (dermal)	1100.000 mg/kg bodyweight
ATE US (gases)	450.000 ppmv/4h
ATE US (vapours)	2.200 mg/l/4h
ATE US (dust,mist)	2.200 mg/l/4h

Skin corrosion/irritation	: Not classified pH: 6 - 7
Serious eye damage/irritation	: Not classified pH: 6 - 7
Respiratory or skin sensitisation	: Not classified

481, DURAGLOSS WAX ERASER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

butyl glycoether (111-76-2)

IARC group : 3 - Not classifiable

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

Potential adverse human health effects and symptoms : Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

1-propanol (71-23-8)

LC50 fish 1 : 3200 mg/l 48 h; *Salmo gairdneri* (*Oncorhynchus mykiss*)

EC50 Daphnia 1 : 4415 mg/l (24 h; *Daphnia magna*)

EC50 other aquatic organisms 1 : 4168 mg/l (48 h; Protozoa)

LC50 fish 2 : 4480 mg/l (96 h; *Pimephales promelas*)

EC50 Daphnia 2 : 3644 mg/l (48 h; *Daphnia magna*)

TLM fish 1 : 200 - 500, *Gobio gobio*

TLM other aquatic organisms 1 : 100 - 1000, 96 h

Threshold limit algae 1 : 2000 mg/l (*Selenastrum capricornutum*)

Threshold limit algae 2 : 3100 mg/l (168 h; *Scenedesmus quadricauda*)

butyl glycoether (111-76-2)

LC50 fish 1 : 1474 ppm (96 h; *Oncorhynchus mykiss*)

EC50 Daphnia 1 : 1550 mg/l (48 h; *Daphnia magna*)

Threshold limit algae 1 : 911 mg/l (72 h; *Pseudokirchneriella subcapitata*)

Threshold limit algae 2 : 88 mg/l (72 h; *Pseudokirchneriella subcapitata*)

12.2. Persistence and degradability

481, DURAGLOSS WAX ERASER

Persistence and degradability : Not established.

1-propanol (71-23-8)

Persistence and degradability : Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions.

Biochemical oxygen demand (BOD) : 0.47 - 1.63 g O₂/g substance

Chemical oxygen demand (COD) : 2.23 g O₂/g substance

ThOD : 2.4 g O₂/g substance

BOD (% of ThOD) : 0.20 - 0.44 % ThOD

butyl glycoether (111-76-2)

Persistence and degradability : Readily biodegradable in water. Low potential for adsorption in soil. Photooxidation in the air.

12.3. Bioaccumulative potential

481, DURAGLOSS WAX ERASER

Bioaccumulative potential : Not established.

1-propanol (71-23-8)

Log Pow : 0.25 (Experimental value)

Bioaccumulative potential : Low potential for bioaccumulation (Log Kow < 4).

481, DURAGLOSS WAX ERASER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

butyl glycolether (111-76-2)	
Log Pow	0.81 (Test data; 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

12.4. Mobility in soil

1-propanol (71-23-8)	
Surface tension	0.024 N/m (20 °C)

butyl glycolether (111-76-2)	
Surface tension	0.065 N/m (20 °C; 003)

12.5. Other adverse effects

Effect on ozone layer :
Effect on the global warming : No known ecological damage caused by this product.
Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with DOT
Not regulated for transport

Additional information

Other information : No supplementary information available.

ADR

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

481, DURAGLOSS WAX ERASER	
Not listed on the United States TSCA (Toxic Substances Control Act) inventory	
1-propanol (71-23-8)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
butyl glycolether (111-76-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

15.2.2. National regulations

481, DURAGLOSS WAX ERASER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.3. US State regulations

1-propanol (71-23-8)

U.S. - New Jersey - Right to Know Hazardous Substance List

butyl glycoether (111-76-2)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Revision date : 05/28/2015

Other information : None.

Full text of H-phrases:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 4	Flammable liquids, Category 4
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour
H227	Combustible liquid
H302	Harmful if swallowed
H312	Harmful in contact with skin
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product