



Model 6126 TRAILER SPARE TIRE CARRIER

Model 6126 Trailer Spare Tire Carrier fits 3", 4", or 5" rectangular frame members 2" or 3" wide. Frame members wider than 3" require replacement of existing mounting bolts with bolts of appropriate length. Mounting on a round tongue requires modification to provide a rectangular mounting area. This trailer spare tire carrier is designed for 13" to 15" wheels with 5-hole rims (4 1/2" bolt circle) or 6-hole rims (5 1/2" bolt circle). **Maximum tire and wheel size of 15".**

INSTALLATION INSTRUCTIONS

Mount the spare tire carrier in a convenient location on the trailer frame or tongue using the clamp plate and 4 1/2" long bolts and nuts as shown. Place the spare tire in position on the mounting bolts and secure with 1/2" hex lug nuts as shown. To use with 6-hole rims, remove the mounting studs and re-install in the three unused holes.

REF. LETTER	PART NAME	PART NO.
A	Spare Tire Clamp	403482
B	1/2 - 13 x 4 1/2" Cap Screw (4)	207267
C	1/2" Lug Nut (3)	207272
D	1/2" Hex Nut (4)	207268
E	Spare Tire Carrier Assembly	303465



MADE IN
U.S.A.