



IN-LINE FUEL & OIL FILTERS

For use as pre or post filters for fuel and oil carbureted systems. Easily disassembled for inspection and cleaning.



PART NO.	DESCRIPTION		
AT230106ERL	6 AN Male		
AT230108ERL	8 AN Male		



FUEL FILTER PART NO.	OIL FILTER PART NO.	FITTINGS SIZE
AT230204ERL (85 micron)	AT230304ERL (140 micron)	4
AT230206ERL (85 micron)	AT230306ERL (140 micron)	6
AT230208ERL (85 micron)	AT230308ERL (140 micron)	8

Overall



SHUT-OFF VALVE

IDEAL FOR USE AS:

- 1. Emergency Fuel Shut Off Valve

- 300 PSI Max 2. Anti-Theft Device	No.	Size	Size	of Body	of Body
3. Drain Valve	AT230502ERL	3/8 Fem. NPT	-6 AN Bulkhead	2-3/4"	Hard Anodized Alum.
San Enter	AT230503ERL	3/8 Fem. NPT	-8 AN Bulkhead	2-3/4"	Hard Anodized Alum.
	AT230505ERL	1/2 Fem. NPT	-10 AN Bulkhead	2-3/4"	Hard Anodized Alum.

Inlet

Outlet