



WIRING KEY						
COLOR	COMPONENT	TYP. MAX CURRENT (A)				
RED	MAIN POWER	7.2				
BLK	GROUND	20A Limit				
BRN	PATTERN 1	.002				
ORG	PATTERN 2	.002				
YEL	ALLEY LEFT	.002				
GRN	ALLEY RIGHT	.002				
BLU	WORKLIGHT	.002				
VIO	PATTERN SELECT	.002				

REAR OF VEHICLE

SPECIFICATIONS

- 1. FLASH MODE: MAXIMUM 150 FPM
- 2. VOLTAGE (NOMINAL): 12-24 VDC
- 3. CURRENT (NOMINAL): 7.2 A @ 12 VDC
- 4. CONNECTION: 14, 18 AND 24 AWG WIRES 5. MOUNTING: 4-BOLT THROUGH MOUNTING KIT
- 6. BASE MATERIAL: ALUMINUM/POLYCARBONATE
- 7. LENS MATERIAL: POLYCARBONATE
- 8. WITH HANDHELD CONTROLLER: NO



NOTES:

- 1. CABLES AND WIRING NOT SHOWN
- 2. TOP VIEW: TOP LENSES NOT SHOWN FOR CLARITY
- 3. MOUNTING FEET: ADD 44mm TO OVERALL HEIGHT
- 4. THE LENGTH BETWEEN MOUNTING FEET IS ADJUSTABLE
- 5. CABLE LENGTH 4.5m[15.0'] FROM INTERNAL CONNECTOR
- 6. CABLE EXIT DRIVER'S SIDE
- 7. LED LENSES ARE COLORED FOR CLARITY ONLY
- 8. DIMENSIONS IN MILLIMETERS[INCHES(FOR REFERENCE)]

NON DISCLOSURE AGREEMENT

THIS DRAWING AND THE DESIGN IT DISCLOSES ARE THE PRIVATE PROPERTY OF ECCO. AND IS ISSUED IN CONFIDENCE FOR ENGINEERINGLINFORMATION ONLY. THE DRAWING SAID / ON DESIGN MAY HOT BE USED. COPIED, BEPRODUCED, OR OTHERWISE DISCLOSED THE OR AS A WHOLE TO OUTSIDESS OF USED FOR ANY OTHER PURPOSE WITHOUT THE PRIOR WRITTEN CONSENT OF ECCO. THE DRAWING IS SUBJECT TO RECALL AT ANY TIME. YOUR POSSESSION OF THIS DOCUMENT CONSTITUTES ACCEPTANCE OF THESE TERMS, © 2013 ECCO.

SCALE 1	1:8.5	APPROVALS	DATE				
CAD GENERATED DRAWING		DRAWN BY					
DO NOT MANUALLY UPDATE. MODEL REFERENCED:A		CHECKED					
TOLERANCES ARE IN INCHES, TOLERANCES A							
MILLIMETERS DECIMALS INCHES DECIMAL	ANGLES ± 0.5°			ASSY,SUB,LBR,12,54"/1.37M			
XX. ± 1.0mm XX.X ± 0.5mm XX ± 0.1 XXX ± 0.04 XXXX ± 0.02	FRACTIONS • 1/64			12-000		PRODUCT SERIES: 12 Series Lightbe	ar
THIRD ANGLE PROJ	ECTION			SIZE: A	DWG. NO.	2-00002-E	REV.
		Electronically Contro	olled Use Latest Copy	SHEET 1 OF 1	Project: LM13201	Date Created: 2016-06-25	1 A