	REVISION HISTORY
	REV. DESCRIPTION DATE
	A INITIAL RELEASE PER LM13201 2013-06-2
1219.2[48.0]	
	279.4[11.0]
WIRING KEY COLOR COMPONENT TYP. MAX CURRENT (A) CURRENT (A) RED MAIN POWER 11.6 BLK GROUND 20A Limit	SPECIFICATIONS 1. FLASH MODE: MAXIMUM 150 FPM 2. VOLTAGE (NOMINAL): 12-24 VDC 3. CURRENT (NOMINAL): 11.6 A @ 12 VDC 4. CONNECTION: 14, 18 AND 24 AWG WIRES 5. MOUNTING: 4-BOLT THROUGH MOUNTING KIT 6. BASE MATERIAL: ALUMINUM/POLYCARBONATE 7. LENS MATERIAL: POLYCARBONATE 8. WITH HANDHELD CONTROLLER: NO
	63.5[2.5] 107.3[4.2]
NOTES: 1. CABLES AND WIRING NOT SHOWN 2. TOP VIEW: TOP LENSES NOT SHOWN FOR CLARITY 3. MOUNTING FEET: ADD 44mm TO OVERALL HEIGHT 4. THE LENGTH BETWEEN MOUNTING FEET IS ADJUSTABLE 5. CABLE LENGTH - 4.5m[15.0'] FROM INTERNAL CONNECTOR 6. CABLE EXIT - DRIVER'S SIDE 7. LED LENSES ARE COLORED FOR CLARITY ONLY 8. DIMENSIONS IN MILLIMETERS[INCHES(FOR REFERENCE)] NON DISCLOSURE AGREEMENT NON DISCLOSURE AGREEMENT NON DISCLOSURE AGREEMENT ONLY THE DRAWING AND THE DESIGN TO RESIGN MAD YOF BE USED. CONFID HERMING BUBLICTO RECOMPORTIONS ON HIM DISCLOSURE AGREEMENT ONLY THE DRAWING AND THE DESIGN TO RESIGN MAD YOF BE USED. CONFID HERMING BUBLICATION PART OR AS A WHOLE TO OURDERESSON	DATE Customer PART NO. 12-00004-E PRODUCT SERIES: 12-00004-E 12-00004-E SIZE: DWG. NO. 12-00004-E REV. A Date Created: 2013-06-24