

REVISION HISTORY					
REV.	DESCRIPTION	DATE			
A	INITIAL RELEASE PER P13012	2020-01-31			

SPECIFICATIONS

- 1. FLASH MODE:
- 2. VOLTAGE (NOMINAL):
- 3. CURRENT (NOMINAL):
- 4. CONNECTION:
- 5. MOUNTING:
- 6. BASE MATERIAL:
- 7. LENS MATERIAL:
- 8. WITH HANDHELD CONTROLLER:

- 1. CABLES AND WIRES NOT SHOWN

- 2. TOP VIEW: TOP LENSES NOT SHOWN FOR CLARITY
 3. THE LENGTH BETWEEN MOUNTING FEET IS ADJUSTABLE
 4. CABLE LENGTH X.Xm[XX.X'] FROM INTERNAL CONNECTOR
- 5. CABLE EXIT DRIVER'S SIDE
- 6. LED LENSES ARE COLORED FOR CLARITY ONLY
- 7. DIMENSIONS IN MILLIMETERS [INCHES (FOR REFERENCE)]

NON DISCLOSURE AGREEMENT THIS DRAWING AND THE DESIGN IT DISCLOSES ARE THE PRIVATE PROPERTY OF ESG AND IS ISSUED IN CONFIDENCE FOR ENGINERING INFORMATION ONLY. THE DRAWING AND OR DESIGN MAY NOT BE USED, COPIED, REPRODUCED OR OTHERWISE DISCLOSED IN PART OR AS A WHOLE TO OUTSIDERS OR USED FOR ANY OTHER PURPOSE WITHOUT THE PRIOR WRITTEN CONSENT OF ESG. THE DRAWING IS SUBJECT TO RECAL AT ANY TIME. YOUR PROSSESION OF THIS DOCUMENT CONSTITUTES ACCEPTANCE OF THESE TERMS. ©

C.A.D. GENERATED. DR.AWING DR.AWING DN.OM TANUALLY UPDATE. MODEL. REFERENCED. CHECKED			SCALE 1:9		APPROVALS	DATE	
MODEL REFERENCED: CHECKED		DO NOT MANUALLY UPDATE. MODEL REFERENCED:			DRAWN BY		
TOLERANCES UNLESS OTHERWISE STATED ARE					CHECKED		İ
MILLIMITERS DECIMALS							İ
XX. ± 1.0mm XY. Y + 0.5 mm X.XX ± 0.04		MILLIMETERS DECIMALS		ANGLES ± 0.5°			
		$XX. \pm 1.0mm$ $XX.X \pm 0.5mm$					

FRACTIONS ± 1/64

Learn more about emergency and warning lighting on our website.

X.X ± 0.1 X.XX ± 0.04 X.XXx ± 0.02

LBR,12+,60"/1.52M,143-20006-12

DWG. NO. 12-20006-E SHEET 1 OF Electronically Controlled Use Latest Date Created: 2020-01-31 Project: P13012

REV. A