

REVISION HISTORY						
REV.	DESCRIPTION	DATE				
A	INITIAL RELEASE PER P13012	2020-08-31				

SPECIFICATIONS

- 1. FLASH MODE:
- 2. VOLTAGE (NOMINAL):
- 3. CURRENT (NOMINAL):
- 4. CONNECTION:
- 5. MOUNTING:
- 6. BASE MATERIAL:
- 7. LENS MATERIAL:
- 8. WITH HANDHELD CONTROLLER:

- 1. CABLES AND WIRES NOT SHOWN

- 2. TOP VIEW: TOP LENSES NOT SHOWN FOR CLARITY
 3. THE LENGTH BETWEEN MOUNTING FEET IS ADJUSTABLE
 4. CABLE LENGTH X.Xm[XX.X'] FROM INTERNAL CONNECTOR
- 5. CABLE EXIT DRIVER'S SIDE
- 6. LED LENSES ARE COLORED FOR CLARITY ONLY
- 7. DIMENSIONS IN MILLIMETERS [INCHES (FOR REFERENCE)]

NON DISCLOSURE AGREEMENT THIS DRAWING AND THE DESIGN IT DISCLOSES ARE THE PRIVATE PROPERTY OF ESG AND IS ISSUED IN CONFIDENCE FOR ENGINERING INFORMATION ONLY. THE DRAWING AND OR DESIGN MAY NOT BE USED, COPIED, REPRODUCED OR OTHERWISE DISCLOSED IN PART OR AS A WHOLE TO OUTSIDERS OR USED FOR ANY OTHER PURPOSE WITHOUT THE PRIOR WRITTEN CONSENT OF ESG. THE DRAWING IS SUBJECT TO RECAL AT ANY TIME. YOUR PROSSESION OF THIS DOCUMENT CONSTITUTES ACCEPTANCE OF THESE TERMS. ©

		SCALE 1:9	APPROVALS	DATE	ſ	
	CAD GENERATED DRAWING DO NOT MANUALLY UPDATE. MODEL REFERENCED: TOLERANIS ARE IN INCHES, AND MILLIMETERS TOLERANIS THES OTHERWIS STATED ARE:			DRAWN BY		ĺ
				CHECKED		ĺ
						ĺ
	$\begin{aligned} & \text{MILLIMETERS DECIMALS} \\ & & XX. \pm 1.0 \text{mm} \\ & & XX.X \pm 0.5 \text{mm} \end{aligned}$	INCHES DECIMALS $ \begin{array}{c} X.X\pm0.1 \\ X.XX\pm0.04 \\ X.XXX\pm0.02 \end{array} $	ANGLES ± 0.5°			ĺ
						ſ
			FRACTIONS ± 1/64			ŀ

Learn more about emergency and warning lighting on our website.

12+SERIES,54",20LED,8LED,SD REAR,12-24V

SIZE: A DWG. NO. 12-20601-E SHEET 1 OF Electronically Controlled Use Latest Project: P13012 Date Created: 2020-08-31

REV. A