

1. DIMENSIONS IN INCHES[MILLIMETERS(FOR REFERENCE)]

REVISION HISTORY						
REV.	DESCRIPTION	DATE				
F	REVISE PER LM10214	2011-09-16				
G	REVISE PER LM10214	2011-09-22				
Н	REVISE PER LM10214	2011-09-27				

SPECIFICATIONS

1. CERTIFICATIONS: **%**:

Note: Unique components, accessories, and hardware kits are not typically Included in the Product Certification Test Protocols. Unless otherwise Specified, the Product Certifications referred to herein are predicated upon the base product model configuration.

- 2. SOUND PRESSURE LEVEL: MIN 80 dB(A) @ 12 VDC @ 30cm (1ft)
- 3. VOLTAGE (NOMINAL): 12 to 48 VDC (dB INCREASES WITH VOLTAGE)
- 4. VOLTAGE (EXTREME): 9.0 to 56.0 VDC
- 5. CURRENT (PEAK): 0.1 A (@ 12 VDC NOMINAL)
- 6. POWER (MAXIMUM): 2.0 W (@ 12 VDC NOMINAL)
- 7. TEMPERATURE RANGE: -4°F (-20°C) TO 140°F (60°C)
- 8. FREQUENCY: 2900 Hz
- 9. CONNECTION: 1/4" MALE SPADE W / M3 0.5X6mm SCREWS
- 10. RECOMMENDED MOUNTING: FLANGE
- 11. HOUSING MATERIAL: ABS
- 12. PRODUCT WEIGHT: 0.1 LBS (0.05 Kg)

DISCLAIMER

Dimensions, Illustrations, Specifications, and Certifications contained in this document are typical of the actual product and are subject to change. ECCO Engineering does not maintain formal Design control of this product.

	SCALE 1:1			APPR	OVALS	DATE		
			ENERATED DRAWING		MDH	2011-09-26	7 5 4 4 1	
DO NOT MANUALLY UPDATE. MODEL REFERENCED:B		CHECKED	JDT	2011-09-26				
	TOLERANCES ARE IN INCHES, AND MILLIMETERS TOLERANCES ARE:		MECH. ENG.	NMT	2011-09-27			
	MILLIMETERS DECIMALS	INCHES DECIMALS	ANGLES ± 0.5°	ELEC. ENG.	JES	2011-09-27	AUDIBLE SIGNAL, FAST PULSE, 12-48V, SCR	EW
	XX. ± 1.0mm XX.X ± 0.5mm	X.X ± 0.1 X.XX ± 0.04 X.XXX ± 0.02	FRACTIONS	TEST ENG.	JRT	2011-09-27	CUSTOMER PART NO. PRODUCT SERIES:	
\dashv		THIRD ANGLE PROJECTION	± 1/64	SALES.	DEH	2011-09-27	201120 ASD	
D	THIRD ANGLE PROJECTION					SIZE: A DWG. NO. 201120 REV.		
ı,		W <u>_</u>					SHEET 1 OF 1 Project: 1862 Date Created: 2005-02-14	┥