



Additional Colors & Custom Configurations Available

BEACONS | MINIBARS | DIRECTIONALS | WORKLAMPS | UTILITY BARS | INTERIOR LIGHTING | BACK-UP ALARMS | CAMERA SYSTEMS

# LIGHTBARS

## 27 SERIES SAE Class I LED Lightbar

ECCO 27 Series Lightbars are versatile and powerful warning devices suitable for a range of vehicle types and duties. There are numerous options and lengths available and the lightbars can either be mounted permanently to the vehicle or mounted using an optional roof mounting kit. The 27 Series is suitable for many vehicle applications and features reflective LED modules, a durable aluminum chassis and polycarbonate lenses. Available in seven standard configurations, the 27 Series can be configured with either centrally controlled or independent flashing warning modules, offering a choice of either 3, 8, 12 or 22 LEDs per module, including dual color options. Stop-Tail-Indicator, worklamp/takedown and alley light modules are also available as well as an integrated Safety Director to control the rear warning modules independently.

### Features

- Medium-profile chassis
- Three, eight, 12 and 22 Reflective LED modules
- Integrated LED Safety Director™
- 19 flash patterns (independent flashing)
- 31 flash patterns (centrally controlled)
- Aluminum chassis, polycarbonate base and lens
- Magnet mount available for 22" lightbars (EZ2122MG)
- Range of strap mounting accessory kits
- Four color options - Amber, Blue, Red, and Clear
- Nine length options - 22", 36", 44", 47", 52", 58", 69", 80" and 91"
- Seven standard chassis configurations
- Customizable configuration available
- SAE J845 Class I, Cal. Title 13
- Height: 2.7", width: 12.2"
- Temperature Range: -22°F to +122°F (-30°C to +50°C)
- Warranty: 5 years

### Symbols / Features Guide

Independent Flashing (IF) indicates the lightbars modules have individual electronic circuits that control their operation. Centrally Controlled (CC) modules are operated via a centrally mounted control board.

#### Warning Modules - Independent Flashing

- REF12
- REF8
- REF3

#### Warning Modules - Centrally Controlled

- REF22 REF22 modules only are available with dual color warning capabilities.
- REF12
- REF8
- REF3 (AB, AW, BW, RB, RW)

#### Auxiliary Modules

- STI LED Stop-Tail-Indicator
- W LED Worklamps
- A LED Alley Lights
- REF Integrated LED Safety Director

Standard configurations shown on back.



# Standard Configurations

# 27 SERIES - LED Lightbar

BEACONS | MINIBARS | DIRECTIONALS | WORKLAMPS | UTILITY BARS | INTERIOR LIGHTING | BACK-UP ALARMS | CAMERA SYSTEMS

## LIGHTBARS

22" / 0.55m	#	V	A	LEDs	WL	AL	STI	Module Safety Director	🕒
	27-00001-E	12	2.0	4	-	-	-	-	5 years
	27-00002-E	12	3.0	6	-	-	-	-	5 years
	27-00003-E	12	4.0	8	-	-	-	-	5 years
47" / 1.19m	#	V	A	LEDs	WL	AL	STI	Module Safety Director	🕒
	27-00004-E	12	7.0	14	-	-	-	-	5 years
	27-00005-E	12	8.0	16	-	-	-	6	5 years
52" / 1.32m	#	V	A	LEDs	WL	AL	STI	Module Safety Director	🕒
	27-00006-E	12	7.0	16	-	-	-	10	5 years
	27-00007-E	12	12.0	10	2	-	2	-	5 years