

REVISION HISTORY		
REV.	DESCRIPTION	DATE
03	REVISED PER EL0045	2016-02-24
04	REVISED PER EL0045	2016-03-02
A	INITIAL RELEASE PER EL0045	2016-03-07



15'[4572] CORD W/ DUAL SWITCH LIGHTER ADAPTER

## SPECIFICATIONS

- CERTIFICATIONS: **CE**; ECE R10; IP-35C CATEGORY 2  
Note: Unique components, accessories, and hardware kits are not typically Included in the Product Certification Test Protocols. Unless otherwise Specified, the Product Certifications referred to herein are predicated upon the base product model configuration.
- FLASH MODE: DOUBLE : 75 ± 5 FLASHES PER MINUTE  
QUAD : 75 ± 5 FLASHES PER MINUTE  
QUINT : 75 ± 5 FLASHES PER MINUTE
- VOLTAGE (NOMINAL): 12 to 24 VDC
- VOLTAGE (EXTREME): 9.0 to 32.0 VDC
- CURRENT (PEAK): SEE CHART (@ 12 VDC NOMINAL)
- POWER (MAXIMUM): SEE CHART (@ 12 VDC NOMINAL)
- TEMPERATURE RANGE: -22°F (-30°C) TO 122°F (50°C)
- CONNECTION: 15' CORD W/DUAL SWITCH LIGHTER ADAPTER
- MOUNTING: VACUUM/MAGNET MOUNT
- BASE MATERIAL: POLYCARBONATE
- LENS MATERIAL: POLYCARBONATE
- PRODUCT WEIGHT: 4.93 LBS (2.22 Kg)

FGS PRODUCT CHART					
FGS NO.	COLOR	CURRENT (PEAK)	POWER (MAX)	SAE J845	CA. TITLE 13
5587CA-VM	CLEAR/AMBER	4.6A	58.9W	CLASS 1	CLASS B

- NOTES:
- ROHS COMPLIANT
  - DIMENSIONS IN INCHES[MILLIMETERS (FOR REFERENCE)]

SCALE 1:5		APPROVALS		DATE						
CAD GENERATED DRAWING DO NOT MANUALLY UPDATE. MODEL REFERENCED:01		DRAWN BY	ABD	2016-03-02						
TOLERANCES ARE IN INCHES, AND MILLIMETERS TOLERANCES UNLESS OTHERWISE STATED ARE:		CHECKED	MDH	2016-03-03						
<table border="1"> <tr> <th>MILLIMETERS DECIMALS</th> <th>INCHES DECIMALS</th> <th>ANGLES</th> </tr> <tr> <td>XX. ± 1.0mm XX.X ± 0.5mm</td> <td>X.X ± 0.1 X.XX ± 0.04 X.XXX ± 0.02</td> <td>± 0.5°  FRACTIONS ± 1/64</td> </tr> </table>		MILLIMETERS DECIMALS	INCHES DECIMALS	ANGLES		XX. ± 1.0mm XX.X ± 0.5mm	X.X ± 0.1 X.XX ± 0.04 X.XXX ± 0.02	± 0.5°  FRACTIONS ± 1/64	MECH. ENG.	JLA
MILLIMETERS DECIMALS	INCHES DECIMALS	ANGLES								
XX. ± 1.0mm XX.X ± 0.5mm	X.X ± 0.1 X.XX ± 0.04 X.XXX ± 0.02	± 0.5°  FRACTIONS ± 1/64								
		ELEC. ENG.	TJT	2016-03-02						
		TEST ENG.	JRT	2016-03-03						
		SALES.	LAT	2016-03-04						
THIRD ANGLE PROJECTION 				<b>LED MINIBAR, 8 HEAD, VAC-MAG, 12-24VDC</b> CUSTOMER PART NO. <b>SEE CHART</b>						
NON DISCLOSURE AGREEMENT				PRODUCT SERIES: <b>5580</b>						
THIS DRAWING AND THE DESIGN IT DISCLOSES ARE THE PRIVATE PROPERTY OF ESG AND IS ISSUED IN CONFIDENCE FOR ENGINEERING INFORMATION ONLY. THE DRAWING AND / OR DESIGN MAY NOT BE USED, COPIED, REPRODUCED, OR OTHERWISE DISCLOSED IN PART OR AS A WHOLE TO OUTSIDERS OR USED FOR ANY OTHER PURPOSE WITHOUT THE PRIOR WRITTEN CONSENT OF ESG. THE DRAWING IS SUBJECT TO RECALL AT ANY TIME. YOUR POSSESSION OF THIS DOCUMENT CONSTITUTES ACCEPTANCE OF THESE TERMS. © 2016 ECCO				SIZE: <b>A</b> DWG. NO. <b>5587CX-VM</b> REV. <b>A</b> Electronically Controlled Use Latest Copy SHEET 1 OF 1 Project: EL0045 Date Created: 2016-02-10						