



NOTES:
1. DIMENSIONS IN INCHES [MILLIMETERS (FOR REFERENCE)]

REVISION HISTORY		
REV.	DESCRIPTION	DATE
01	PRELIMINARY RELEASE PER P10017	2012-11-20
02	REVISED PER P10017	2012-11-27
A	INITIAL RELEASE PER P10017	2012-12-04

SPECIFICATIONS

- CERTIFICATIONS: **CE**; **UL**; e; SAE J994 (March 2009) TYPE C;
Note: Unique components, accessories, and hardware kits are not typically included in the Product Certification Test Protocols. Unless otherwise Specified, the Product Certifications referred to herein are predicated upon the base product model configuration.
- SOUND PRESSURE LEVEL: 97 ± 4 dB (A) @ 1.2m (4ft)
- VOLTAGE (NOMINAL): 12 to 36 VDC
- VOLTAGE (EXTREME): 9.0 to 42.0 VDC
- CURRENT (PEAK): 0.49 A (@ 12 VDC NOMINAL)
- POWER (MAXIMUM): 5.1 W (@ 12 VDC NOMINAL)
- TEMPERATURE RANGE: -40°F (-40°C) TO 185°F (85°C)
- FREQUENCY: 700 to 2800 Hz
- CONNECTION: 2-16 AWG WIRES
- RECOMMENDED MOUNTING: 5/16-18 UNC, GRADE 5 OR BETTER; 5/16" TYPE A, SERIES N OR W WASHER
- HOUSING MATERIAL: GLASS FILLED NYLON
- PRODUCT WEIGHT: 1.0 LBS (0.45 Kg)

SCALE 1:2		APPROVALS	DATE	 ALARM, BACK-UP, 97DBA, 12-36VDC, GFN
CAD GENERATED DRAWING DO NOT MANUALLY UPDATE. MODEL REFERENCED: A		DRAWN BY: SNS	2012-11-27	
TOLERANCES ARE IN INCHES, AND MILLIMETERS TOLERANCES ARE:		CHECKED: MDH	2012-11-28	
MILLIMETERS DECIMALS XX. ± 1.0mm XX.X ± 0.5mm	INCHES DECIMALS X.X ± 0.1 X.XX ± 0.04 X.XXX ± 0.02	MECH. ENG.: JLA	2012-11-27	
		ELEC. ENG.: JES	2012-11-27	
		TEST ENG.: JRT	2012-11-29	
		SALES: DEH	2012-11-28	
		CUSTOMER PART NO. 610N		PRODUCT SERIES: 600
THIRD ANGLE PROJECTION 		SIZE: A	DWG. NO. 610N	REV. A
Electronically Controlled Use Latest Copy		SHEET 1 OF 1	Project: P10017	Date Created: 2012-11-20