
	REVISION HISTORY						
REV.	DESCRIPTION	DATE					
В	REVISE PER P13008	2015-01-16					
С	REVISE PER EC4573	2017-06-28					
D	REVISE PER EP0026	2018-08-27					






15'[4572] CORD W/SINGLE SWITCH LIGHTER ADAPTER

SPECIFICATIONS

CERTIFICATIONS: **C€**; ECE R10; SAE SEE CHART

Note: Unique components, accessories, and hardware kits are not typically Included in the Product Certification Test Protocols. Unless otherwise Specified, the Product Certifications referred to herein are predicated upon the base product model configuration.

- 2. FLASH MODE: PULSE8: 80 ± 5 FLASHES PER MINUTE
- 3. VOLTAGE (NOMINAL): 12-24 VDC
- 4. VOLTAGE (EXTREME): 9-32 VDC
- 5. CURRENT (PEAK): 0.1A (@ 12 VDC NOMINAL)
- 6. POWER (MAXIMUM): 1.3W (@ 12 VDC NOMINAL)
- 7. TEMPERATURE RANGE: -22°F (-30°C) TO 122°F (50°C)
- 8. CONNECTION: 2 CONDUCTOR CABLE W/LIGHTER ADAPTER
- 9. MOUNTING: MAGNET MOUNT
- 10. BASE MATERIAL: GLASS FILLED NYLON
- 11. LENS MATERIAL: POLYCARBONATE
- 12. PRODUCT WEIGHT: 1.5 LBS (0.68 Kg)



FG PRODUCT CHART						
FG P/N	COLOR	SAE J845				
6465A-MG	AMBER	CLASS 3				
6465B-MG	BLUE	N/A				
6465C-MG	CLEAR	CLASS 3				
6465G-MG	GREEN	N/A				
6465R-MG	RED	CLASS 3				

NOTES:

- 1. ROHS COMPLIANT
- 2. DIMENSIONS IN INCHES[MILLIMETERS(FOR REFERENCE)]

NON DISCLOSURE AGREEMENT	
THIS DRAWING AND THE DESIGN IT DISCLOSES ARE THE PRIVATE PROPERTY OF ELECTRONIC CONTROLS CO. AND IS ISSUED I	N CONFIDENCE FOR
ENGINEERING INFORMATION ONLY. THE DRAWING AND / OR DESIGN MAY NOT BE USED, COPIED, REPRODUCED, OR OTHERWISE	DISCLOSED IN PART OR AS
A WHOLE TO OUTSIDERS OR USED FOR ANY OTHER PURPOSE WITHOUT THE PRIOR WRITTEN CONSENT OF ELECTRONIC CONTRO	
ISUBJECT TO RECALL AT ANY TIME, YOUR POSSESSION OF THIS DOCUMENT CONSTITUTES ACCEPTANCE OF THESE TERMS. © 2012 EL	ECTRONIC CONTROLS CO.

	SCALE 1:2.5		APP	ROVALS	DATE							
CAD GENERATED DRAWING				DRAWN BY ABD 2018-05-01				ECC				
	DO NOT MANUALLY UPDATE. MODEL REFERENCED: A			CHECKED	ABB	2018-05-02	(\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\					
Ī	TOLERANCES ARE IN INCHES, AND MILLIMETERS TOLERANCES UNLESS OTHERWISE STATED ARE:			MECH. ENG.	JLA	2018-05-01						
Ī	MILLIMETERS DECIMALS	ILLIMETERS DECIMALS INCHES DECIMALS ± 0.5°		ELEC. ENG.	GCJ	2018-05-02	LEC	D BEACON,360*	*,12-24 V	DC,MAG M	NT	
	XX. ± 1.0mm XX.X ± 0.5mm	X.X ± 0.1 X.XX ± 0.04	FRACTIONS	TEST ENG.	JRT	2018-05-02	CUSTOMER PA			PRODUCT SERIES:		
\dashv	TUI	X.XXX ± 0.02	THIRD ANGLE PROJECTION	± 1/64	SALES.	ARS	2018-05-02	SEE C	HAKI		6400	
24	(+) - - -					SIZE: A	DWG. NO.	6465X-	-MG	REV.		
Ο.			Electronically Controlled Use Latest Cop		lled Use Latest Copy	SHEET 1 OF	1 Project: P10015	Date Cre	eated: 2012-07-16			