
REVISION HISTORY			
REV.	DESCRIPTION	DATE	
В	REVISE PER P13008	2015-01-16	
С	REVISE PER EC4573	2017-06-28	
D	REVISE PER EP0026	2018-08-27	





(+)

15'[4572] CORD W/SINGLE SWITCH LIGHTER ADAPTER

SPECIFICATIONS

CERTIFICATIONS: (); ECE R10; SAE SEE CHART

Note: Unique components, accessories, and hardware kits are not typically Included in the Product Certification Test Protocols. Unless otherwise Specified, the Product Certifications referred to herein are predicated upon the base product model configuration.

2. FLASH MODE: PULSE8: 80 ± 5 FLASHES PER MINUTE

3. VOLTAGE (NOMINAL): 12-24 VDC

4. VOLTAGE (EXTREME): 9-32 VDC

5. CURRENT (PEAK): 0.1A (@ 12 VDC NOMINAL)

6. POWER (MAXIMUM): 1.3W (@ 12 VDC NOMINAL)

7. TEMPERATURE RANGE: -22°F (-30°C) TO 122°F (50°C)


8. CONNECTION: 2 CONDUCTOR CABLE W/LIGHTER ADAPTER


MOUNTING: MAGNET MOUNT

10. BASE MATERIAL: GLASS FILLED NYLON

11. LENS MATERIAL: POLYCARBONATE

12. PRODUCT WEIGHT: 1.5 LBS (0.68 Kg)





NOTES:

1. ROHS COMPLIANT

2. DIMENSIONS IN INCHES[MILLIMETERS(FOR REFERENCE)]

NON DISCLOSURE AGREEMENT	
S ARE THE PRIVATE PROPERTY OF ELECTRONIC CONTROLS CO. AND IS ISSUED IN CONF	ĪD

FINGINFERING INFORMATION ONLY. THE DRAWING AND / OR DESIGN MAY NOT BE USED. COPIED, REPRODUCED, OR OTHERWISE DISCLOSED IN PART OR AS A WHOLE TO OUTSIDERS OR USED FOR ANY OTHER PURPOSE WITHOUT THE PRIOR WRITTEN CONSENT OF ELECTRONIC CONTROLS CO. THE DRAWING IS SUBJECT TO RECALL AT ANY TIME. YOUR POSSESSION OF THIS DOCUMENT CONSTITUTES ACCEPTANCE OF THESE TERMS. © 2012 ELECTRONIC CONTROLS.

